EDDL
Duesseldorf


-

LOWW
Wien Schwechat

2024/03/19 0740Z

EDDL AMETU **T852** SULUS **UZ650** VEMUT **UZ37** BUDEX LOWW

430.55 nm / 797.37 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EDDL APT	–	51.28942 6.76664	0 ft 0 m	–	Duesseldorf
AMETU FIX	–	50.83306 8.96444	31,200 ft 9,510 m	87	–
ARNIX FIX	T852 AWY-HI	50.52889 9.56167	35,000 ft 10,668 m	29	–
TIKNI FIX	T852 AWY-HI	50.40972 9.87333	35,000 ft 10,668 m	13	–
SULUS FIX	T852 AWY-HI	50.07528 10.72889	35,000 ft 10,668 m	38	–
ERETO FIX	UZ650 AWY-HI	49.93111 11.40833	35,000 ft 10,668 m	27	–
NOGRA FIX	UZ650 AWY-HI	49.92056 11.82167	35,000 ft 10,668 m	15	–
TIPAM FIX	UZ650 AWY-HI	49.90972 12.16500	35,000 ft 10,668 m	13	–
VEMUT FIX	UZ650 AWY-HI	49.78861 12.45389	35,000 ft 10,668 m	13	–
VADOV FIX	UZ37 AWY-HI	49.12980 13.97304	25,700 ft 7,833 m	71	–
BUDEX FIX	UZ37 AWY-HI	48.94833 14.33603	23,500 ft 7,163 m	17	–
LOWW APT	–	48.11007 16.56964	0 ft 0 m	102	Wien Schwechat

EDDL

Region: GERMANY - CIVIL
Timezone: EUROPE/BERLIN
Runways: 2

Elevation: 145 ft / 44 m
Location: 51.289400 6.766620
Magnetic Var: 2.658 E

METAR

EDDL 190720Z AUTO 14005KT CAVOK 10/07 Q1019 NOSIG

TAF

TAF EDDL 190500Z 1906/2012 15006KT 9999 SCT040 BECMG 1910/1913 22006KT BECMG 1917/1920 15006KT BECMG 2009/2012 23

Frequencies

REC - 123.77 MHz - ATIS
GND - 121.90 MHz - GROUND
GND - 121.67 MHz - GROUND
TWR - 124.35 MHz - TOWER
APP - 121.35 MHz - LANGEN RADAR
APP - 128.65 MHz - DUSSELDORF DIRECTOR
CLD - 121.77 MHz - CLEARANCE DELIVERY
GND - 121.60 MHz - GROUND
TWR - 118.30 MHz - TOWER
APP - 128.55 MHz - LANGEN RADAR
APP - 128.50 MHz - LANGEN RADAR
DEP - 133.77 MHz - DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05R	148 ft 45 m	9,851 ft 3,003 m	52.68 50.02	CONCRETE	984 ft 300 m	659 ft 201 m
23L	148 ft 45 m	9,851 ft 3,003 m	232.71 230.05	CONCRETE	984 ft 300 m	702 ft 214 m
05L	148 ft 45 m	8,866 ft 2,702 m	52.68 50.02	CONCRETE	994 ft 303 m	906 ft 276 m
23R	148 ft 45 m	8,866 ft 2,702 m	232.70 230.04	CONCRETE	971 ft 296 m	928 ft 283 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05L	LOC-ILS	IDNE	110.95 MHz	18 nm 33 km	52.69 50.03	-	145 ft 145 m
05R	LOC-ILS	IDSE	110.15 MHz	18 nm 33 km	52.70 50.04	-	145 ft 145 m
23L	LOC-ILS	IDSW	109.90 MHz	18 nm 33 km	232.70 230.04	-	145 ft 145 m
23R	LOC-ILS	IDNW	109.30 MHz	18 nm 33 km	232.69 230.03	-	145 ft 145 m
05L	GS	IDNE	110.95 MHz	10 nm 19 km	52.69 50.03	3.00	145 ft 145 m
05R	GS	IDSE	110.15 MHz	10 nm 19 km	52.70 50.04	3.00	145 ft 145 m
23L	GS	IDSW	109.90 MHz	10 nm 19 km	232.70 230.04	3.00	145 ft 145 m
23R	GS	IDNW	109.30 MHz	10 nm 19 km	232.69 230.03	3.00	145 ft 145 m

LOWW

Region: AUSTRIA
Timezone: EUROPE/VIENNA
Runways: 2

Elevation: 600 ft / 183 m
Location: 48.110100 16.569600
Magnetic Var: 4.997 E

METAR

LOWW 190720Z 34005KT 320V020 CAVOK 02/M03 Q1022 NOSIG

TAF

TAF LOWW 190515Z 1906/2012 35007KT CAVOK TX12/2012Z TNM02/2004Z BECMG 1916/1918 VRB03KT

Frequencies

REC - 122.95 MHz - ATIS ARRIVAL
TWR - 124.47 MHz - WIEN TOWER
TWR - 121.20 MHz - WIEN TOWER
GND - 121.77 MHz - WIEN GROUND
CLD - 122.12 MHz - CLEARANCE DELIVERY
APP - 125.17 MHz - WIEN RADAR
APP - 118.77 MHz - WIEN RADAR
APP - 119.80 MHz - WIEN DIRECTOR
REC - 118.52 MHz - WIEN INFORMATION

REC - 121.72 MHz - ATIS DEPARTURE
TWR - 123.80 MHz - WIEN TOWER
TWR - 119.40 MHz - WIEN TOWER
GND - 121.60 MHz - WIEN GROUND
APP - 134.67 MHz - WIEN RADAR
APP - 129.05 MHz - WIEN RADAR
APP - 136.25 MHz - WIEN RADAR
APP - 134.12 MHz - WIEN DIRECTOR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16	148 ft	11,822 ft	164.23	ASPHALT	0 ft	197 ft
	45 m	3,604 m	159.23		0 m	60 m
34	148 ft	11,822 ft	344.24	ASPHALT	0 ft	194 ft
	45 m	3,604 m	339.24		0 m	59 m
11	148 ft	11,495 ft	115.99	ASPHALT	0 ft	174 ft
	45 m	3,504 m	110.99		0 m	53 m
29	148 ft	11,495 ft	296.02	ASPHALT	0 ft	187 ft
	45 m	3,504 m	291.02		0 m	57 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11	DME	OEW	110.30 MHz	18 nm	-	-	593 ft
				33 km	-		593 m
16	DME	OEZ	108.50 MHz	18 nm	-	-	610 ft
				33 km	-		610 m
29	DME	OEX	109.55 MHz	18 nm	-	-	624 ft
				33 km	-		624 m
34	DME	OEN	108.10 MHz	18 nm	-	-	572 ft
				33 km	-		572 m
11	LOC-ILS	OEW	110.30 MHz	18 nm	116.04	-	600 ft
				33 km	111.04		600 m
16	LOC-ILS	OEZ	108.50 MHz	18 nm	164.25	-	600 ft
				33 km	159.26		600 m
29	LOC-ILS	OEX	109.55 MHz	18 nm	295.98	-	600 ft
				33 km	290.98		600 m
34	LOC-ILS	OEN	108.10 MHz	18 nm	344.21	-	600 ft
				33 km	339.22		600 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11	GS	OEW	110.30 MHz	10 nm 19 km	116.02 111.02	3.10	593 ft 593 m
16	GS	OEZ	108.50 MHz	10 nm 19 km	164.47 159.48	3.00	610 ft 610 m
29	GS	OEX	109.55 MHz	10 nm 19 km	296.02 291.02	3.00	624 ft 624 m
34	GS	OEN	108.10 MHz	10 nm 19 km	344.47 339.48	3.00	604 ft 604 m