KJFK
John F Kennedy Intl


-

CYYZ
Toronto/pearson Intl

2024/03/30 0355Z

KJFK CERUP ZYZ CYYZ

317.81 nm / 588.58 km



Notes

Generated

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KJFK APT	–	40.62537 −73.77035	0 ft 0 m	–	–
CERUP FIX	–	42.24186 −76.75981	0 ft 0 m	165	–
ZYZ NDB	–	43.61950 −79.54778	0 ft 0 m	147	QUEENSWAY(TORONTO NDB
CYYZ APT	–	43.65859 −79.62155	0 ft 0 m	3	–

KJFK

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 4

Elevation: 12 ft / 4 m
Location: 40.640100 -73.776500
Magnetic Var: 12.823 W

METAR

KJFK 300251Z 31016G26KT 10SM FEW050 06/M04 A2980 RMK AO2 PK WND 33036/0200 SLP091 T00561044 51018

TAF

TAF AMD KJFK 300231Z 3003/3106 31016G27KT P6SM FEW050 FM301800 26015G22KT P6SM SCT040 SCT250 FM310300 27008KT P6S

Frequencies

REC - 115.40 MHz - D-ATIS
REC - 128.72 MHz - D-ATIS
CLD - 135.05 MHz - CLEARANCE DELIVERY
GND - 121.65 MHz - KENNEDY GROUND
TWR - 123.90 MHz - KENNEDY TOWER
APP - 128.12 MHz - NEW YORK APPROACH
APP - 123.70 MHz - NEW YORK APPROACH
APP - 132.40 MHz - NEW YORK APPROACH
DEP - 135.90 MHz - NEW YORK DEPARTURE
DEP - 124.75 MHz - NEW YORK DEPARTURE

REC - 117.70 MHz - D-ATIS
COM - 122.95 MHz - UNICOM
GND - 121.90 MHz - KENNEDY GROUND
TWR - 119.10 MHz - KENNEDY TOWER
APP - 125.70 MHz - NEW YORK APPROACH
APP - 118.40 MHz - NEW YORK APPROACH
APP - 126.80 MHz - NEW YORK APPROACH
APP - 134.35 MHz - NEW YORK APPROACH
DEP - 123.70 MHz - NEW YORK DEPARTURE
DEP - 134.35 MHz - NEW YORK DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
13R	200 ft 61 m	14,526 ft 4,428 m	120.83 133.65	CONCRETE	2,057 ft 627 m	390 ft 119 m
31L	200 ft 61 m	14,526 ft 4,428 m	300.86 313.68	CONCRETE	3,271 ft 997 m	495 ft 151 m
13L	151 ft 46 m	10,010 ft 3,051 m	120.85 133.68	CONCRETE	912 ft 278 m	387 ft 118 m
31R	151 ft 46 m	10,010 ft 3,051 m	300.87 313.70	CONCRETE	1,037 ft 316 m	177 ft 54 m
04R	200 ft 61 m	8,407 ft 2,562 m	30.67 43.49	ASPHALT	0 ft 0 m	440 ft 134 m
22L	200 ft 61 m	8,407 ft 2,562 m	210.68 223.50	ASPHALT	0 ft 0 m	505 ft 154 m
04L	200 ft 61 m	12,091 ft 3,685 m	30.67 43.49	CONCRETE	459 ft 140 m	200 ft 61 m
22R	200 ft 61 m	12,091 ft 3,685 m	210.68 223.50	CONCRETE	3,425 ft 1,044 m	407 ft 124 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04L	DME	IHIQ	110.90 MHz	18 nm 33 km	- -	-	13 ft 13 m
04R	DME	IJFK	109.50 MHz	18 nm 33 km	- -	-	13 ft 13 m
13L	DME	ITLK	111.50 MHz	18 nm 33 km	- -	-	13 ft 13 m
22L	DME	IIWY	110.90 MHz	18 nm 33 km	- -	-	13 ft 13 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
22R	DME	IJOC	109.50 MHz	18 nm 33 km	– –	–	13 ft 13 m
31R	DME	IRTH	111.50 MHz	18 nm 33 km	– –	–	13 ft 13 m
04L	LOC-ILS	IHIQ	110.90 MHz	18 nm 33 km	30.68 43.50	–	12 ft 12 m
04R	LOC-ILS	IJFK	109.50 MHz	18 nm 33 km	30.67 43.49	–	12 ft 12 m
13L	LOC-ILS	ITLK	111.50 MHz	18 nm 33 km	120.87 133.69	–	12 ft 12 m
22L	LOC-ILS	IIWY	110.90 MHz	18 nm 33 km	210.67 223.49	–	12 ft 12 m
22R	LOC-ILS	IJOC	109.50 MHz	18 nm 33 km	210.68 223.50	–	12 ft 12 m
31L	LOC-ILS	IMOH	111.35 MHz	18 nm 33 km	300.84 313.66	–	12 ft 12 m
31R	LOC-ILS	IRTH	111.50 MHz	18 nm 33 km	300.87 313.69	–	12 ft 12 m
04L	GS	IHIQ	110.90 MHz	10 nm 19 km	30.68 43.50	3.00	12 ft 12 m
04R	GS	IJFK	109.50 MHz	10 nm 19 km	30.67 43.49	3.00	12 ft 12 m
13L	GS	ITLK	111.50 MHz	10 nm 19 km	120.87 133.69	3.00	12 ft 12 m
22L	GS	IIWY	110.90 MHz	10 nm 19 km	210.67 223.49	3.00	12 ft 12 m
22R	GS	IJOC	109.50 MHz	10 nm 19 km	210.68 223.50	3.00	12 ft 12 m
31L	GS	IMOH	111.35 MHz	10 nm 19 km	300.84 313.66	3.00	12 ft 12 m
31R	GS	IRTH	111.50 MHz	10 nm 19 km	300.87 313.69	3.00	12 ft 12 m

CYYZ

Region: CANADA
Timezone: AMERICA/TORONTO
Runways: 5

Elevation: 564 ft / 172 m
Location: 43.676100 -79.627700
Magnetic Var: 10.261 W

METAR

CYYZ 300300Z 28005KT 15SM FEW035 M00/M05 A2998 RMK SC2 SLP160

TAF

TAF TAF CYYZ 300240Z 3003/3106 30010KT P6SM FEW030 BECMG 3004/3006 30005KT FM301200 33005KT P6SM FEW015 BECMG 301

Frequencies

TWR - 118.35 MHz - TORONTO TOWER
GND - 119.10 MHz - TORONTO GROUND
GND - 121.90 MHz - TORONTO GROUND
REC - 133.10 MHz - ATIS
APP - 132.80 MHz - TORONTO APPROACH
APP - 125.40 MHz - TORONTO APPROACH
DEP - 127.57 MHz - TORONTO DEPARTURE

TWR - 118.70 MHz - TORONTO TOWER
GND - 121.65 MHz - TORONTO GROUND
REC - 120.82 MHz - ATIS
CLD - 121.30 MHz - CLEARANCE DELIVERY
APP - 124.47 MHz - TORONTO APPROACH
APP - 123.27 MHz - LONDON RADIO
DEP - 128.80 MHz - TORONTO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06L	197 ft 60 m	9,707 ft 2,959 m	46.43 56.69	ASPHALT	0 ft 0 m	131 ft 40 m
24R	197 ft 60 m	9,707 ft 2,959 m	226.45 236.71	ASPHALT	194 ft 59 m	98 ft 30 m
06R	197 ft 60 m	9,007 ft 2,745 m	46.43 56.69	ASPHALT	0 ft 0 m	95 ft 29 m
24L	197 ft 60 m	9,007 ft 2,745 m	226.45 236.71	ASPHALT	0 ft 0 m	95 ft 29 m
05	197 ft 60 m	11,128 ft 3,392 m	46.39 56.65	ASPHALT	141 ft 43 m	141 ft 43 m
23	197 ft 60 m	11,128 ft 3,392 m	226.41 236.68	ASPHALT	492 ft 150 m	141 ft 43 m
15L	197 ft 60 m	11,061 ft 3,372 m	136.64 146.90	ASPHALT	0 ft 0 m	92 ft 28 m
33R	197 ft 60 m	11,061 ft 3,372 m	316.66 326.92	ASPHALT	0 ft 0 m	89 ft 27 m
15R	197 ft 60 m	9,097 ft 2,773 m	136.62 146.88	ASPHALT	597 ft 182 m	0 ft 0 m
33L	197 ft 60 m	9,097 ft 2,773 m	316.64 326.90	ASPHALT	591 ft 180 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24L	DME	IIDP	111.95 MHz	18 nm 33 km	- -	-	568 ft 568 m
24R	DME	INV	109.30 MHz	18 nm 33 km	- -	-	546 ft 546 m
05	LOC-ILS	ITX	109.70 MHz	18 nm 33 km	46.40 56.66	-	564 ft 564 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	LOC-ILS	IJS	109.10 MHz	18 nm 33 km	46.44 56.70	-	564 ft 564 m
06R	LOC-ILS	ICV	111.95 MHz	18 nm 33 km	46.44 56.70	-	564 ft 564 m
15L	LOC-ILS	IRW	110.50 MHz	18 nm 33 km	136.65 146.91	-	564 ft 564 m
15R	LOC-ILS	ILP	110.95 MHz	18 nm 33 km	136.63 146.89	-	564 ft 564 m
23	LOC-ILS	IYZ	111.50 MHz	18 nm 33 km	226.40 236.66	-	564 ft 564 m
24L	LOC-ILS	IDP	111.95 MHz	18 nm 33 km	226.44 236.70	-	564 ft 564 m
24R	LOC-ILS	INV	109.30 MHz	18 nm 33 km	226.44 236.70	-	564 ft 564 m
33L	LOC-ILS	ITO	110.95 MHz	18 nm 33 km	316.63 326.89	-	564 ft 564 m
33R	LOC-ILS	ILE	110.30 MHz	18 nm 33 km	316.65 326.91	-	564 ft 564 m
05	GS	ITX	109.70 MHz	10 nm 19 km	46.40 56.66	3.00	564 ft 564 m
06L	GS	IJS	109.10 MHz	10 nm 19 km	46.44 56.70	3.00	564 ft 564 m
06R	GS	ICV	111.95 MHz	10 nm 19 km	46.44 56.70	3.00	564 ft 564 m
15L	GS	IRW	110.50 MHz	10 nm 19 km	136.65 146.91	3.00	564 ft 564 m
15R	GS	ILP	110.95 MHz	10 nm 19 km	136.63 146.89	3.00	564 ft 564 m
23	GS	IYZ	111.50 MHz	10 nm 19 km	226.40 236.66	3.00	564 ft 564 m
24L	GS	IIDP	111.95 MHz	10 nm 19 km	226.44 236.70	3.00	564 ft 564 m
24R	GS	INV	109.30 MHz	10 nm 19 km	226.44 236.70	3.00	564 ft 564 m
33L	GS	ITO	110.95 MHz	10 nm 19 km	316.63 326.89	3.00	564 ft 564 m
33R	GS	ILE	110.30 MHz	10 nm 19 km	316.65 326.91	3.00	564 ft 564 m