LIRP
PISA


-

LIRN
Naples Capodichino

2024/03/29 0444Z

LIRP BOL **UL995** PEMAR LIRN

241.47 nm / 447.21 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: no
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LIRP APT	–	43.68388 10.39272	0 ft 0 m	–	PISA
BOL VOR	–	42.61833 12.04861	31,000 ft 9,449 m	96	BOLSENA VORTAC
TIBER FIX	UL995 AWY-HI	42.24889 12.59889	23,900 ft 7,285 m	32	–
PEMAR FIX	UL995 AWY-HI	42.02972 12.91944	19,700 ft 6,005 m	19	–
LIRN APT	–	40.88603 14.29078	0 ft 0 m	92	Naples Capodichino

LIRP

Region: ITALY
Timezone: EUROPE/ROME
Runways: 2

Elevation: 4 ft / 1 m
Location: 43.682800 10.395600
Magnetic Var: 3.396 E

METAR

LIRP 290415Z 13004KT CAVOK 11/11 Q1011 NOSIG

TAF

TAF LIRP 282300Z 2900/2924 11007KT 9999 FEW020 SCT070 TEMPO 2902/2909 VRB03KT SCT030 SCT070 BECMG 2907/2909 17012

Frequencies

GND - 121.60 MHz - PISA GROUND
TWR - 119.10 MHz - PISA TOWER
APP - 122.10 MHz - PISA APPROACH

TWR - 122.10 MHz - PISA TOWER
APP - 124.27 MHz - PISA APPROACH
APP - 126.07 MHz - PISA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04R	148 ft 45 m	9,825 ft 2,995 m	36.73 33.33	ASPHALT	463 ft 141 m	0 ft 0 m
22L	148 ft 45 m	9,825 ft 2,995 m	216.74 213.35	ASPHALT	833 ft 254 m	190 ft 58 m
04L	148 ft 45 m	8,984 ft 2,738 m	36.71 33.32	ASPHALT	791 ft 241 m	0 ft 0 m
22R	148 ft 45 m	8,984 ft 2,738 m	216.73 213.33	ASPHALT	0 ft 0 m	190 ft 58 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04R	LOC-ILS	IPI	109.70 MHz	18 nm 33 km	36.76 33.37	-	7 ft 7 m
04R	GS	IPI	109.70 MHz	10 nm 19 km	37.45 34.05	3.00	3 ft 3 m

LIRN

Region: ITALY
Timezone: EUROPE/ROME
Runways: 1

Elevation: 292 ft / 89 m
Location: 40.886000 14.290800
Magnetic Var: 3.950 E

METAR

LIRN 290420Z 13003KT 090V160 CAVOK 15/11 Q1016 NOSIG

TAF

TAF LIRN 282300Z 2900/2924 17010KT 9999 FEW030 BECMG 2902/2904 VRB05KT BECMG 2910/2912 18012KT BECMG 2916/2918 VR

Frequencies

APP - 124.35 MHz - NAPOLI APPROACH
TWR - 118.50 MHz - NAPOLI TOWER
REC - 135.97 MHz - ATIS

APP - 120.95 MHz - NAPOLI APPROACH
GND - 121.90 MHz - NAPOLI GROUND

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	148 ft 45 m	8,630 ft 2,630 m	58.04 54.09	ASPHALT	1,312 ft 400 m	217 ft 66 m
24	148 ft 45 m	8,630 ft 2,630 m	238.05 234.10	ASPHALT	607 ft 185 m	230 ft 70 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	DME	NPC	110.15 MHz	25 nm 46 km	- -	-	294 ft 294 m
24	DME	INPL	109.50 MHz	25 nm 46 km	- -	-	250 ft 250 m
06	LOC-ILS	NPC	110.15 MHz	18 nm 33 km	58.08 54.13	-	292 ft 292 m
24	LOC-ILS	INPL	109.50 MHz	18 nm 33 km	238.03 234.08	-	288 ft 288 m
24	LOC-ILS	INP	109.50 MHz	18 nm 33 km	238.08 234.13	-	292 ft 292 m
24	GS	INPL	109.50 MHz	10 nm 19 km	238.06 234.11	3.33	250 ft 250 m
24	GS	INP	109.50 MHz	10 nm 19 km	238.08 234.13	3.33	292 ft 292 m