MYGF
Grand Bahama Intl


-

MYNN
Nassau Intl

2024/03/19 0518Z

MYGF LAUTH **BR65V** PEACH MYNN

112.92 nm / 209.12 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: yes
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
MYGF APT	–	26.55868 -78.69555	0 ft 0 m	–	Grand Bahama Intl
LAUTH FIX	–	26.12666 -78.34300	11,400 ft 3,475 m	32	–
SYDNY FIX	BR65V AWY-LO	25.56259 -77.88107	8,200 ft 2,499 m	42	–
PEACH FIX	BR65V AWY-LO	25.42963 -77.77301	6,100 ft 1,859 m	9	–
MYNN APT	–	25.03860 -77.46662	0 ft 0 m	28	Nassau Intl

MYGF

Region: BAHAMAS
Timezone: AMERICA/NASSAU
Runways: 1

Elevation: 6 ft / 2 m
Location: 26.558700 -78.695500
Magnetic Var: 8.274 W

METAR

MYGF 190500Z AUTO 24004KT 210V270 //// R24///// // BKN250/// 26/21 A2986

TAF

TAF MYGF 182332Z 1900/1924 24016G26KT 5000 TSRA SCT014 SCT030 BKN080

Frequencies

GND - 121.70 MHz -
APP - 126.50 MHz -

TWR - 118.50 MHz -
COM - 123.00 MHz - UNICOM

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	151 ft 46 m	11,016 ft 3,358 m	60.89 69.17	ASPHALT	0 ft 0 m	239 ft 73 m
24	151 ft 46 m	11,016 ft 3,358 m	240.91 249.18	ASPHALT	0 ft 0 m	226 ft 69 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	LOC-ILS	IZFP	109.70 MHz	18 nm 33 km	60.91 69.18	-	7 ft 7 m
06	GS	IZFP	109.70 MHz	10 nm 19 km	61.80 70.08	3.00	7 ft 7 m

MYNN

Region: BAHAMAS
Timezone: AMERICA/NASSAU
Runways: 2

Elevation: 16 ft / 5 m
Location: 25.038700 -77.466800
Magnetic Var: 8.768 W

METAR

MYNN 190500Z 26004KT 9999 FEW020CB 24/23 A2993

TAF

TAF MYNN 182332Z 1900/1924 23006KT 9999 CAVOK FM191000 30014KT 9000 SHRA SCT016 SCT030 BKN050 FM192100 36015KT 999

Frequencies

REC - 118.70 MHz - ATIS
GND - 121.70 MHz - NASSAU GROUND
APP - 121.00 MHz - NASSAU APPROACH
DEP - 121.00 MHz - NASSAU DEPARTURE

CLD - 118.30 MHz - NASSAU CLEARANCE
TWR - 119.50 MHz - NASSAU TOWER
APP - 125.30 MHz - NASSAU APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
14	151 ft 46 m	11,136 ft 3,394 m	134.80 143.57	CONCRETE	210 ft 64 m	0 ft 0 m
32	151 ft 46 m	11,136 ft 3,394 m	314.81 323.58	CONCRETE	0 ft 0 m	0 ft 0 m
10	151 ft 46 m	8,282 ft 2,524 m	89.67 98.44	CONCRETE	0 ft 0 m	0 ft 0 m
28	151 ft 46 m	8,282 ft 2,524 m	269.68 278.45	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
14	LOC-ILS	IZQA	110.10 MHz	18 nm 33 km	134.83 143.60	-	7 ft 7 m
14	GS	IZQA	110.10 MHz	10 nm 19 km	135.66 144.43	3.00	8 ft 8 m