UIII
Irkutsk


-

UIBB
BRATSK

2024/03/28 0929Z

UIII SENAR **G490** LIDKA UIBB

263.96 nm / 488.85 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: yes
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
UIII APT	-	52.26644 104.39569	0 ft 0 m	-	Irkutsk
SENAR FIX	-	53.92167 103.49167	34,100 ft 10,394 m	104	-
DOMOR FIX	G490 AWY-LO	54.31167 103.22500	28,700 ft 8,748 m	25	-
LIDKA FIX	G490 AWY-LO	55.46056 102.38833	12,700 ft 3,871 m	74	-
UIBB APT	-	56.37016 101.70295	0 ft 0 m	59	BRATSK

UIII

Region: RUSSIA
Timezone: ASIA/IRKUTSK
Runways: 1

Elevation: 1,669 ft / 509 m
Location: 52.267100 104.395000
Magnetic Var: 4.142 W

METAR

UIII 280900Z 31005MPS 280V340 CAVOK M00/M10 Q1011 R30/150060 NOSIG RMK QFE714/0952

TAF

TAF UIII 280800Z 2809/2909 30003MPS 9999 BKN040CB TEMPO 2814/2903 0500 +SHSN VV004

Frequencies

APP - 125.20 MHz - IRKUTSK APPROACH
GND - 121.70 MHz - IRKUTSK GROUND
COM - 119.30 MHz - IRKUTSK RADAR

REC - 124.85 MHz - IRKUTSK ATIS
TWR - 118.10 MHz - IRKUTSK TOWER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
12	148 ft 45 m	11,686 ft 3,562 m	113.50 117.64	CONCRETE	1,312 ft 400 m	0 ft 0 m
30	148 ft 45 m	11,686 ft 3,562 m	293.53 297.68	CONCRETE	1,309 ft 399 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12	LOC-ILS	ICN	111.30 MHz	18 nm 33 km	113.52 117.66	-	1,669 ft 1,669 m
30	LOC-ILS	IIR	110.30 MHz	18 nm 33 km	293.52 297.66	-	1,669 ft 1,669 m
12	GS	ICN	111.30 MHz	10 nm 19 km	113.52 117.66	3.30	1,669 ft 1,669 m
30	GS	IIR	110.30 MHz	10 nm 19 km	293.52 297.66	3.30	1,669 ft 1,669 m

UIBB

Region: RUSSIA
Timezone: ASIA/IRKUTSK
Runways: 1

Elevation: 1,610 ft / 491 m
Location: 56.370600 101.699000
Magnetic Var: 2.503 W

METAR

UIBB 280900Z VRB01MPS 9999 SCT039 M06/M15 Q1013 R30/450150 NOSIG RMK QFE717/0956

TAF

TAF UIBB 280800Z 2809/2909 12002G07MPS 9999 SCT020CB

Frequencies

REC - 127.20 MHz - BRATSK ATIS
TWR - 124.00 MHz - BRATSK TOWER
APP - 124.00 MHz - BRATSK APPROACH
TWR - 121.80 MHz - BRATSK TOWER
APP - 118.10 MHz - BRATSK APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
12	148 ft 45 m	10,379 ft 3,164 m	114.89 117.40	CONCRETE	0 ft 0 m	0 ft 0 m
30	148 ft 45 m	10,379 ft 3,164 m	294.93 297.44	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
30	LOC-ILS	IBS	110.30 MHz	18 nm 33 km	294.92 297.42	-	1,610 ft 1,610 m
30	GS	IBS	110.30 MHz	10 nm 19 km	294.92 297.42	3.00	1,610 ft 1,610 m