


2024/05/12 0619Z

EBBR VABIK EGLL

189.61 nm / 351.15 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EBBR	-	50.89995	0 ft	-	Brussels Airport
APT	-	4.49281	0 m		
VABIK	-	51.24639	19,900 ft	96	-
FIX	-	2.00000	6,066 m		
EGLL	-	51.47122	0 ft	93	London Heathrow
APT	-	-0.46098	0 m		

EBBR

Region: BELGIUM
Timezone: EUROPE/BRUSSELS
Runways: 3

Elevation: 184 ft / 56 m
Location: 50.899900 4.492770
Magnetic Var: 2.003 E

METAR

EBBR 120550Z 08003KT CAVOK 14/11 Q1016 NOSIG

TAF

TAF TAF EBBR 120510Z 1206/1312 10006KT CAVOK PROB40 TEMPO 1215/1221 VRB15G30KT 3500 TSRAGR BKN050CB PROB30 TEMPO 1

Frequencies

REC - 121.75 MHz - ATIS DEP
COM - 130.55 MHz - ABELAG UNICOM
GND - 118.05 MHz -
GND - 121.87 MHz -
TWR - 120.77 MHz -
APP - 120.10 MHz -
DEP - 126.62 MHz -

REC - 132.47 MHz - ATIS ARR
CLD - 121.95 MHz - CLNC DEL
GND - 121.70 MHz -
TWR - 118.60 MHz -
APP - 118.25 MHz -
APP - 122.50 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07L	148 ft	11,917 ft	65.37	ASPHALT	843 ft	72 ft
	45 m	3,632 m	63.37		257 m	22 m
25R	148 ft	11,917 ft	245.41	ASPHALT	981 ft	0 ft
	45 m	3,632 m	243.41		299 m	0 m
07R	148 ft	10,522 ft	69.88	ASPHALT	407 ft	0 ft
	45 m	3,207 m	67.87		124 m	0 m
25L	148 ft	10,522 ft	249.91	ASPHALT	0 ft	13 ft
	45 m	3,207 m	247.91		0 m	4 m
01	164 ft	9,810 ft	14.44	ASPHALT	157 ft	0 ft
	50 m	2,990 m	12.44		48 m	0 m
19	164 ft	9,810 ft	194.45	ASPHALT	722 ft	43 ft
	50 m	2,990 m	192.45		220 m	13 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01	DME	IBX	109.90 MHz	18 nm	-	-	184 ft
				33 km	-		184 m
19	DME	IBM	111.15 MHz	18 nm	-	-	184 ft
				33 km	-		184 m
25R	DME	IBR	108.90 MHz	18 nm	-	-	184 ft
				33 km	-		184 m
01	LOC-ILS	IBX	109.90 MHz	18 nm	14.45	-	184 ft
				33 km	12.45		184 m
19	LOC-ILS	IBM	111.15 MHz	18 nm	194.45	-	184 ft
				33 km	192.45		184 m
25L	LOC-ILS	IBL	110.35 MHz	18 nm	249.89	-	184 ft
				33 km	247.89		184 m
25R	LOC-ILS	IBR	108.90 MHz	18 nm	245.39	-	184 ft
				33 km	243.39		184 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01	GS	IBX	109.90 MHz	10 nm	14.45	3.00	184 ft
				19 km	12.45		184 m
19	GS	IBM	111.15 MHz	10 nm	194.45	3.00	184 ft
				19 km	192.45		184 m
25L	GS	IBL	110.35 MHz	10 nm	249.89	3.00	184 ft
				19 km	247.89		184 m
25R	GS	IBR	108.90 MHz	10 nm	245.39	3.00	184 ft
				19 km	243.39		184 m

EGLL

Region: UNITED KINGDOM
Timezone: EUROPE/LONDON
Runways: 2

Elevation: 83 ft / 25 m
Location: 51.471200 -0.460881
Magnetic Var: 0.378 E

METAR

EGLL 120550Z AUTO 06003KT 9999 NCD 13/11 Q1014 NOSIG

TAF

TAF EGLL 120455Z 1206/1312 08007KT 9999 FEW045 PROB30 TEMPO 1212/1218 3000 +SHRA BECMG 1214/1217 19010KT PROB40 1.

Frequencies

REC - 128.07 MHz - HEATHROW INFORMATION	REC - 121.92 MHz - HEATHROW INFORMATION
CLD - 121.97 MHz - HEATHROW DELIVERY	GND - 121.70 MHz - HEATHROW GROUND
GND - 121.85 MHz - HEATHROW GROUND	GND - 121.90 MHz - HEATHROW GROUND
TWR - 118.50 MHz - HEATHROW TOWER	TWR - 118.70 MHz - HEATHROW TOWER
TWR - 124.47 MHz - HEATHROW TOWER	APP - 119.72 MHz - HEATHROW DIRECTOR
APP - 120.40 MHz - HEATHROW DIRECTOR	APP - 134.97 MHz - HEATHROW DIRECTOR
APP - 125.62 MHz - HEATHROW RADAR	APP - 127.52 MHz - HEATHROW RADAR
DEP - 120.52 MHz - HEATHROW DEPARTURE	

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09L	164 ft	12,770 ft	89.66	ASPHALT	1,007 ft	0 ft
	50 m	3,892 m	89.28		307 m	0 m
27R	164 ft	12,770 ft	269.70	ASPHALT	0 ft	177 ft
	50 m	3,892 m	269.33		0 m	54 m
09R	164 ft	11,975 ft	89.68	ASPHALT	1,004 ft	0 ft
	50 m	3,650 m	89.30		306 m	0 m
27L	164 ft	11,975 ft	269.72	ASPHALT	0 ft	95 ft
	50 m	3,650 m	269.34		0 m	29 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	IAA	110.30 MHz	18 nm	-	-	89 ft
				33 km	-		89 m
09R	DME	IBB	109.50 MHz	18 nm	-	-	84 ft
				33 km	-		84 m
27L	DME	ILL	109.50 MHz	18 nm	-	-	84 ft
				33 km	-		84 m
27R	DME	IRR	110.30 MHz	18 nm	-	-	89 ft
				33 km	-		89 m
09L	LOC-ILS	IAA	110.30 MHz	18 nm	89.68	-	83 ft
				33 km	89.30		83 m
09R	LOC-ILS	IBB	109.50 MHz	18 nm	89.70	-	83 ft
				33 km	89.32		83 m
27L	LOC-ILS	ILL	109.50 MHz	18 nm	269.70	-	83 ft
				33 km	269.32		83 m
27R	LOC-ILS	IRR	110.30 MHz	18 nm	269.68	-	83 ft
				33 km	269.30		83 m
09L	GS	IAA	110.30 MHz	10 nm	89.68	3.00	83 ft
				19 km	89.30		83 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09R	GS	IBB	109.50 MHz	10 nm	89.70	3.00	83 ft
				19 km	89.32		83 m
27L	GS	ILL	109.50 MHz	10 nm	269.70	3.00	83 ft
				19 km	269.32		83 m
27R	GS	IRR	110.30 MHz	10 nm	269.68	3.00	83 ft
				19 km	269.30		83 m