LIPZ
Venezia Tessera


-

OMDB
DUBAI INTL

2024/03/29 0540Z

LIPZ NAKIT **UL615** VEBAR **L615** DOLAP **UL615** LUKOV **UL610** VADEN **L615** BKZ **A4** BUK **T32** GEM **W73** DYB **UP975** NOLDO **P975** SIDAD **R784** IMDAT **B416** ORSAR OMDB

2426.59 nm / 4494.05 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 300kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes

- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LIPZ APT	–	45.50479 12.34969	0 ft 0 m	–	Venezia Tessera
NAKIT FIX	–	45.18806 13.44778	17,800 ft 5,425 m	50	–
OBALA FIX	UL615 AWY-HI	44.92028 14.97250	35,000 ft 10,668 m	66	–
KOREX FIX	UL615 AWY-HI	44.77111 15.76917	35,000 ft 10,668 m	35	–
SUDIM FIX	UL615 AWY-HI	44.66722 16.30556	35,000 ft 10,668 m	23	–
BOSNA FIX	UL615 AWY-HI	44.37056 17.75972	35,000 ft 10,668 m	64	–
VEBAR FIX	UL615 AWY-HI	44.13581 19.17942	35,000 ft 10,668 m	62	–
KUKUN FIX	L615 AWY-LO	44.07083 19.56028	35,000 ft 10,668 m	16	–
KOSIV FIX	L615 AWY-LO	44.02686 19.80908	35,000 ft 10,668 m	11	–
GONAR FIX	L615 AWY-LO	43.85467 20.75311	35,000 ft 10,668 m	42	–
RAVAK FIX	L615 AWY-LO	43.68742 21.62697	35,000 ft 10,668 m	39	–
OBLAK FIX	L615 AWY-LO	43.48683 22.36394	35,000 ft 10,668 m	34	–
DOLAP FIX	L615 AWY-LO	43.37417 22.76833	35,000 ft 10,668 m	18	–
RESLA FIX	UL615 AWY-HI	43.32861 23.31278	35,000 ft 10,668 m	23	–
LUKOV FIX	UL615 AWY-HI	43.28472 23.80611	35,000 ft 10,668 m	21	–
GOL VOR	UL610 AWY-HI	43.09500 24.22056	35,000 ft 10,668 m	21	GOLYAMA VOR-DME
VADEN FIX	UL610 AWY-HI	42.06556 27.21611	35,000 ft 10,668 m	146	–
BKZ VOR	L615 AWY-LO	41.12694 29.14278	35,000 ft 10,668 m	103	BEYKOZ VOR-DME
GAYEM FIX	A4 AWY-LO	41.04694 29.62861	35,000 ft 10,668 m	22	–
ERSEN FIX	A4 AWY-LO	40.86556 30.66611	35,000 ft 10,668 m	48	–
YAVRU FIX	A4 AWY-LO	40.58222 31.83278	35,000 ft 10,668 m	55	–
SALGO FIX	A4 AWY-LO	40.47500 32.20000	35,000 ft 10,668 m	17	–
BUK NDB	A4 AWY-LO	40.24167 33.10472	35,000 ft 10,668 m	43	CUBUK NDB
GEM VOR	T32 AWY-LO	39.15528 36.02917	35,000 ft 10,668 m	150	GEMEREK VOR-DME
ERH NDB	W73 AWY-LO	38.46333 38.11222	35,000 ft 10,668 m	105	ERHAC NDB
ASKER FIX	W73 AWY-LO	38.27389 38.77472	35,000 ft 10,668 m	33	–
DYB	W73	37.87083	35,000 ft	71	DIYARBAKIR NDB

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
NDB	AWY-LO	40.20861	10,668 m		
LESRI	UP975	37.07222	35,000 ft	68	-
FIX	AWY-HI	41.23028	10,668 m		
KANOK	UP975	36.56515	35,000 ft	37	-
FIX	AWY-HI	41.68316	10,668 m		
GETID	UP975	35.26406	35,000 ft	99	-
FIX	AWY-HI	42.93303	10,668 m		
LOPAS	UP975	34.50096	35,000 ft	57	-
FIX	AWY-HI	43.64288	10,668 m		
SOGUM	UP975	34.20333	35,000 ft	22	-
FIX	AWY-HI	43.91500	10,668 m		
ETBOM	UP975	33.36048	35,000 ft	67	-
FIX	AWY-HI	44.79793	10,668 m		
NOLDO	UP975	32.82567	35,000 ft	42	-
FIX	AWY-HI	45.35817	10,668 m		
DENKI	P975	32.37457	35,000 ft	36	-
FIX	AWY-LO	45.85599	10,668 m		
ILMAP	P975	31.35917	35,000 ft	82	-
FIX	AWY-LO	46.95056	10,668 m		
SIDAD	P975	29.87528	35,000 ft	119	-
FIX	AWY-LO	48.49556	10,668 m		
DESLU	R784	29.46667	35,000 ft	37	-
FIX	AWY-LO	49.03056	10,668 m		
NANPI	R784	29.08250	35,000 ft	34	-
FIX	AWY-LO	49.53250	10,668 m		
OBMOR	R784	28.97056	35,000 ft	9	-
FIX	AWY-LO	49.67000	10,668 m		
ALNIN	R784	28.67861	35,000 ft	25	-
FIX	AWY-LO	50.02722	10,668 m		
IMDAT	R784	27.68333	35,000 ft	85	-
FIX	AWY-LO	51.18333	10,668 m		
DURSI	B416	27.20528	35,000 ft	53	-
FIX	AWY-LO	52.02889	10,668 m		
EGMID	B416	26.60417	31,700 ft	66	-
FIX	AWY-LO	53.06694	9,662 m		
ORSAR	B416	26.07500	19,400 ft	57	-
FIX	AWY-LO	53.95833	5,913 m		
OMDB	-	25.25491	0 ft	90	DUBAI INTL
APT	-	55.36426	0 m		

LIPZ

Region: ITALY
Timezone: EUROPE/ROME
Runways: 2

Elevation: 4 ft / 1 m
Location: 45.504800 12.349700
Magnetic Var: 3.892 E

METAR

LIPZ 290520Z 05006KT 7000 SCT010 BKN065 08/08 Q1012 NOSIG

TAF

TAF LIPZ 282300Z 2900/3006 03008KT CAVOK PROB30 TEMPO 2900/2906 2000 BCFG

Frequencies

REC - 128.65 MHz - ATIS
TWR - 120.20 MHz - VENEZIA TOWER
APP - 118.25 MHz - VENEZIA APPROACH

GND - 121.70 MHz - VENEZIA GROUND
APP - 118.90 MHz - VENEZIA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04R	148 ft 45 m	10,836 ft 3,303 m	42.03 38.14	ASPHALT	0 ft 0 m	0 ft 0 m
22L	148 ft 45 m	10,836 ft 3,303 m	222.05 218.16	ASPHALT	0 ft 0 m	0 ft 0 m
04L	148 ft 45 m	9,129 ft 2,782 m	42.03 38.14	ASPHALT	318 ft 97 m	0 ft 0 m
22R	148 ft 45 m	9,129 ft 2,782 m	222.05 218.15	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04R	DME	VTS	109.95 MHz	18 nm 33 km	- -	-	26 ft 26 m
04R	LOC-ILS	VTS	109.95 MHz	18 nm 33 km	42.04 38.15	-	4 ft 4 m
04R	GS	VTS	109.95 MHz	10 nm 19 km	42.04 38.15	3.00	4 ft 4 m

OMDB

Region: UNITED ARAB EMIRATES
Timezone: ASIA/DUBAI
Runways: 2

Elevation: 62 ft / 19 m
Location: 25.251100 55.371100
Magnetic Var: 2.347 E

METAR

OMDB 290500Z 27014KT 9999 FEW035 24/15 Q1013 NOSIG

TAF

TAF TAF OMDB 282300Z 2900/3006 27012KT CAVOK PROB30 2900/2905 20008KT BECMG 2917/2919 19005KT

Frequencies

REC - 126.27 MHz - ATIS ARRIVAL
TWR - 126.77 MHz - DUBAI TOWER
TWR - 118.75 MHz - DUBAI TOWER
GND - 118.35 MHz - DUBAI GROUND
GND - 121.65 MHz - DUBAI GROUND
APP - 122.50 MHz - MINHAD APPROACH
APP - 120.25 MHz - DUBAI ARRIVAL
APP - 124.90 MHz - DUBAI ARRIVAL
DEP - 121.02 MHz - DUBAI DEPARTURE
DEP - 120.25 MHz - DUBAI DEPARTURE
APP - 126.02 MHz - DUBAI RADAR

REC - 131.70 MHz - ATIS DEPARTURE
TWR - 119.55 MHz - DUBAI TOWER
TWR - 119.05 MHz - DUBAI TOWER
GND - 118.85 MHz - DUBAI GROUND
CLD - 120.35 MHz - CLEARANCE DELIVERY
APP - 126.02 MHz - MINHAD APPROACH
APP - 124.45 MHz - DUBAI ARRIVAL
DEP - 126.02 MHz - DUBAI DEPARTURE
DEP - 126.20 MHz - DUBAI DEPARTURE
APP - 120.40 MHz - DUBAI RADAR
APP - 127.90 MHz - DUBAI DIRECT

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
12R	200 ft 61 m	14,604 ft 4,452 m	121.53 119.18	ASPHALT	2,352 ft 717 m	771 ft 235 m
30L	200 ft 61 m	14,604 ft 4,452 m	301.54 299.20	ASPHALT	436 ft 133 m	0 ft 0 m
12L	200 ft 61 m	14,289 ft 4,355 m	121.48 119.14	ASPHALT	1,496 ft 456 m	381 ft 116 m
30R	200 ft 61 m	14,289 ft 4,355 m	301.50 299.15	ASPHALT	991 ft 302 m	377 ft 115 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12L	DME	IDBL	110.10 MHz	18 nm 33 km	- -	-	62 ft 62 m
30L	DME	IDBW	111.30 MHz	18 nm 33 km	- -	-	41 ft 41 m
30R	DME	IDBR	110.90 MHz	18 nm 33 km	- -	-	44 ft 44 m
12L	LOC-ILS	IDBL	110.10 MHz	18 nm 33 km	121.49 119.14	-	62 ft 62 m
12R	LOC-ILS	IDBE	109.50 MHz	18 nm 33 km	121.54 119.19	-	62 ft 62 m
30L	LOC-ILS	IDBW	111.30 MHz	18 nm 33 km	301.54 299.19	-	62 ft 62 m
30R	LOC-ILS	IDBR	110.90 MHz	18 nm 33 km	301.49 299.14	-	62 ft 62 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12L	GS	IDBL	110.10 MHz	10 nm	121.49	3.00	62 ft
				19 km	119.14		62 m
12R	GS	IDBE	109.50 MHz	10 nm	121.54	3.00	62 ft
				19 km	119.19		62 m
30L	GS	IDBW	111.30 MHz	10 nm	301.54	3.00	62 ft
				19 km	299.19		62 m
30R	GS	IDBR	110.90 MHz	10 nm	301.49	3.00	62 ft
				19 km	299.14		62 m