KDFW
Dallas Fort Worth Intl


-

KPBI
Palm Beach Intl

2024/03/19 1314Z

KDFW FUZ **J58** HRV **Q105** REDFN **Q100** SRQ **J616** MMDUQ KPBI

985.35 nm / 1824.87 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: no
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KDFW APT	–	32.89711 -97.03655	0 ft 0 m	–	Dallas Fort Worth Intl
FUZ VOR	–	32.88944 -97.17942	2,500 ft 762 m	7	RANGER VORTAC
MOTLY FIX	J58 AWY-HI	31.84276 -94.10538	35,000 ft 10,668 m	168	–
NOBBL FIX	J58 AWY-HI	31.74819 -93.81977	35,000 ft 10,668 m	15	–
TURNN FIX	J58 AWY-HI	31.67524 -93.63906	35,000 ft 10,668 m	10	–
FOSIN FIX	J58 AWY-HI	31.51350 -93.19466	35,000 ft 10,668 m	24	–
AEX VOR	J58 AWY-HI	31.25672 -92.50097	35,000 ft 10,668 m	38	ALEXANDRIA VORTAC
PEBBY FIX	J58 AWY-HI	30.67039 -91.44048	35,000 ft 10,668 m	64	–
HRV VOR	J58 AWY-HI	29.85019 -90.00297	35,000 ft 10,668 m	89	HARVEY VORTAC
FATSO FIX	Q105 AWY-HI	29.69000 -89.78457	35,000 ft 10,668 m	14	–
REDFN FIX	Q105 AWY-HI	28.88297 -88.70178	35,000 ft 10,668 m	74	–
ROZZI FIX	Q100 AWY-HI	28.31451 -86.70517	35,000 ft 10,668 m	110	–
REMIS FIX	Q100 AWY-HI	27.88405 -85.25789	35,000 ft 10,668 m	80	–
SRQ VOR	Q100 AWY-HI	27.40703 -82.56367	29,700 ft 9,053 m	146	SARASOTA VORTAC
MMDUQ FIX	J616 AWY-HI	27.26276 -81.90713	21,000 ft 6,401 m	36	–
KPBI APT	–	26.68286 -80.09700	0 ft 0 m	102	Palm Beach Intl

KDFW

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 7

Elevation: 604 ft / 184 m
Location: 32.897200 -97.037700
Magnetic Var: 2.747 E

METAR

KDFW 191253Z 19005KT 10SM FEW250 06/00 A3026 RMK AO2 SLP245 T00560000

TAF

TAF KDFW 191120Z 1912/2018 19007KT P6SM BKN250 FM201400 21009KT P6SM BKN120

Frequencies

REC - 123.77 MHz - ATIS ARRIVAL
COM - 122.95 MHz - UNICOM
GND - 121.65 MHz - RGNL GND EAST 1
GND - 121.85 MHz - RGNL GND WEST
TWR - 127.50 MHz - RGNL TWR EAST 2
TWR - 124.15 MHz - RGNL TWR WEST 2
APP - 133.52 MHz - RGNL APP EAST 3
APP - 119.87 MHz - RGNL APP WEST 2
DEP - 124.82 MHz - RGNL DEP NORTH 1
DEP - 126.47 MHz - RGNL DEP WEST 1

REC - 135.92 MHz - ATIS DEPARTURE
CLD - 128.25 MHz - CLNC DEL
GND - 121.80 MHz - RGNL GND EAST 2
TWR - 126.55 MHz - RGNL TWR EAST 1
TWR - 134.90 MHz - RGNL TWR WEST 1
APP - 125.02 MHz - RGNL APP EAST 1
APP - 133.62 MHz - RGNL APP WEST 1
DEP - 118.55 MHz - RGNL DEP EAST 1
DEP - 125.12 MHz - RGNL DEP SOUTH 1

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
17C	151 ft 46 m	13,440 ft 4,097 m	180.26 177.52	CONCRETE	0 ft 0 m	413 ft 126 m
35C	151 ft 46 m	13,440 ft 4,097 m	0.26 357.52	CONCRETE	0 ft 0 m	299 ft 91 m
17L	151 ft 46 m	8,523 ft 2,598 m	180.25 177.51	CONCRETE	0 ft 0 m	400 ft 122 m
35R	151 ft 46 m	8,523 ft 2,598 m	0.25 357.51	CONCRETE	0 ft 0 m	407 ft 124 m
18R	151 ft 46 m	13,439 ft 4,096 m	180.25 177.50	CONCRETE	0 ft 0 m	404 ft 123 m
36L	151 ft 46 m	13,439 ft 4,096 m	0.25 357.50	CONCRETE	0 ft 0 m	299 ft 91 m
17R	200 ft 61 m	13,439 ft 4,096 m	180.26 177.51	CONCRETE	0 ft 0 m	400 ft 122 m
35L	200 ft 61 m	13,439 ft 4,096 m	0.26 357.51	CONCRETE	0 ft 0 m	400 ft 122 m
18L	200 ft 61 m	13,439 ft 4,096 m	180.25 177.50	CONCRETE	0 ft 0 m	404 ft 123 m
36R	200 ft 61 m	13,439 ft 4,096 m	0.25 357.50	CONCRETE	0 ft 0 m	394 ft 120 m
13R	151 ft 46 m	9,309 ft 2,837 m	139.18 136.44	CONCRETE	0 ft 0 m	397 ft 121 m
31L	151 ft 46 m	9,309 ft 2,837 m	319.19 316.45	CONCRETE	0 ft 0 m	400 ft 122 m
13L	200 ft 61 m	9,010 ft 2,746 m	135.41 132.66	CONCRETE	630 ft 192 m	299 ft 91 m
31R	200 ft 61 m	9,010 ft 2,746 m	315.42 312.67	CONCRETE	0 ft 0 m	299 ft 91 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
13R	DME	ILWN	109.50 MHz	18 nm 33 km	– –	–	590 ft 590 m
17C	DME	IFLQ	110.30 MHz	18 nm 33 km	– –	–	575 ft 575 m
17L	DME	IPPZ	111.75 MHz	18 nm 33 km	– –	–	603 ft 603 m
17R	DME	IJHZ	111.35 MHz	18 nm 33 km	– –	–	607 ft 607 m
18L	DME	ICIX	110.55 MHz	18 nm 33 km	– –	–	607 ft 607 m
18R	DME	IVYN	111.90 MHz	18 nm 33 km	– –	–	584 ft 584 m
31R	DME	IRRA	110.90 MHz	18 nm 33 km	– –	–	548 ft 548 m
35C	DME	IPKQ	110.30 MHz	18 nm 33 km	– –	–	603 ft 603 m
35L	DME	IUWX	111.35 MHz	18 nm 33 km	– –	–	607 ft 607 m
35R	DME	IAJQ	111.75 MHz	18 nm 33 km	– –	–	603 ft 603 m
36L	DME	IBXN	111.90 MHz	18 nm 33 km	– –	–	584 ft 584 m
36R	DME	IFJN	110.55 MHz	18 nm 33 km	– –	–	607 ft 607 m
13R	LOC-ILS	ILWN	109.50 MHz	18 nm 33 km	139.19 136.44	–	577 ft 577 m
17C	LOC-ILS	IFLQ	110.30 MHz	18 nm 33 km	180.26 177.52	–	563 ft 563 m
17L	LOC-ILS	IPPZ	111.75 MHz	18 nm 33 km	180.27 177.52	–	570 ft 570 m
17R	LOC-ILS	IJHZ	111.35 MHz	18 nm 33 km	180.26 177.51	–	558 ft 558 m
18L	LOC-ILS	ICIX	110.55 MHz	18 nm 33 km	180.25 177.50	–	570 ft 570 m
18R	LOC-ILS	IVYN	111.90 MHz	18 nm 33 km	180.25 177.50	–	580 ft 580 m
31R	LOC-ILS	IRRA	110.90 MHz	18 nm 33 km	315.40 312.65	–	552 ft 552 m
35C	LOC-ILS	IPKQ	110.30 MHz	18 nm 33 km	0.26 357.51	–	558 ft 558 m
35L	LOC-ILS	IUWX	111.35 MHz	18 nm 33 km	0.26 357.51	–	607 ft 607 m
35R	LOC-ILS	IAJQ	111.75 MHz	18 nm 33 km	0.27 357.52	–	607 ft 607 m
36L	LOC-ILS	IBXN	111.90 MHz	18 nm 33 km	0.25 357.50	–	598 ft 598 m
36R	LOC-ILS	IFJN	110.55 MHz	18 nm 33 km	0.25 357.50	–	595 ft 595 m
13R	GS	ILWN	109.50 MHz	10 nm 19 km	139.37 136.62	3.00	589 ft 589 m
17C	GS	IFLQ	110.30 MHz	10 nm 19 km	180.53 177.78	3.00	562 ft 562 m
17L	GS	IPPZ	111.75 MHz	10 nm 19 km	180.54 177.79	3.00	532 ft 532 m
17R	GS	IJHZ	111.35 MHz	10 nm 19 km	180.52 177.77	3.00	567 ft 567 m
18L	GS	ICIX	110.55 MHz	10 nm 19 km	180.49 177.75	3.00	594 ft 594 m
18R	GS	IVYN	111.90 MHz	10 nm	180.50	3.00	601 ft

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
				19 km	177.76		601 m
31R	GS	IRRA	110.90 MHz	10 nm	315.80	3.00	513 ft
				19 km	313.05		513 m
35C	GS	IPKQ	110.30 MHz	10 nm	0.52	3.00	563 ft
				19 km	357.77		563 m
35L	GS	IUWX	111.35 MHz	10 nm	0.52	3.00	564 ft
				19 km	357.77		564 m
35R	GS	IAJQ	111.75 MHz	10 nm	0.54	3.00	565 ft
				19 km	357.79		565 m
36L	GS	IBXN	111.90 MHz	10 nm	0.50	3.00	584 ft
				19 km	357.76		584 m
36R	GS	IFJN	110.55 MHz	10 nm	0.49	3.00	577 ft
				19 km	357.75		577 m

KPBI

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 3

Elevation: 19 ft / 6 m
Location: 26.682900 -80.097000
Magnetic Var: 7.484 W

METAR

KPBI 191253Z 35013G20KT 10SM FEW024 SCT047 SCT230 19/13 A2999 RMK AO2 PK WND 36026/1211 SLP155 T01940128

TAF

TAF KPBI 191129Z 1912/2012 35012KT P6SM FEW050 SCT090 BKN150 FM191500 01015G23KT P6SM FEW030 FEW250 FM192100 0301

Frequencies

REC - 123.75 MHz - PALM BEACH ATIS
GND - 121.90 MHz - PALM BEACH GROUND
DEP - 128.30 MHz - PALM BEACH DEPARTURE
DEP - 125.20 MHz - PALM BEACH DEPARTURE

CLD - 121.60 MHz - PALM BEACH CLEARANCE
TWR - 119.10 MHz - PALM BEACH TOWER
DEP - 127.35 MHz - PALM BEACH DEPARTURE
APP - 124.60 MHz - PALM BEACH APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10L	150 ft 46 m	9,988 ft 3,044 m	92.80 100.28	ASPHALT	1,201 ft 366 m	203 ft 62 m
28R	150 ft 46 m	9,988 ft 3,044 m	272.81 280.29	ASPHALT	810 ft 247 m	200 ft 61 m
14	150 ft 46 m	6,941 ft 2,116 m	135.32 142.80	ASPHALT	0 ft 0 m	197 ft 60 m
32	150 ft 46 m	6,941 ft 2,116 m	315.33 322.81	ASPHALT	427 ft 130 m	272 ft 83 m
10R	75 ft 23 m	3,209 ft 978 m	92.80 100.28	ASPHALT	0 ft 0 m	197 ft 60 m
28L	75 ft 23 m	3,209 ft 978 m	272.81 280.29	ASPHALT	0 ft 0 m	187 ft 57 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10L	LOC-ILS	IPBI	111.90 MHz	18 nm 33 km	92.80 100.28	-	19 ft 19 m
28R	LOC-ILS	IPWB	111.90 MHz	18 nm 33 km	272.80 280.28	-	19 ft 19 m
10L	GS	IPBI	111.90 MHz	10 nm 19 km	93.59 101.08	3.00	17 ft 17 m
28R	GS	IPWB	111.90 MHz	10 nm 19 km	273.59 281.08	3.00	19 ft 19 m