KSAN
San Diego Intl


-

KLAX
Los Angeles Intl

2024/03/19 0207Z

KSAN MZB SLI KLAX

96.62 nm / 178.93 km



Notes

None

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KSAN APT	–	32.73355 −117.18970	0 ft 0 m	–	San Diego Intl
MZB VOR	–	32.78220 −117.22540	0 ft 0 m	3	MISSION BAY VORTAC
SLI VOR	–	33.78330 −118.05480	0 ft 0 m	73	SEAL BEACH VORTAC
KLAX APT	–	33.94254 −118.40810	0 ft 0 m	20	Los Angeles Intl

KSAN

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 1
Elevation: 17 ft / 5 m
Location: 32.733600 -117.190000
Magnetic Var: 10.982 E

METAR

KSAN 190051Z 05005KT 10SM FEW060 BKN110 BKN180 21/09 A3003 RMK AO2 SLP168 T02060089 $

TAF

TAF KSAN 182342Z 1900/2006 30010KT P6SM VCSH FEW020 BKN100 FM190200 VRB05KT P6SM VCSH BKN060 FM190700 VRB05KT P6SM

Frequencies

REC - 134.80 MHz - LINDBERGH ATIS
GND - 123.90 MHz - LINDBERGH GROUND
DEP - 119.60 MHz - SOCAL WEST DEPARTURE
APP - 119.60 MHz - SOCAL WEST APPROACH
CLD - 125.90 MHz - LINDBERGH CLEARANCE
TWR - 118.30 MHz - LINDBERGH TOWER
DEP - 124.35 MHz - SOCAL EAST DEPARTURE
APP - 124.35 MHz - SOCAL EAST APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	200 ft 61 m	9,388 ft 2,861 m	106.13 95.15	ASPHALT	1,004 ft 306 m	390 ft 119 m
27	200 ft 61 m	9,388 ft 2,861 m	286.15 275.17	ASPHALT	1,811 ft 552 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09	DME	ISAN	111.55 MHz	18 nm 33 km	- -	-	29 ft 29 m
27	DME	IUBR	110.90 MHz	18 nm 33 km	- -	-	26 ft 26 m
09	LOC-ILS	ISAN	111.55 MHz	18 nm 33 km	106.14 95.16	-	17 ft 17 m
27	LOC-LOC	IUBR	110.90 MHz	18 nm 33 km	286.14 275.16	-	17 ft 17 m
09	GS	ISAN	111.55 MHz	10 nm 19 km	106.14 95.16	3.10	17 ft 17 m

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4
Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.454 E

METAR

KLAX 190053Z 19007KT 10SM FEW080 FEW110 SCT150 17/12 A3003 RMK AO2 SLP168 T01720122

TAF

TAF AMD KLAX 190122Z 1901/2006 24005KT P6SM FEW010 FEW100 SCT150 FM190500 VRB03KT P6SM FEW010 SCT200 FM191800 250

Frequencies

COM - 122.95 MHz - UNICOM
GND - 121.75 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER
REC - 135.65 MHz - D-ATIS
APP - 124.30 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH
DEP - 124.30 MHz - SOCAL DEPARTURE
GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 120.95 MHz - LOS ANGELES TOWER
REC - 133.80 MHz - D-ATIS
APP - 124.90 MHz - SOCAL APPROACH
APP - 124.50 MHz - SOCAL APPROACH
DEP - 125.20 MHz - SOCAL DEPARTURE
CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft 61 m	11,106 ft 3,385 m	82.96 71.50	CONCRETE	0 ft 0 m	381 ft 116 m
25L	200 ft 61 m	11,106 ft 3,385 m	262.98 251.52	CONCRETE	0 ft 0 m	381 ft 116 m
07L	151 ft 46 m	12,935 ft 3,943 m	82.95 71.50	CONCRETE	846 ft 258 m	374 ft 114 m
25R	151 ft 46 m	12,935 ft 3,943 m	262.98 251.52	CONCRETE	968 ft 295 m	197 ft 60 m
06R	151 ft 46 m	10,896 ft 3,321 m	82.95 71.49	CONCRETE	551 ft 168 m	384 ft 117 m
24L	151 ft 46 m	10,896 ft 3,321 m	262.97 251.51	CONCRETE	814 ft 248 m	384 ft 117 m
06L	151 ft 46 m	8,936 ft 2,724 m	82.95 71.49	CONCRETE	0 ft 0 m	0 ft 0 m
24R	151 ft 46 m	8,936 ft 2,724 m	262.96 251.51	CONCRETE	0 ft 0 m	285 ft 87 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm 33 km	- -	-	120 ft 120 m
06R	DME	IGPE	111.70 MHz	18 nm 33 km	- -	-	120 ft 120 m
07L	DME	IIAS	111.10 MHz	18 nm 33 km	- -	-	103 ft 103 m
07R	DME	IMKZ	109.90 MHz	18 nm 33 km	- -	-	103 ft 103 m
24L	DME	IHQB	111.70 MHz	18 nm 33 km	- -	-	133 ft 133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm	– –	–	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	– –	–	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	– –	–	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.53	–	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.53	–	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.53	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.53	3.00	125 ft 125 m