EDDN
Nurnberg


-

LFPG
Paris Charles De Gaulle

2024/03/29 0950Z

EDDN 4900N01000E 4900N0500E LFPG

344.78 nm / 638.53 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: no
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EDDN APT	–	49.49874 11.07758	0 ft 0 m	–	Nurnberg
4900N01000E LATLON	–	49.00000 10.00000	18,400 ft 5,608 m	51	–
4900N0500E LATLON	–	49.00000 5.00000	20,500 ft 6,248 m	196	–
LFPG APT	–	49.00974 2.56262	0 ft 0 m	96	Paris Charles De Gaulle

EDDN

Region: GERMANY - CIVIL
Timezone: EUROPE/BERLIN
Runways: 1

Elevation: 1,043 ft / 318 m
Location: 49.498700 11.077600
Magnetic Var: 3.810 E

METAR

EDDN 290920Z AUTO 15011KT 120V180 9999 -RA FEW049 09/03 Q1002 TEMPO RA

TAF

TAF EDDN 290500Z 2906/3006 12008KT CAVOK BECMG 2906/2908 15013KT BECMG 2911/2913 14006KT

Frequencies

REC - 123.08 MHz - NUERNBERG ATIS
GND - 118.10 MHz - NUERNBERG GROUND
APP - 129.53 MHz - MUENCHEN RADAR

COM - 122.80 MHz - NUERNBERG UNICOM
TWR - 118.30 MHz - NUERNBERG TOWER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10	148 ft 45 m	8,835 ft 2,693 m	98.58 94.78	ASPHALT	0 ft 0 m	102 ft 31 m
28	148 ft 45 m	8,835 ft 2,693 m	278.61 274.80	ASPHALT	0 ft 0 m	108 ft 33 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10	LOC-ILS	INUE	109.55 MHz	18 nm 33 km	98.60 94.79	-	1,043 ft 1,043 m
28	LOC-ILS	INUW	109.10 MHz	18 nm 33 km	278.60 274.79	-	1,043 ft 1,043 m
10	GS	INUE	109.55 MHz	10 nm 19 km	98.60 94.79	3.00	1,043 ft 1,043 m
28	GS	INUW	109.10 MHz	10 nm 19 km	278.60 274.79	3.00	1,043 ft 1,043 m

LFPG

Region: FRANCE
Timezone: EUROPE/PARIS
Runways: 4

Elevation: 392 ft / 119 m
Location: 49.009700 2.562570
Magnetic Var: 1.480 E

METAR

LFPG 290930Z 21015KT 9999 SCT020 SCT028 BKN220 12/07 Q0994 NOSIG

TAF

TAF LFPG 290500Z 2906/3012 23012KT 9999 BKN020 TX14/2915Z TN08/3005Z TEMPO 2906/2910 BKN014 BECMG 2918/2920 17010

Frequencies

REC - 128.32 MHz - ATIS
TWR - 120.90 MHz - DE GAULLE TOWER
TWR - 119.62 MHz - DE GAULLE TOWER
TWR - 118.65 MHz - DE GAULLE TOWER
TWR - 120.65 MHz - DE GAULLE TOWER
GND - 125.30 MHz - DE GAULLE GROUND
CLD - 121.80 MHz - CLEARANCE DELIVERY
APP - 119.85 MHz - DE GAULLE APPROACH
APP - 125.82 MHz - DE GAULLE APPROACH
DEP - 124.35 MHz - DE GAULLE DEPARTURE
DEP - 131.20 MHz - DE GAULLE DEPARTURE

REC - 127.12 MHz - ATIS
TWR - 125.32 MHz - DE GAULLE TOWER
TWR - 119.25 MHz - DE GAULLE TOWER
TWR - 123.60 MHz - DE GAULLE TOWER
GND - 121.90 MHz - DE GAULLE GROUND
GND - 121.70 MHz - DE GAULLE GROUND
APP - 118.15 MHz - DE GAULLE APPROACH
APP - 121.15 MHz - DE GAULLE APPROACH
APP - 126.42 MHz - DE GAULLE APPROACH
DEP - 126.57 MHz - DE GAULLE DEPARTURE
DEP - 133.37 MHz - DE GAULLE DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08L	148 ft 45 m	13,713 ft 4,180 m	85.31 83.83	ASPHALT	0 ft 0 m	489 ft 149 m
26R	148 ft 45 m	13,713 ft 4,180 m	265.35 263.87	ASPHALT	1,877 ft 572 m	279 ft 85 m
09L	197 ft 60 m	8,866 ft 2,703 m	85.32 83.84	ASPHALT	0 ft 0 m	0 ft 0 m
27R	197 ft 60 m	8,866 ft 2,703 m	265.35 263.87	ASPHALT	0 ft 0 m	0 ft 0 m
08R	197 ft 60 m	8,833 ft 2,692 m	85.33 83.85	ASPHALT	0 ft 0 m	489 ft 149 m
26L	197 ft 60 m	8,833 ft 2,692 m	265.35 263.87	ASPHALT	0 ft 0 m	486 ft 148 m
09R	148 ft 45 m	13,746 ft 4,190 m	85.30 83.82	ASPHALT	0 ft 0 m	0 ft 0 m
27L	148 ft 45 m	13,746 ft 4,190 m	265.34 263.86	ASPHALT	1,959 ft 597 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08R	DME	DSE	108.55 MHz	18 nm 33 km	- -	-	358 ft 358 m
09L	DME	PNE	109.35 MHz	18 nm 33 km	- -	-	392 ft 392 m
09R	DME	CGE	110.10 MHz	18 nm 33 km	- -	-	392 ft 392 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
26L	DME	DSU	108.35 MHz	18 nm	– –	–	338 ft 338 m
27L	DME	CGW	110.70 MHz	18 nm 33 km	– –	–	407 ft 407 m
27R	DME	PNW	110.35 MHz	18 nm 33 km	– –	–	392 ft 392 m
08L	LOC-ILS	GLE	108.70 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
08R	LOC-ILS	DSE	108.55 MHz	18 nm 33 km	85.34 83.86	–	392 ft 392 m
09L	LOC-ILS	PNE	109.35 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
09R	LOC-ILS	CGE	110.10 MHz	18 nm 33 km	85.32 83.84	–	392 ft 392 m
26L	LOC-ILS	DSU	108.35 MHz	18 nm 33 km	265.34 263.86	–	392 ft 392 m
26R	LOC-ILS	GAU	111.95 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
27L	LOC-ILS	CGW	110.70 MHz	18 nm 33 km	265.32 263.84	–	392 ft 392 m
27R	LOC-ILS	PNW	110.35 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
08L	GS	GLE	108.70 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
08R	GS	DSE	108.55 MHz	10 nm 19 km	85.34 83.86	3.00	392 ft 392 m
09L	GS	PNE	109.35 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
09R	GS	CGE	110.10 MHz	10 nm 19 km	85.32 83.84	3.00	392 ft 392 m
26L	GS	DSU	108.35 MHz	10 nm 19 km	265.34 263.86	3.00	392 ft 392 m
26R	GS	GAU	111.95 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m
27L	GS	CGW	110.70 MHz	10 nm 19 km	265.32 263.84	3.00	392 ft 392 m
27R	GS	PNW	110.35 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m