ESMT
Halmstad


-

EKAH
Aarhus

2024/03/29 0844Z

ESMT NORTI EKAH

76.68 nm / 142.01 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: yes
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
ESMT	–	56.69110	0 ft	–	Halmstad
APT	–	12.82020	0 m		
NORTI	–	56.52444	7,700 ft	40	–
FIX	–	11.62556	2,347 m		
EKAH	–	56.30426	0 ft	35	Aarhus
APT	–	10.61945	0 m		

ESMT

Region: SWEDEN
Timezone: EUROPE/STOCKHOLM
Runways: 2

Elevation: 101 ft / 31 m
Location: 56.688500 12.815800
Magnetic Var: 4.803 E

METAR

ESMT 290820Z AUTO 17012KT 140V200 9999 NCD 08/05 Q0994

TAF

UNKNOWN

Frequencies

TWR - 135.05 MHz -

TWR - 130.10 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01	131 ft 40 m	7,410 ft 2,259 m	6.19 1.39	ASPHALT	0 ft 0 m	0 ft 0 m
19	131 ft 40 m	7,410 ft 2,259 m	186.19 181.39	ASPHALT	0 ft 0 m	0 ft 0 m
06	98 ft 30 m	1,970 ft 601 m	53.44 48.64	GRASS	0 ft 0 m	0 ft 0 m
24	98 ft 30 m	1,970 ft 601 m	233.45 228.65	GRASS	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
19	LOC-ILS	MT	110.10 MHz	18 nm 33 km	186.18 181.37	-	101 ft 101 m
19	GS	MT	110.10 MHz	10 nm 19 km	186.39 181.58	3.00	101 ft 101 m

EKAH

Region: DENMARK / FAROE ISLANDS
Timezone: EUROPE/COPENHAGEN
Runways: 2

Elevation: 82 ft / 25 m
Location: 56.304300 10.619400
Magnetic Var: 4.007 E

METAR

EKAH 290820Z VRB06KT CAVOK 09/04 Q0992

TAF

TAF EKAH 290524Z 2906/3006 18008KT 9999 BKN020 TEMPO 2912/2920 BKN012 SCT020TCU TEMPO 2920/2923 2500 BR TEMPO 292

Frequencies

TWR - 118.52 MHz - AARHUS TOWER

APP - 119.27 MHz - AARHUS APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10L	75 ft 23 m	9,081 ft 2,768 m	100.30 96.29	ASPHALT	0 ft 0 m	0 ft 0 m
28R	75 ft 23 m	9,081 ft 2,768 m	280.34 276.33	ASPHALT	0 ft 0 m	0 ft 0 m
10R	148 ft 45 m	8,837 ft 2,693 m	100.29 96.28	ASPHALT	0 ft 0 m	938 ft 286 m
28L	148 ft 45 m	8,837 ft 2,693 m	280.33 276.32	ASPHALT	0 ft 0 m	738 ft 225 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
28L	DME	TR	111.10 MHz	18 nm 33 km	- -	-	79 ft 79 m
10R	LOC-ILS	AAR	111.90 MHz	18 nm 33 km	100.33 96.32	-	82 ft 82 m
28L	LOC-ILS	TR	111.10 MHz	18 nm 33 km	280.29 276.28	-	82 ft 82 m
10R	GS	AAR	111.90 MHz	10 nm 19 km	100.62 96.61	2.75	82 ft 82 m
28L	GS	TR	111.10 MHz	10 nm 19 km	280.62 276.61	2.75	82 ft 82 m