KJFK

John F Kennedy Intl

-


FOOL

Leon M Ba

2024/03/29 0652Z

KJFK CUTOX **J62** ACK SAILE **N18C** DOVEY **Z** +42.000_--60.000 4000N05500W 3800N05000W 3600N04500W 3400N04000W 3200N03500W 3000N03000W 2700N02500W NORED USOTI ISOKA ETIBA AMDIB PE **UA600F** KISBA **UA600** BKO **UA601** PAM **UR983** DIBSI **UB600** LV FOOL

5216.05 nm / 9660.12 km



Notes

Using NAT tracks from 3/5/2016

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KJFK APT	–	40.63990 -73.77666	0 ft 0 m	–	John F Kennedy Intl
CUTOX FIX	–	40.88147 -71.78663	31,700 ft 9,662 m	91	–
CUJKE FIX	J62 AWY-HI	41.16306 -70.56357	35,000 ft 10,668 m	57	–
ACK VOR	J62 AWY-HI	41.28189 -70.02672	35,000 ft 10,668 m	25	NANTUCKET VOR-DME
SAILE FIX	–	41.18577 -67.89571	35,000 ft 10,668 m	96	–
DOVEY FIX	N18C AWY-HI	41.11667 -67.00000	35,000 ft 10,668 m	40	–
+42.000_--60.000 LATLON	Z NAT	42.00000 -60.00000	35,000 ft 10,668 m	318	–
4000N05500W LATLON	–	40.00000 -55.00000	35,000 ft 10,668 m	256	–
3800N05000W LATLON	–	38.00000 -50.00000	35,000 ft 10,668 m	262	–
3600N04500W LATLON	–	36.00000 -45.00000	35,000 ft 10,668 m	268	–
3400N04000W LATLON	–	34.00000 -40.00000	35,000 ft 10,668 m	273	–
3200N03500W LATLON	–	32.00000 -35.00000	35,000 ft 10,668 m	278	–
3000N03000W LATLON	–	30.00000 -30.00000	35,000 ft 10,668 m	283	–
2700N02500W LATLON	–	27.00000 -25.00000	35,000 ft 10,668 m	319	–
NORED FIX	–	24.63836 -22.48003	35,000 ft 10,668 m	196	–
USOTI FIX	–	23.06677 -20.83637	35,000 ft 10,668 m	130	–
ISOKA FIX	–	22.08136 -19.59002	35,000 ft 10,668 m	90	–
ETIBA FIX	–	21.33826 -18.67879	35,000 ft 10,668 m	67	–
AMDIB FIX	–	20.91667 -18.00000	35,000 ft 10,668 m	45	–
PE VOR	–	20.91444 -17.03497	35,000 ft 10,668 m	54	NOUADHIBOU VOR-DME
KISBA FIX	UA600F AWY-HI	19.50000 -16.48528	35,000 ft 10,668 m	90	–
KC VOR	UA600 AWY-HI	18.09158 -15.94828	35,000 ft 10,668 m	89	NOUAKCHOTT VOR-DME
IDINI FIX	UA600 AWY-HI	17.64306 -15.26583	35,000 ft 10,668 m	47	–
EGABU FIX	UA600 AWY-HI	17.19861 -14.59639	35,000 ft 10,668 m	46	–
POVIN FIX	UA600 AWY-HI	16.84667 -14.07111	35,000 ft 10,668 m	36	–
MOKOD FIX	UA600 AWY-HI	16.41333 -13.42944	35,000 ft 10,668 m	45	–
TIPAD	UA600	15.59667	35,000 ft	84	–

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
FIX	AWY-HI	-12.23583	10,668 m		
KIMGA	UA600	15.30111	35,000 ft	30	-
FIX	AWY-HI	-11.80861	10,668 m		
AMTAK	UA600	14.73611	35,000 ft	57	-
FIX	AWY-HI	-10.99806	10,668 m		
TOBAS	UA600	14.03083	35,000 ft	71	-
FIX	AWY-HI	-9.99806	10,668 m		
BKO	UA600	12.54611	35,000 ft	150	BAMAKO/SENOU VOR-DME
VOR	AWY-HI	-7.93047	10,668 m		
EBSUD	UA601	11.50194	35,000 ft	169	-
FIX	AWY-HI	-5.24833	10,668 m		
BD	UA601	11.14503	35,000 ft	57	BOBO DIOULASSO VOR-DME
VOR	AWY-HI	-4.35086	10,668 m		
BIGOM	UA601	10.53083	35,000 ft	83	-
FIX	AWY-HI	-3.08444	10,668 m		
NANGA	UA601	10.40833	35,000 ft	16	-
FIX	AWY-HI	-2.83333	10,668 m		
BUGBU	UA601	10.20139	35,000 ft	36	-
FIX	AWY-HI	-2.25000	10,668 m		
TLE	UA601	9.57349	35,000 ft	91	TAMALE VOR-DME
VOR	AWY-HI	-0.84714	10,668 m		
TURUT	UA601	8.63528	35,000 ft	75	-
FIX	AWY-HI	0.00111	10,668 m		
PAM	UA601	8.01333	35,000 ft	50	PAMPA VOR-DME
VOR	AWY-HI	0.56150	10,668 m		
LM	UR983	6.18408	35,000 ft	117	LOME VOR-DME
VOR	AWY-HI	1.26878	10,668 m		
DIBSI	UR983	3.89583	35,000 ft	176	-
FIX	AWY-HI	3.12000	10,668 m		
EBULI	UB600	2.01056	35,000 ft	236	-
FIX	AWY-HI	6.58333	10,668 m		
SEMAD	UB600	1.45167	25,400 ft	70	-
FIX	AWY-HI	7.61361	7,742 m		
LV	UB600	0.47983	23,500 ft	122	LIBREVILLE VOR-DME
VOR	AWY-HI	9.40197	7,163 m		
FOOL	-	0.45862	0 ft	1	Leon M Ba
APT	-	9.41225	0 m		

KJFK

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 4

Elevation: 12 ft / 4 m
Location: 40.640100 -73.776500
Magnetic Var: 12.823 W

METAR

KJFK 290551Z 33016KT 10SM OVC100 07/M01 A2980 RMK AO2 SLP089 60007 T00671006 10078 20061 56015

TAF

TAF KJFK 290526Z 2906/3012 33017G25KT P6SM SCT040 BKN100 FM291500 31020G30KT P6SM SCT050 FM300000 31016G25KT P6SM

Frequencies

REC - 115.40 MHz - D-ATIS
REC - 128.72 MHz - D-ATIS
CLD - 135.05 MHz - CLEARANCE DELIVERY
GND - 121.65 MHz - KENNEDY GROUND
TWR - 123.90 MHz - KENNEDY TOWER
APP - 128.12 MHz - NEW YORK APPROACH
APP - 123.70 MHz - NEW YORK APPROACH
APP - 132.40 MHz - NEW YORK APPROACH
DEP - 135.90 MHz - NEW YORK DEPARTURE
DEP - 124.75 MHz - NEW YORK DEPARTURE

REC - 117.70 MHz - D-ATIS
COM - 122.95 MHz - UNICOM
GND - 121.90 MHz - KENNEDY GROUND
TWR - 119.10 MHz - KENNEDY TOWER
APP - 125.70 MHz - NEW YORK APPROACH
APP - 118.40 MHz - NEW YORK APPROACH
APP - 126.80 MHz - NEW YORK APPROACH
APP - 134.35 MHz - NEW YORK APPROACH
DEP - 123.70 MHz - NEW YORK DEPARTURE
DEP - 134.35 MHz - NEW YORK DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
13R	200 ft 61 m	14,526 ft 4,428 m	120.83 133.65	CONCRETE	2,057 ft 627 m	390 ft 119 m
31L	200 ft 61 m	14,526 ft 4,428 m	300.86 313.68	CONCRETE	3,271 ft 997 m	495 ft 151 m
13L	151 ft 46 m	10,010 ft 3,051 m	120.85 133.68	CONCRETE	912 ft 278 m	387 ft 118 m
31R	151 ft 46 m	10,010 ft 3,051 m	300.87 313.70	CONCRETE	1,037 ft 316 m	177 ft 54 m
04R	200 ft 61 m	8,407 ft 2,562 m	30.67 43.49	ASPHALT	0 ft 0 m	440 ft 134 m
22L	200 ft 61 m	8,407 ft 2,562 m	210.68 223.50	ASPHALT	0 ft 0 m	505 ft 154 m
04L	200 ft 61 m	12,091 ft 3,685 m	30.67 43.49	CONCRETE	459 ft 140 m	200 ft 61 m
22R	200 ft 61 m	12,091 ft 3,685 m	210.68 223.50	CONCRETE	3,425 ft 1,044 m	407 ft 124 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04L	DME	IHIQ	110.90 MHz	18 nm 33 km	- -	-	13 ft 13 m
04R	DME	IJFK	109.50 MHz	18 nm 33 km	- -	-	13 ft 13 m
13L	DME	ITLK	111.50 MHz	18 nm 33 km	- -	-	13 ft 13 m
22L	DME	IIWY	110.90 MHz	18 nm 33 km	- -	-	13 ft 13 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
22R	DME	IJOC	109.50 MHz	18 nm	– –	–	13 ft 13 m
31R	DME	IRTH	111.50 MHz	18 nm 33 km	– –	–	13 ft 13 m
04L	LOC-ILS	IHIQ	110.90 MHz	18 nm 33 km	30.68 43.50	–	12 ft 12 m
04R	LOC-ILS	IJFK	109.50 MHz	18 nm 33 km	30.67 43.49	–	12 ft 12 m
13L	LOC-ILS	ITLK	111.50 MHz	18 nm 33 km	120.87 133.69	–	12 ft 12 m
22L	LOC-ILS	IIWY	110.90 MHz	18 nm 33 km	210.67 223.49	–	12 ft 12 m
22R	LOC-ILS	IJOC	109.50 MHz	18 nm 33 km	210.68 223.50	–	12 ft 12 m
31L	LOC-ILS	IMOH	111.35 MHz	18 nm 33 km	300.84 313.66	–	12 ft 12 m
31R	LOC-ILS	IRTH	111.50 MHz	18 nm 33 km	300.87 313.69	–	12 ft 12 m
04L	GS	IHIQ	110.90 MHz	10 nm 19 km	30.68 43.50	3.00	12 ft 12 m
04R	GS	IJFK	109.50 MHz	10 nm 19 km	30.67 43.49	3.00	12 ft 12 m
13L	GS	ITLK	111.50 MHz	10 nm 19 km	120.87 133.69	3.00	12 ft 12 m
22L	GS	IIWY	110.90 MHz	10 nm 19 km	210.67 223.49	3.00	12 ft 12 m
22R	GS	IJOC	109.50 MHz	10 nm 19 km	210.68 223.50	3.00	12 ft 12 m
31L	GS	IMOH	111.35 MHz	10 nm 19 km	300.84 313.66	3.00	12 ft 12 m
31R	GS	IRTH	111.50 MHz	10 nm 19 km	300.87 313.69	3.00	12 ft 12 m

FOOL

Region: GABON
Timezone: AFRICA/LIBREVILLE
Runways: 1

Elevation: 39 ft / 12 m
Location: 0.458442 9.412330
Magnetic Var: 1.110 W

METAR

FOOL 290600Z 14008KT 8000 SCT010 26/25 Q1009 NOSIG

TAF

TAF FOOL 290500Z 2906/3012 17005KT 8000 BKN010 FEW020CB TEMPO 2906/2909 4000 TSRA BECMG 2909/2911 SCT010 PROB30 TE

Frequencies

COM - 112.10 MHz - LIBREVILLE ATIS
TWR - 118.70 MHz - LIBREVILLE TOWER
APP - 126.50 MHz - LIBREVILLE APPROACH
GND - 121.70 MHz - LIBREVILLE GROUND

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16	148 ft 45 m	9,852 ft 3,003 m	154.26 155.37	ASPHALT	0 ft 0 m	213 ft 65 m
34	148 ft 45 m	9,852 ft 3,003 m	334.26 335.37	ASPHALT	0 ft 0 m	210 ft 64 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	DME	LB	109.50 MHz	18 nm 33 km	- -	-	39 ft 39 m
16	LOC-ILS	LB	109.50 MHz	18 nm 33 km	154.26 155.37	-	39 ft 39 m
16	GS	LB	109.50 MHz	10 nm 19 km	154.26 155.37	3.00	39 ft 39 m