
KABQ
Albuquerque International Sunport

KLAX
Los Angeles Intl

2024/03/29 0643Z

KABQ ABQ **J6** DRK **J231** HIPPI **J10** PIONE KLAX

588.71 nm / 1090.29 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: no
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KABQ APT	– –	35.03965 -106.61058	0 ft 0 m	–	Albuquerque International Sunport
ABQ VOR	– –	35.04381 -106.81631	3,600 ft 1,097 m	10	ALBUQUERQUE VORTAC
ZUN VOR	J6 AWY-HI	34.96575 -109.15450	34,000 ft 10,363 m	115	ZUNI VORTAC
PYRIT FIX	J6 AWY-HI	34.86955 -110.51143	34,000 ft 10,363 m	67	–
DRK VOR	J6 AWY-HI	34.70256 -112.48036	34,000 ft 10,363 m	97	DRAKE VORTAC
HIPPI FIX	J231 AWY-HI	34.56229 -113.63937	34,000 ft 10,363 m	57	–
CADEZ FIX	J10 AWY-HI	34.20656 -115.34287	32,900 ft 10,028 m	87	–
TNP DME	J10 AWY-HI	34.11223 -115.76991	28,200 ft 8,595 m	21	TWENTYNINE PALMS VORTAC
PIONE FIX	J10 AWY-HI	34.09447 -116.73879	18,000 ft 5,486 m	48	–
KLAX APT	– –	33.94313 -118.40892	0 ft 0 m	83	Los Angeles Intl

KABQ

Region: UNITED STATES
Timezone: AMERICA/DENVER
Runways: 3

Elevation: 5,354 ft / 1,632 m
Location: 35.038200 -106.610000
Magnetic Var: 7.904 E

METAR

KABQ 290552Z 18006KT 10SM BKN200 13/M07 A2996 RMK AO2 SLP100 T01281072 10189 20122 50002

TAF

TAF KABQ 290522Z 2906/3006 16008KT P6SM BKN200 FM290900 VRB06KT P6SM BKN200 FM291800 23011KT P6SM FEW100 SCT250 FM

Frequencies

REC - 118.00 MHz - ATIS
CLD - 119.20 MHz - CLNC DEL
TWR - 123.77 MHz -
APP - 123.90 MHz - APP/DEP
APP - 127.40 MHz - APP/DEP

COM - 122.95 MHz - UNICOM
GND - 121.90 MHz -
TWR - 120.30 MHz -
APP - 124.40 MHz - APP/DEP
APP - 134.80 MHz - APP/DEP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08	150 ft 46 m	13,762 ft 4,195 m	90.43 82.52	CONCRETE	1,001 ft 305 m	551 ft 168 m
26	150 ft 46 m	13,762 ft 4,195 m	270.45 262.55	CONCRETE	0 ft 0 m	1,001 ft 305 m
03	150 ft 46 m	10,002 ft 3,049 m	44.66 36.75	CONCRETE	0 ft 0 m	400 ft 122 m
21	150 ft 46 m	10,002 ft 3,049 m	224.67 216.77	CONCRETE	0 ft 0 m	0 ft 0 m
12	150 ft 46 m	6,024 ft 1,836 m	128.99 121.09	CONCRETE	0 ft 0 m	0 ft 0 m
30	150 ft 46 m	6,024 ft 1,836 m	309.00 301.10	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08	DME	ISPT	111.90 MHz	18 nm 33 km	- -	-	5,374 ft 5,374 m
03	LOC-ILS	IBZY	111.50 MHz	18 nm 33 km	44.67 36.77	-	5,354 ft 5,354 m
08	LOC-ILS	ISPT	111.90 MHz	18 nm 33 km	90.44 82.54	-	5,354 ft 5,354 m
03	GS	IBZY	111.50 MHz	10 nm 19 km	44.67 36.77	3.00	5,354 ft 5,354 m
08	GS	ISPT	111.90 MHz	10 nm 19 km	90.44 82.54	3.00	5,354 ft 5,354 m

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4
Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.451 E

METAR

KLAX 290553Z 28012G18KT 10SM FEW015 FEW050 SCT250 13/09 A3000 RMK AO2 SLP158 T01280089 10156 20122 50006 $

TAF

KLAX 290551Z 2906/3012 26007KT P6SM SCT250 FM291200 12006KT P6SM OVC025 FM291800 23012KT P6SM SCT025 BKN050 FM300

Frequencies

COM - 122.95 MHz - UNICOM
GND - 121.75 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER
REC - 135.65 MHz - D-ATIS
APP - 124.30 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH
DEP - 124.30 MHz - SOCAL DEPARTURE
GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 120.95 MHz - LOS ANGELES TOWER
REC - 133.80 MHz - D-ATIS
APP - 124.90 MHz - SOCAL APPROACH
APP - 124.50 MHz - SOCAL APPROACH
DEP - 125.20 MHz - SOCAL DEPARTURE
CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft 61 m	11,106 ft 3,385 m	82.96 71.51	CONCRETE	0 ft 0 m	381 ft 116 m
25L	200 ft 61 m	11,106 ft 3,385 m	262.98 251.53	CONCRETE	0 ft 0 m	381 ft 116 m
07L	151 ft 46 m	12,935 ft 3,943 m	82.95 71.50	CONCRETE	846 ft 258 m	374 ft 114 m
25R	151 ft 46 m	12,935 ft 3,943 m	262.98 251.52	CONCRETE	968 ft 295 m	197 ft 60 m
06R	151 ft 46 m	10,896 ft 3,321 m	82.95 71.50	CONCRETE	551 ft 168 m	384 ft 117 m
24L	151 ft 46 m	10,896 ft 3,321 m	262.97 251.52	CONCRETE	814 ft 248 m	384 ft 117 m
06L	151 ft 46 m	8,936 ft 2,724 m	82.95 71.50	CONCRETE	0 ft 0 m	0 ft 0 m
24R	151 ft 46 m	8,936 ft 2,724 m	262.96 251.51	CONCRETE	0 ft 0 m	285 ft 87 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm 33 km	- -	-	120 ft 120 m
06R	DME	IGPE	111.70 MHz	18 nm 33 km	- -	-	120 ft 120 m
07L	DME	IIAS	111.10 MHz	18 nm 33 km	- -	-	103 ft 103 m
07R	DME	IMKZ	109.90 MHz	18 nm 33 km	- -	-	103 ft 103 m
24L	DME	IHQB	111.70 MHz	18 nm 33 km	- -	-	133 ft 133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	– –	–	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	– –	–	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	– –	–	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.53	–	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.53	–	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.53	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.53	3.00	125 ft 125 m