LSGG
Geneva


-

EKCH
Kastrup

2024/03/19 0721Z

LSGG OLBEN **Y164** HERBI **Y163** PABLA **T715** KRH **UN850** BOMBI **UZ728** MASEK **UN851** ABASO EKCH

627.85 nm / 1162.78 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 34000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LSGG APT	–	46.23775 6.10617	0 ft 0 m	–	Geneva
OLBEN FIX	–	47.30444 7.62944	31,000 ft 9,449 m	89	–
MOPAN FIX	Y164 AWY-HI	48.24639 8.15444	35,000 ft 10,668 m	60	–
HERBI FIX	Y164 AWY-HI	48.49083 8.24361	35,000 ft 10,668 m	15	–
PABLA FIX	Y163 AWY-HI	48.78861 8.35194	35,000 ft 10,668 m	18	–
KRH VOR	T715 AWY-HI	48.99294 8.58424	35,000 ft 10,668 m	15	KARLSRUHE VOR-DME
ABUKA FIX	UN850 AWY-HI	49.46528 8.67917	35,000 ft 10,668 m	28	–
GIGET FIX	UN850 AWY-HI	49.70111 8.67917	35,000 ft 10,668 m	14	–
BOMBI FIX	UN850 AWY-HI	50.05667 8.80028	35,000 ft 10,668 m	21	–
TEKTU FIX	UZ728 AWY-HI	50.34278 9.13639	35,000 ft 10,668 m	21	–
MASEK FIX	UZ728 AWY-HI	50.72917 9.59833	35,000 ft 10,668 m	29	–
KEMAD FIX	UN851 AWY-HI	51.12361 9.67500	35,000 ft 10,668 m	23	–
DEKEL FIX	UN851 AWY-HI	52.30278 10.29806	35,000 ft 10,668 m	74	–
AMALI FIX	UN851 AWY-HI	52.47972 10.40639	35,000 ft 10,668 m	11	–
IRKIS FIX	UN851 AWY-HI	53.24889 10.88861	33,100 ft 10,089 m	49	–
ABASO FIX	UN851 AWY-HI	53.97611 11.43389	25,000 ft 7,620 m	47	–
EKCH APT	–	55.61291 12.64096	0 ft 0 m	106	Kastrup

LSGG

Region: SWITZERLAND
Timezone: EUROPE/ZURICH
Runways: 1

Elevation: 1,411 ft / 430 m
Location: 46.238100 6.109010
Magnetic Var: 2.493 E

METAR

LSGG 190650Z VRB02KT 9999 FEW008 BKN012 06/05 Q1018 NOSIG

TAF

TAF AMD LSGG 190606Z 1906/2012 VRB02KT 9999 MIFG FEW020 TX17/1916Z TN04/1906Z TN03/2006Z PROB30 TEMPO 1906/1908 3

Frequencies

REC - 124.75 MHz - ATIS
GND - 121.75 MHz - GENEVA APRON
GND - 121.67 MHz - GENEVA GROUND
TWR - 118.70 MHz - GENEVA TOWER
DEP - 131.32 MHz - GENEVA DEPARTURE
APP - 136.45 MHz - GENEVA TRANSIT
APP - 130.55 MHz - GENEVA APPROACH

REC - 135.57 MHz - ATIS
GND - 121.85 MHz - GENEVA APRON
GND - 119.70 MHz - GENEVA GROUND
TWR - 119.90 MHz - GENEVA TOWER
DEP - 119.52 MHz - GENEVA DEPARTURE
APP - 136.25 MHz - GENEVA ARRIVAL
APP - 120.30 MHz - GENEVA FINAL

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04	164 ft 50 m	12,806 ft 3,903 m	45.42 42.93	CONCRETE	1,076 ft 328 m	0 ft 0 m
22	164 ft 50 m	12,806 ft 3,903 m	225.45 222.95	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04	LOC-ILS	INE	110.90 MHz	18 nm 33 km	45.44 42.95	-	1,411 ft 1,411 m
22	LOC-ILS	ISW	109.90 MHz	18 nm 33 km	225.44 222.95	-	1,411 ft 1,411 m
04	GS	INE	110.90 MHz	10 nm 19 km	45.44 42.95	3.00	1,411 ft 1,411 m
22	GS	ISW	109.90 MHz	10 nm 19 km	225.44 222.95	3.00	1,411 ft 1,411 m

EKCH

Region: DENMARK / FAROE ISLANDS
Timezone: EUROPE/COPENHAGEN
Runways: 3

Elevation: 17 ft / 5 m
Location: 55.617900 12.656000
Magnetic Var: 4.650 E

METAR

EKCH 190650Z AUTO 15010KT 9999 BKN025/// 03/M02 Q1023 NOSIG

TAF

TAF EKCH 190506Z 1906/2006 16012KT 9999 BKN025 BECMG 2000/2003 21010KT BKN010 BECMG 2003/2006 27005KT BKN005

Frequencies

REC - 122.75 MHz - KASTRUP ARRIVAL INFORMATION
CLD - 119.90 MHz - CLEARANCE DELIVERY
GND - 121.72 MHz - APRON
TWR - 118.10 MHz - TOWER (ARRIVAL)
TWR - 118.70 MHz - TOWER (VFR)
APP - 120.20 MHz - FINAL
DEP - 120.25 MHz - DEPARTURE
APP - 118.45 MHz - ARRIVAL

REC - 122.85 MHz - KASTRUP DEPARTURE INFORMATION
GND - 121.62 MHz - APRON
GND - 121.90 MHz - APRON
TWR - 118.57 MHz - TOWER
TWR - 119.35 MHz - TOWER (DEPARTURE)
APP - 119.80 MHz - COPPENHAGEN APPROACH
DEP - 124.95 MHz - DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04L	148 ft 45 m	11,695 ft 3,565 m	41.13 36.48	ASPHALT	0 ft 0 m	0 ft 0 m
22R	148 ft 45 m	11,695 ft 3,565 m	221.16 216.51	ASPHALT	1,870 ft 570 m	0 ft 0 m
04R	148 ft 45 m	10,814 ft 3,296 m	41.14 36.49	ASPHALT	0 ft 0 m	0 ft 0 m
22L	148 ft 45 m	10,814 ft 3,296 m	221.17 216.52	ASPHALT	0 ft 0 m	0 ft 0 m
12	148 ft 45 m	10,046 ft 3,062 m	123.21 118.56	ASPHALT	2,306 ft 703 m	0 ft 0 m
30	148 ft 45 m	10,046 ft 3,062 m	303.24 298.59	ASPHALT	886 ft 270 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04L	DME	CH	110.50 MHz	18 nm 33 km	- -	-	14 ft 14 m
12	DME	KA	109.90 MHz	18 nm 33 km	- -	-	14 ft 14 m
22L	DME	OXS	109.50 MHz	18 nm 33 km	- -	-	7 ft 7 m
22R	DME	KLK	110.90 MHz	18 nm 33 km	- -	-	14 ft 14 m
30	DME	OY	108.90 MHz	18 nm 33 km	- -	-	9 ft 9 m
04L	LOC-ILS	CH	110.50 MHz	18 nm 33 km	41.16 36.51	-	17 ft 17 m
04R	LOC-ILS	NE	109.30 MHz	18 nm 33 km	41.18 36.53	-	17 ft 17 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12	LOC-ILS	KA	109.90 MHz	18 nm 33 km	123.25 118.60	-	17 ft 17 m
22L	LOC-ILS	OXS	109.50 MHz	18 nm 33 km	221.14 216.49	-	17 ft 17 m
22R	LOC-ILS	KLK	110.90 MHz	18 nm 33 km	221.14 216.49	-	17 ft 17 m
30	LOC-ILS	OY	108.90 MHz	18 nm 33 km	303.23 298.58	-	17 ft 17 m
04L	GS	CH	110.50 MHz	10 nm 19 km	41.32 36.67	3.00	17 ft 17 m
04R	GS	NE	109.30 MHz	10 nm 19 km	41.32 36.67	3.00	17 ft 17 m
12	GS	KA	109.90 MHz	10 nm 19 km	123.46 118.81	3.00	17 ft 17 m
22L	GS	OXS	109.50 MHz	10 nm 19 km	221.32 216.67	3.00	17 ft 17 m
22R	GS	KLK	110.90 MHz	10 nm 19 km	221.32 216.67	3.00	17 ft 17 m
30	GS	OY	108.90 MHz	10 nm 19 km	303.46 298.81	3.00	17 ft 17 m