ZGGG
Baiyun Intl


-

OMDB
Dubai Intl

2024/03/29 0712Z

ZGGG TZ DUB03 OMDB

3147.58 nm / 5829.32 km



Notes

Generated

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
ZGGG APT	–	23.37682 113.28350	0 ft 0 m	–	–
TZ NDB	–	26.71075 92.79946	0 ft 0 m	1131	TEZPUR NDB
DUB03 FIX	–	25.26236 55.34948	0 ft 0 m	2016	–
OMDB APT	–	25.26213 55.34757	0 ft 0 m	0	–

ZGGG

Region: CHINA
Timezone: ASIA/SHANGHAI
Runways: 3

Elevation: 50 ft / 15 m
Location: 23.390400 113.303000
Magnetic Var: 3.291 W

METAR

ZGGG 290700Z VRB02MPS 9999 FEW040 31/19 Q1012 NOSIG

TAF

TAF ZGGG 282113Z 2900/2924 16004MPS 6000 BKN040 TX30/2907Z TN21/2922Z TEMPO 2908/2912 TSRA SCT030CB BKN033 TEMPO

Frequencies

REC - 128.60 MHz - ATIS
CLD - 121.95 MHz - CLEARANCE DELIVERY
GND - 121.85 MHz - BAIYUN GROUND
GND - 121.97 MHz - BAIYUN APRON
TWR - 118.10 MHz - BAIYUN TOWER
TWR - 118.25 MHz - BAIYUN TOWER
APP - 126.55 MHz - GUANGZHOU APPROACH
APP - 121.05 MHz - GUANGZHOU APPROACH
APP - 121.17 MHz - GUANGZHOU APPROACH

REC - 127.00 MHz - ATIS
GND - 121.75 MHz - BAIYUN GROUND
GND - 121.77 MHz - BAIYUN APRON
GND - 121.82 MHz - BAIYUN APRON
TWR - 118.80 MHz - BAIYUN TOWER
DEP - 119.70 MHz - GUANGZHOU DEPARTURE
APP - 126.35 MHz - GUANGZHOU APPROACH
APP - 120.40 MHz - GUANGZHOU APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
02R	197 ft 60 m	12,518 ft 3,815 m	13.92 17.21	CONCRETE	0 ft 0 m	387 ft 118 m
20L	197 ft 60 m	12,518 ft 3,815 m	193.92 197.21	CONCRETE	0 ft 0 m	390 ft 119 m
02L	197 ft 60 m	12,522 ft 3,817 m	13.91 17.20	CONCRETE	0 ft 0 m	394 ft 120 m
20R	197 ft 60 m	12,522 ft 3,817 m	193.91 197.20	CONCRETE	650 ft 198 m	400 ft 122 m
01	148 ft 45 m	11,860 ft 3,615 m	13.91 17.20	CONCRETE	0 ft 0 m	397 ft 121 m
19	148 ft 45 m	11,860 ft 3,615 m	193.91 197.20	CONCRETE	0 ft 0 m	400 ft 122 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
02L	DME	IOO	109.30 MHz	18 nm 33 km	- -	-	59 ft 59 m
02R	DME	IBB	110.90 MHz	18 nm 33 km	- -	-	64 ft 64 m
20L	DME	IAA	110.30 MHz	18 nm 33 km	- -	-	64 ft 64 m
20R	DME	IPP	111.50 MHz	18 nm 33 km	- -	-	50 ft 50 m
01	LOC-ILS	IOO	109.30 MHz	18 nm 33 km	13.91 17.20	-	50 ft 50 m
02L	LOC-ILS	IBB	110.90 MHz	18 nm 33 km	13.91 17.20	-	50 ft 50 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
02R	LOC-ILS	IDM	108.50 MHz	18 nm 33 km	13.92 17.21	-	50 ft 50 m
19	LOC-ILS	IPP	111.50 MHz	18 nm 33 km	193.91 197.20	-	50 ft 50 m
20L	LOC-ILS	IXL	111.90 MHz	18 nm 33 km	193.92 197.21	-	50 ft 50 m
20R	LOC-ILS	IAA	110.75 MHz	18 nm 33 km	193.91 197.20	-	50 ft 50 m

OMDB

Region: UNITED ARAB EMIRATES
Timezone: ASIA/DUBAI
Runways: 2

Elevation: 62 ft / 19 m
Location: 25.251100 55.371100
Magnetic Var: 2.347 E

METAR

OMDB 290700Z 27015KT 240V310 9999 FEW035 26/15 Q1013 NOSIG

TAF

TAF OMDB 290500Z 2906/3012 27015KT 9999 FEW035 BECMG 2917/2919 19005KT PROB30 2923/3004 4000 HZ BKN010 BECMG 3006/

Frequencies

REC - 126.27 MHz - ATIS ARRIVAL
TWR - 126.77 MHz - DUBAI TOWER
TWR - 118.75 MHz - DUBAI TOWER
GND - 118.35 MHz - DUBAI GROUND
GND - 121.65 MHz - DUBAI GROUND
APP - 122.50 MHz - MINHAD APPROACH
APP - 120.25 MHz - DUBAI ARRIVAL
APP - 124.90 MHz - DUBAI ARRIVAL
DEP - 121.02 MHz - DUBAI DEPARTURE
DEP - 120.25 MHz - DUBAI DEPARTURE
APP - 126.02 MHz - DUBAI RADAR

REC - 131.70 MHz - ATIS DEPARTURE
TWR - 119.55 MHz - DUBAI TOWER
TWR - 119.05 MHz - DUBAI TOWER
GND - 118.85 MHz - DUBAI GROUND
CLD - 120.35 MHz - CLEARANCE DELIVERY
APP - 126.02 MHz - MINHAD APPROACH
APP - 124.45 MHz - DUBAI ARRIVAL
DEP - 126.02 MHz - DUBAI DEPARTURE
DEP - 126.20 MHz - DUBAI DEPARTURE
APP - 120.40 MHz - DUBAI RADAR
APP - 127.90 MHz - DUBAI DIRECT

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
12R	200 ft 61 m	14,604 ft 4,452 m	121.53 119.18	ASPHALT	2,352 ft 717 m	771 ft 235 m
30L	200 ft 61 m	14,604 ft 4,452 m	301.54 299.20	ASPHALT	436 ft 133 m	0 ft 0 m
12L	200 ft 61 m	14,289 ft 4,355 m	121.48 119.14	ASPHALT	1,496 ft 456 m	381 ft 116 m
30R	200 ft 61 m	14,289 ft 4,355 m	301.50 299.15	ASPHALT	991 ft 302 m	377 ft 115 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12L	DME	IDBL	110.10 MHz	18 nm 33 km	- -	-	62 ft 62 m
30L	DME	IDBW	111.30 MHz	18 nm 33 km	- -	-	41 ft 41 m
30R	DME	IDBR	110.90 MHz	18 nm 33 km	- -	-	44 ft 44 m
12L	LOC-ILS	IDBL	110.10 MHz	18 nm 33 km	121.49 119.14	-	62 ft 62 m
12R	LOC-ILS	IDBE	109.50 MHz	18 nm 33 km	121.54 119.19	-	62 ft 62 m
30L	LOC-ILS	IDBW	111.30 MHz	18 nm 33 km	301.54 299.19	-	62 ft 62 m
30R	LOC-ILS	IDBR	110.90 MHz	18 nm 33 km	301.49 299.14	-	62 ft 62 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12L	GS	IDBL	110.10 MHz	10 nm 19 km	121.49 119.14	3.00	62 ft 62 m
12R	GS	IDBE	109.50 MHz	10 nm 19 km	121.54 119.19	3.00	62 ft 62 m
30L	GS	IDBW	111.30 MHz	10 nm 19 km	301.54 299.19	3.00	62 ft 62 m
30R	GS	IDBR	110.90 MHz	10 nm 19 km	301.49 299.14	3.00	62 ft 62 m