
LFPG – LGAV

Paris Charles De Gaulle — Athens Intl Airport Elefterios Venizel

2024/03/19 0435Z

LFPG MELKO **UM606** MANAG **UM139** LUL **UL613** NATLI **UG42** HOC **UL613** AKADO **UL615** NAKIT **UN606** PUL **UL611** ZDA **UL607** XORKI LGAV

1153.35 nm / 2136.01 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 37000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: no

- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LFPG APT	–	49.00974 2.56262	0 ft 0 m	–	Paris Charles De Gaulle
MELKO FIX	–	48.27806 4.67361	33,700 ft 10,272 m	94	–
MANAG FIX	UM606 AWY-HI	48.10306 5.16583	35,000 ft 10,668 m	22	–
LUL VOR	UM139 AWY-HI	47.68828 6.29558	35,000 ft 10,668 m	51	LUXEUIL VOR
NATLI FIX	UL613 AWY-HI	47.49194 7.50722	35,000 ft 10,668 m	50	–
HOC VOR	UG42 AWY-HI	47.46656 7.66544	35,000 ft 10,668 m	6	HOCHWALD VOR-DME
DITON FIX	UL613 AWY-HI	47.30222 8.33333	35,000 ft 10,668 m	28	–
RIPUS FIX	UL613 AWY-HI	47.26028 8.50000	35,000 ft 10,668 m	7	–
MANEG FIX	UL613 AWY-HI	47.20417 8.72222	35,000 ft 10,668 m	9	–
ELMUR FIX	UL613 AWY-HI	47.15667 8.90750	35,000 ft 10,668 m	8	–
ARGAX FIX	UL613 AWY-HI	47.05000 9.29806	35,000 ft 10,668 m	17	–
RONAK FIX	UL613 AWY-HI	46.81056 10.15056	35,000 ft 10,668 m	37	–
SUXAN FIX	UL613 AWY-HI	46.56222 10.47917	35,000 ft 10,668 m	20	–
BORMI FIX	UL613 AWY-HI	46.03611 11.16667	35,000 ft 10,668 m	42	–
VIC VOR	UL613 AWY-HI	45.63720 11.67638	35,000 ft 10,668 m	32	VICENZA VOR-DME
LAPAB FIX	UL613 AWY-HI	45.52944 11.97167	35,000 ft 10,668 m	13	–
AKADO FIX	UL613 AWY-HI	45.33333 12.50000	35,000 ft 10,668 m	25	–
ROTAR FIX	UL615 AWY-HI	45.26278 12.99556	35,000 ft 10,668 m	21	–
NAKIT FIX	UL615 AWY-HI	45.18806 13.44778	35,000 ft 10,668 m	19	–
PUL VOR	UN606 AWY-HI	44.89237 13.91813	35,000 ft 10,668 m	26	PULA VOR-DME
ZDA VOR	UL611 AWY-HI	44.09532 15.36421	35,000 ft 10,668 m	78	ZADAR VOR-DME
SPL VOR	UL607 AWY-HI	43.49658 16.30472	35,000 ft 10,668 m	54	SPLIT VOR-DME
NERRA FIX	UL607 AWY-HI	42.90528 17.54333	35,000 ft 10,668 m	64	–
DBK VOR	UL607 AWY-HI	42.55384 18.27743	35,000 ft 10,668 m	38	DUBROVNIK VOR-DME
KONUV FIX	UL607 AWY-HI	42.43594 18.43672	35,000 ft 10,668 m	9	–
TIMUS FIX	UL607 AWY-HI	42.34611 18.55750	35,000 ft 10,668 m	7	–
LASTI	UL607	42.10044	35,000 ft	20	–

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
FIX	AWY-HI	18.88508	10,668 m		
LEBGA	UL607	41.88314	35,000 ft	18	-
FIX	AWY-HI	19.17172	10,668 m		
PETAK	UL607	41.77528	35,000 ft	9	-
FIX	AWY-HI	19.31389	10,668 m		
TRN	UL607	41.41612	35,000 ft	28	TIRANA VOR-DME
VOR	AWY-HI	19.71819	10,668 m		
PINDO	UL607	40.48083	35,000 ft	79	-
FIX	AWY-HI	20.95583	10,668 m		
PIKOS	UL607	39.96167	35,000 ft	41	-
FIX	AWY-HI	21.55000	10,668 m		
XORKI	UL607	38.16972	23,500 ft	141	-
FIX	AWY-HI	23.50917	7,163 m		
LGAV	-	37.93636	0 ft	24	Athens Intl Airport Elefterios Venizel
APT	-	23.94447	0 m		

LFPG

Region: FRANCE
Timezone: EUROPE/PARIS
Runways: 4

Elevation: 392 ft / 119 m
Location: 49.009700 2.562570
Magnetic Var: 1.476 E

METAR

LFPG 190400Z AUTO 00000KT 9000 BKN033 BKN041 BKN047 09/08 Q1017

TAF

TAF LFPG 181755Z 1818/1924 CNL

Frequencies

REC - 128.32 MHz - ATIS
TWR - 120.90 MHz - DE GAULLE TOWER
TWR - 119.62 MHz - DE GAULLE TOWER
TWR - 118.65 MHz - DE GAULLE TOWER
TWR - 120.65 MHz - DE GAULLE TOWER
GND - 125.30 MHz - DE GAULLE GROUND
CLD - 121.80 MHz - CLEARANCE DELIVERY
APP - 119.85 MHz - DE GAULLE APPROACH
APP - 125.82 MHz - DE GAULLE APPROACH
DEP - 124.35 MHz - DE GAULLE DEPARTURE
DEP - 131.20 MHz - DE GAULLE DEPARTURE

REC - 127.12 MHz - ATIS
TWR - 125.32 MHz - DE GAULLE TOWER
TWR - 119.25 MHz - DE GAULLE TOWER
TWR - 123.60 MHz - DE GAULLE TOWER
GND - 121.90 MHz - DE GAULLE GROUND
GND - 121.70 MHz - DE GAULLE GROUND
APP - 118.15 MHz - DE GAULLE APPROACH
APP - 121.15 MHz - DE GAULLE APPROACH
APP - 126.42 MHz - DE GAULLE APPROACH
DEP - 126.57 MHz - DE GAULLE DEPARTURE
DEP - 133.37 MHz - DE GAULLE DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08L	148 ft 45 m	13,713 ft 4,180 m	85.31 83.83	ASPHALT	0 ft 0 m	489 ft 149 m
26R	148 ft 45 m	13,713 ft 4,180 m	265.35 263.88	ASPHALT	1,877 ft 572 m	279 ft 85 m
09L	197 ft 60 m	8,866 ft 2,703 m	85.32 83.84	ASPHALT	0 ft 0 m	0 ft 0 m
27R	197 ft 60 m	8,866 ft 2,703 m	265.35 263.87	ASPHALT	0 ft 0 m	0 ft 0 m
08R	197 ft 60 m	8,833 ft 2,692 m	85.33 83.85	ASPHALT	0 ft 0 m	489 ft 149 m
26L	197 ft 60 m	8,833 ft 2,692 m	265.35 263.88	ASPHALT	0 ft 0 m	486 ft 148 m
09R	148 ft 45 m	13,746 ft 4,190 m	85.30 83.82	ASPHALT	0 ft 0 m	0 ft 0 m
27L	148 ft 45 m	13,746 ft 4,190 m	265.34 263.87	ASPHALT	1,959 ft 597 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08R	DME	DSE	108.55 MHz	18 nm 33 km	- -	-	358 ft 358 m
09L	DME	PNE	109.35 MHz	18 nm 33 km	- -	-	392 ft 392 m
09R	DME	CGE	110.10 MHz	18 nm 33 km	- -	-	392 ft 392 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
26L	DME	DSU	108.35 MHz	18 nm	– –	–	338 ft 338 m
27L	DME	CGW	110.70 MHz	18 nm 33 km	– –	–	407 ft 407 m
27R	DME	PNW	110.35 MHz	18 nm 33 km	– –	–	392 ft 392 m
08L	LOC-ILS	GLE	108.70 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
08R	LOC-ILS	DSE	108.55 MHz	18 nm 33 km	85.34 83.86	–	392 ft 392 m
09L	LOC-ILS	PNE	109.35 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
09R	LOC-ILS	CGE	110.10 MHz	18 nm 33 km	85.32 83.84	–	392 ft 392 m
26L	LOC-ILS	DSU	108.35 MHz	18 nm 33 km	265.34 263.86	–	392 ft 392 m
26R	LOC-ILS	GAU	111.95 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
27L	LOC-ILS	CGW	110.70 MHz	18 nm 33 km	265.32 263.84	–	392 ft 392 m
27R	LOC-ILS	PNW	110.35 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
08L	GS	GLE	108.70 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
08R	GS	DSE	108.55 MHz	10 nm 19 km	85.34 83.86	3.00	392 ft 392 m
09L	GS	PNE	109.35 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
09R	GS	CGE	110.10 MHz	10 nm 19 km	85.32 83.84	3.00	392 ft 392 m
26L	GS	DSU	108.35 MHz	10 nm 19 km	265.34 263.86	3.00	392 ft 392 m
26R	GS	GAU	111.95 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m
27L	GS	CGW	110.70 MHz	10 nm 19 km	265.32 263.84	3.00	392 ft 392 m
27R	GS	PNW	110.35 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m

LGAV

Region: GREECE
Timezone: EUROPE/ATHENS
Runways: 2

Elevation: 308 ft / 94 m
Location: 37.936700 23.944500
Magnetic Var: 5.093 E

METAR

LGAV 190420Z 29003KT 9999 FEW030 07/06 Q1011 NOSIG

TAF

TAF TAF LGAV 182300Z 1900/1924 VRB05KT 9999 FEW030 SCT070 BECMG 1905/1907 SCT025 BKN070 PROB40 TEMPO 1912/1924 50

Frequencies

REC - 136.12 MHz - ATIS
REC - 124.02 MHz - ATHENS INFORMATION
TWR - 122.10 MHz - VENIZELOS TOWER
GND - 121.75 MHz - VENIZELOS GROUND
GND - 121.90 MHz - VENIZELOS GROUND
CLD - 118.67 MHz - CLEARANCE DELIVERY
APP - 130.25 MHz - ATHENS APPROACH
APP - 126.57 MHz - ATHENS APPROACH
APP - 121.40 MHz - ATHENS APPROACH
APP - 118.47 MHz - ATHENS DIRECT
DEP - 128.95 MHz - ATHENS DEPARTURE
REC - 131.17 MHz - ATHENS INFORMATION
TWR - 136.27 MHz - VENIZELOS TOWER
TWR - 118.62 MHz - VENIZELOS TOWER
GND - 121.95 MHz - VENIZELOS GROUND
GND - 121.80 MHz - VENIZELOS GROUND
APP - 132.97 MHz - ATHENS APPROACH
APP - 128.95 MHz - ATHENS APPROACH
APP - 125.52 MHz - ATHENS APPROACH
APP - 121.40 MHz - ATHENS DIRECT
DEP - 118.30 MHz - ATHENS DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03R	151 ft 46 m	13,135 ft 4,004 m	36.87 31.78	ASPHALT	984 ft 300 m	394 ft 120 m
21L	151 ft 46 m	13,135 ft 4,004 m	216.89 211.80	ASPHALT	984 ft 300 m	394 ft 120 m
03L	151 ft 46 m	12,478 ft 3,803 m	36.86 31.76	ASPHALT	984 ft 300 m	394 ft 120 m
21R	151 ft 46 m	12,478 ft 3,803 m	216.87 211.78	ASPHALT	984 ft 300 m	394 ft 120 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03L	DME	IATL	110.50 MHz	18 nm 33 km	- -	-	255 ft 255 m
21L	DME	IEVL	111.10 MHz	18 nm 33 km	- -	-	303 ft 303 m
21R	DME	IEVR	110.50 MHz	18 nm 33 km	- -	-	282 ft 282 m
03L	LOC-ILS	IATL	110.50 MHz	18 nm 33 km	36.52 31.43	-	282 ft 282 m
03R	LOC-ILS	IATR	111.10 MHz	18 nm 33 km	36.97 31.88	-	302 ft 302 m
21L	LOC-ILS	IEVL	111.10 MHz	18 nm 33 km	216.52 211.43	-	271 ft 271 m
21R	LOC-ILS	IEVR	110.50 MHz	18 nm 33 km	216.50 211.41	-	255 ft 255 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03L	GS	IATL	110.50 MHz	10 nm	37.04	3.00	255 ft
				19 km	31.94		255 m
03R	GS	IATR	111.10 MHz	10 nm	37.07	3.00	271 ft
				19 km	31.97		271 m
21L	GS	IEVL	111.10 MHz	10 nm	217.07	3.00	302 ft
				19 km	211.97		302 m
21R	GS	IEVR	110.50 MHz	10 nm	217.04	3.00	282 ft
				19 km	211.94		282 m