

# KSAN

San Diego Intl


# KLAX

Los Angeles Intl

2024/05/02 1427Z

KSAN MZB KLAX

94.97 nm / 175.89 km



## Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: no
- Use high airways: yes



## Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KSAN	-	32.73350	0 ft	-	San Diego Intl
APT	-	-117.19000	0 m		
MZB	-	32.78220	1,200 ft	3	MISSION BAY (SAN DIEGO)
VOR	-	-117.22500	366 m		
KLAX	-	33.94320	0 ft	91	Los Angeles Intl
APT	-	-118.40800	0 m		

## KSAN

Region: UNITED STATES  
Timezone: AMERICA/LOS\_ANGELES  
Runways: 1

Elevation: 17 ft / 5 m  
Location: 32.733600 -117.190000  
Magnetic Var: 10.972 E

## METAR

KSAN 021351Z 18006KT 7SM OVC016 16/12 A2993 RMK A02 SLP133 T01610117 \$

## TAF

TAF KSAN 021120Z 0212/0318 VRB04KT P6SM OVC016 FM021600 18006KT P6SM BKN021 FM021900 24009KT P6SM BKN021 TEMPO 021

## Frequencies

REC - 134.80 MHz - LINDBERGH ATIS	CLD - 125.90 MHz - LINDBERGH CLEARANCE
GND - 123.90 MHz - LINDBERGH GROUND	TWR - 118.30 MHz - LINDBERGH TOWER
DEP - 119.60 MHz - SOCAL WEST DEPARTURE	DEP - 124.35 MHz - SOCAL EAST DEPARTURE
APP - 119.60 MHz - SOCAL WEST APPROACH	APP - 124.35 MHz - SOCAL EAST APPROACH

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	200 ft	9,388 ft	106.13	ASPHALT	1,004 ft	390 ft
	61 m	2,861 m	95.16		306 m	119 m
27	200 ft	9,388 ft	286.15	ASPHALT	1,811 ft	0 ft
	61 m	2,861 m	275.18		552 m	0 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09	DME	ISAN	111.55 MHz	18 nm	-	-	29 ft
				33 km	-		29 m
27	DME	IUBR	110.90 MHz	18 nm	-	-	26 ft
				33 km	-		26 m
09	LOC-ILS	ISAN	111.55 MHz	18 nm	106.14	-	17 ft
				33 km	95.17		17 m
27	LOC-LOC	IUBR	110.90 MHz	18 nm	286.14	-	17 ft
				33 km	275.17		17 m
09	GS	ISAN	111.55 MHz	10 nm	106.14	3.10	17 ft
				19 km	95.17		17 m

## KLAX

Region: UNITED STATES  
Timezone: AMERICA/LOS\_ANGELES  
Runways: 4

Elevation: 125 ft / 38 m  
Location: 33.943100 -118.409000  
Magnetic Var: 11.443 E

## METAR

KLAX 021353Z 26006KT 8SM FEW009 OVC016 15/13 A2992 RMK AO2 SLP130 T01500128 \$

## TAF

TAF KLAX 021138Z 0212/0318 10005KT P6SM OVC012 FM021800 25007KT P6SM FEW020 FM022100 26012KT P6SM SKC FM030300 260

## Frequencies

COM - 122.95 MHz - UNICOM	GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.75 MHz - LOS ANGELES GROUND	GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER	TWR - 120.95 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER	REC - 133.80 MHz - D-ATIS
REC - 135.65 MHz - D-ATIS	APP - 124.90 MHz - SOCAL APPROACH
APP - 124.30 MHz - SOCAL APPROACH	APP - 124.50 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH	DEP - 125.20 MHz - SOCAL DEPARTURE
DEP - 124.30 MHz - SOCAL DEPARTURE	CLD - 120.35 MHz - CLEARANCE DELIVERY

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft	11,106 ft	82.96	CONCRETE	0 ft	381 ft
	61 m	3,385 m	71.51		0 m	116 m
25L	200 ft	11,106 ft	262.98	CONCRETE	0 ft	381 ft
	61 m	3,385 m	251.53		0 m	116 m
07L	151 ft	12,935 ft	82.95	CONCRETE	846 ft	374 ft
	46 m	3,943 m	71.51		258 m	114 m
25R	151 ft	12,935 ft	262.98	CONCRETE	968 ft	197 ft
	46 m	3,943 m	251.53		295 m	60 m
06R	151 ft	10,896 ft	82.95	CONCRETE	551 ft	384 ft
	46 m	3,321 m	71.50		168 m	117 m
24L	151 ft	10,896 ft	262.97	CONCRETE	814 ft	384 ft
	46 m	3,321 m	251.52		248 m	117 m
06L	151 ft	8,936 ft	82.95	CONCRETE	0 ft	0 ft
	46 m	2,724 m	71.51		0 m	0 m
24R	151 ft	8,936 ft	262.96	CONCRETE	0 ft	285 ft
	46 m	2,724 m	251.52		0 m	87 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
06R	DME	IGPE	111.70 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
07L	DME	IIAS	111.10 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
07R	DME	IMKZ	109.90 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
24L	DME	IHQB	111.70 MHz	18 nm	-	-	133 ft
				33 km	-		133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	- -	-	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	- -	-	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	- -	-	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.54	-	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.54	-	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.54	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.54	3.00	125 ft 125 m