
EIDW – LFMN

Dublin — Nice/Cote d'Azur

2024/03/29 0854Z

EIDW DEKAP **UL18** MID **UN615** XAMAB **UL612** RESMI **UM975** ATN **UZ12** BULOL **UM733** OKTET LFMN

811.73 nm / 1503.32 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EIDW APT	–	53.42826 -6.25955	0 ft 0 m	–	Dublin
DEKAP FIX	–	52.43111 -4.37250	31,400 ft 9,571 m	90	–
MEDOG FIX	UL18 AWY-HI	51.95028 -3.54944	35,000 ft 10,668 m	41	–
DIKAS FIX	UL18 AWY-HI	51.77694 -3.25917	35,000 ft 10,668 m	14	–
BASET FIX	UL18 AWY-HI	51.56389 -1.71000	35,000 ft 10,668 m	59	–
INLAK FIX	UL18 AWY-HI	51.47806 -1.52417	35,000 ft 10,668 m	8	–
NIGIT FIX	UL18 AWY-HI	51.31306 -1.17083	35,000 ft 10,668 m	16	–
VAPID FIX	UL18 AWY-HI	51.25389 -1.04500	35,000 ft 10,668 m	5	–
MID VOR	UL18 AWY-HI	51.05389 -0.62500	35,000 ft 10,668 m	19	MIDHURST VOR-DME
BOGNA FIX	UN615 AWY-HI	50.70194 -0.25167	35,000 ft 10,668 m	25	–
BENBO FIX	UN615 AWY-HI	50.45139 0.01028	35,000 ft 10,668 m	18	–
HAWKE FIX	UN615 AWY-HI	50.37417 0.09028	35,000 ft 10,668 m	5	–
XAMAB FIX	UN615 AWY-HI	50.20444 0.26472	35,000 ft 10,668 m	12	–
VEULE FIX	UL612 AWY-HI	49.85667 0.62000	35,000 ft 10,668 m	24	–
RESMI FIX	UL612 AWY-HI	48.56861 2.19194	35,000 ft 10,668 m	98	–
PEKIM FIX	UM975 AWY-HI	48.27583 2.82556	35,000 ft 10,668 m	30	–
PILUL FIX	UM975 AWY-HI	48.08333 3.04806	35,000 ft 10,668 m	14	–
PIMUP FIX	UM975 AWY-HI	47.54028 3.38750	35,000 ft 10,668 m	35	–
PIXIS FIX	UM975 AWY-HI	46.94028 3.75389	35,000 ft 10,668 m	39	–
ATN VOR	UM975 AWY-HI	46.80594 4.25914	35,000 ft 10,668 m	22	–
MOMIL FIX	UZ12 AWY-HI	46.54611 4.54667	35,000 ft 10,668 m	19	–
BULOL FIX	UZ12 AWY-HI	46.04583 5.09194	35,000 ft 10,668 m	37	–
GIPNO FIX	UM733 AWY-HI	45.56000 5.52917	27,900 ft 8,504 m	34	–
OKTET FIX	UM733 AWY-HI	44.48500 6.56944	19,500 ft 5,944 m	78	–
LFMN APT	–	43.65798 7.21536	0 ft 0 m	56	Nice/Cote d’Azur

EIDW

Region: IRELAND
Timezone: EUROPE/DUBLIN
Runways: 2

Elevation: 240 ft / 73 m
Location: 53.424900 -6.263080
Magnetic Var: 1.994 W

METAR

EIDW 290830Z 13004KT 9999 FEW018CB SCT050 07/04 Q0978 NOSIG

TAF

TAF EIDW 290500Z 2906/3006 VRB03KT 9999 FEW025 SCT040 TEMPO 2907/2921 -SHRA FEW018CB BECMG 2908/2910 16012KT PROB

Frequencies

REC - 124.52 MHz - ATIS
GND - 118.75 MHz - DUBLIN GROUND
CLD - 121.87 MHz - CLEARANCE DELIVERY
APP - 121.10 MHz - DUBLIN APPROACH
APP - 119.55 MHz - DUBLIN APPROACH

TWR - 118.60 MHz - DUBLIN TOWER
GND - 121.80 MHz - DUBLIN GROUND
APP - 133.27 MHz - DUBLIN APPROACH
APP - 119.92 MHz - DUBLIN APPROACH
REC - 118.50 MHz - DUBLIN INFORMATION

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10R	148 ft 45 m	8,660 ft 2,640 m	95.26 97.25	ASPHALT	0 ft 0 m	0 ft 0 m
28L	148 ft 45 m	8,660 ft 2,640 m	275.29 277.28	ASPHALT	0 ft 0 m	0 ft 0 m
16	190 ft 58 m	6,805 ft 2,074 m	156.64 158.63	ASPHALT	0 ft 0 m	0 ft 0 m
34	190 ft 58 m	6,805 ft 2,074 m	336.65 338.64	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	DME	IAC	111.50 MHz	18 nm 33 km	- -	-	200 ft 200 m
10R	LOC-ILS	IDE	108.90 MHz	18 nm 33 km	95.26 97.25	-	242 ft 242 m
16	LOC-ILS	IAC	111.50 MHz	18 nm 33 km	156.64 158.63	-	242 ft 242 m
28L	LOC-ILS	IDW	111.35 MHz	18 nm 33 km	275.26 277.25	-	242 ft 242 m
10R	GS	IDE	108.90 MHz	10 nm 19 km	95.26 97.25	3.00	242 ft 242 m
16	GS	IAC	111.50 MHz	10 nm 19 km	156.64 158.63	3.00	242 ft 242 m
28L	GS	IDW	111.35 MHz	10 nm 19 km	275.26 277.25	3.00	242 ft 242 m

LFMN

Region: FRANCE
Timezone: UNKNOWN
Runways: 2

Elevation: 12 ft / 4 m
Location: 43.658400 7.215760
Magnetic Var: 2.723 E

METAR

LFMN 290830Z 34009KT 9999 FEW040 OVC250 15/10 Q1009 NOSIG

TAF

TAF LFMN 290800Z 2909/3015 34010KT 9999 FEW040 BKN250 BECMG 2909/2911 08015KT TEMPO 2914/2919 09025KT PROB30 TEMP

Frequencies

REC - 129.60 MHz - NICE ATIS
TWR - 118.70 MHz - NICE TOWER
APP - 134.47 MHz - NICE WEST APPROACH
APP - 128.20 MHz - NICE APPROACH
GND - 121.70 MHz - NICE GROUND
TWR - 123.15 MHz - NICE TOWER
APP - 120.65 MHz - NICE APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04R	148 ft 45 m	9,706 ft 2,958 m	44.86 42.14	ASPHALT	0 ft 0 m	417 ft 127 m
22L	148 ft 45 m	9,706 ft 2,958 m	224.88 222.16	ASPHALT	0 ft 0 m	525 ft 160 m
04L	148 ft 45 m	8,992 ft 2,741 m	44.86 42.14	ASPHALT	0 ft 0 m	161 ft 49 m
22R	148 ft 45 m	8,992 ft 2,741 m	224.88 222.15	ASPHALT	564 ft 172 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04L	DME	NI	109.95 MHz	27 nm 50 km	- -	-	12 ft 12 m
04R	DME	NA	110.70 MHz	27 nm 50 km	- -	-	12 ft 12 m
04L	LOC-ILS	NI	109.95 MHz	18 nm 33 km	44.87 42.15	-	12 ft 12 m
04R	LOC-ILS	NA	110.70 MHz	18 nm 33 km	44.87 42.15	-	12 ft 12 m
04L	GS	NI	109.95 MHz	10 nm 19 km	44.87 42.15	3.00	12 ft 12 m
04R	GS	NA	110.70 MHz	10 nm 19 km	44.87 42.15	3.00	12 ft 12 m