SKAR
EL EDEN


-

KFLL
Fort Lauderdale Hollywood Intl

2024/03/19 1022Z

SKAR RNG **UG438** BUTAL **UQ105** KILER **UG430** UCA **UA301** URSUS **A509** ELLEE KFLL

1338.14 nm / 2478.24 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 360ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
SKAR APT	-	4.45278 -75.76649	0 ft 0 m	-	EL EDEN
RNG VOR	-	5.98056 -75.41833	33,600 ft 10,241 m	94	RIONEGRO VOR-DME
BUTAL FIX	UG438 AWY-HI	7.85361 -75.45722	34,000 ft 10,363 m	112	-
EKATI FIX	UQ105 AWY-HI	10.00000 -75.87722	34,000 ft 10,363 m	131	-
KILER FIX	UQ105 AWY-HI	15.00000 -76.88000	34,000 ft 10,363 m	305	-
BEREX FIX	UG430 AWY-HI	16.34694 -77.27722	34,000 ft 10,363 m	84	-
SIA VOR	UG430 AWY-HI	18.50106 -77.92411	34,000 ft 10,363 m	134	SANGSTER VOR-DME
PUTUL FIX	UG430 AWY-HI	19.97611 -78.29333	34,000 ft 10,363 m	91	-
UCA DME	UG430 AWY-HI	22.01506 -78.81582	34,000 ft 10,363 m	125	CIEGO DE AVILA VOR-DME
URSUS FIX	UA301 AWY-HI	24.00005 -79.06980	28,700 ft 8,748 m	120	-
ELLEE FIX	A509 AWY-HI	24.88061 -79.69002	16,200 ft 4,938 m	62	-
KFLL APT	- -	26.07164 -80.15269	0 ft 0 m	75	Fort Lauderdale Hollywood Intl

KFLL

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 2

Elevation: 65 ft / 20 m
Location: 26.071300 -80.149500
Magnetic Var: 7.376 W

METAR

KFLL 190953Z 32012G21KT 10SM FEW026 BKN070 OVC100 22/17 A2997 RMK AO2 SLP147 T02220167

TAF

TAF AMD KFLL 190834Z 1909/2012 29007KT P6SM VCSH FEW025 BKN250 FM191100 34010KT P6SM SCT025 SCT070 SCT250 FM19160

Frequencies

REC - 135.00 MHz - D-ATIS
CLD - 128.40 MHz - CLEARANCE DELIVERY
GND - 121.70 MHz - FORT LAUDERDALE GROUND
TWR - 120.20 MHz - FORT LAUDERDALE TOWER
APP - 119.45 MHz - MIAMI APPROACH
DEP - 128.60 MHz - MIAMI DEPARTURE
DEP - 119.70 MHz - MIAMI DEPARTURE

COM - 122.95 MHz - UNICOM
GND - 121.40 MHz - FORT LAUDERDALE GROUND
TWR - 119.30 MHz - FORT LAUDERDALE TOWER
APP - 118.10 MHz - MIAMI APPROACH
APP - 133.77 MHz - MIAMI APPROACH
DEP - 126.05 MHz - MIAMI DEPARTURE
DEP - 119.45 MHz - MIAMI DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10L	151 ft 46 m	9,008 ft 2,746 m	90.36 97.73	CONCRETE	577 ft 176 m	341 ft 104 m
28R	151 ft 46 m	9,008 ft 2,746 m	270.37 277.75	CONCRETE	607 ft 185 m	453 ft 138 m
10R	151 ft 46 m	8,006 ft 2,440 m	90.36 97.74	CONCRETE	0 ft 0 m	597 ft 182 m
28L	151 ft 46 m	8,006 ft 2,440 m	270.37 277.75	CONCRETE	0 ft 0 m	604 ft 184 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10L	DME	ILHI	110.10 MHz	18 nm 33 km	- -	-	11 ft 11 m
28R	DME	IUDL	110.70 MHz	18 nm 33 km	- -	-	10 ft 10 m
10L	LOC-LOC	ILHI	110.10 MHz	18 nm 33 km	90.36 97.74	-	62 ft 62 m
10R	LOC-LOC	IFLL	111.75 MHz	18 nm 33 km	90.33 97.71	-	62 ft 62 m
28L	LOC-LOC	IADI	111.75 MHz	18 nm 33 km	270.33 277.71	-	62 ft 62 m
28R	LOC-LOC	IUDL	110.70 MHz	18 nm 33 km	270.36 277.74	-	62 ft 62 m
10L	GS	ILHI	110.10 MHz	10 nm 19 km	90.36 97.74	3.00	62 ft 62 m
10R	GS	IFLL	111.75 MHz	10 nm 19 km	90.33 97.71	3.00	62 ft 62 m
28L	GS	IADI	111.75 MHz	10 nm 19 km	270.33 277.71	3.00	62 ft 62 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
28R	GS	IUDL	110.70 MHz	10 nm 19 km	270.36 277.74	3.00	62 ft 62 m