MPTO
Tocumen Intl


-

SVMI
Caracas Simon Bolivar Intl

2024/03/19 0854Z

MPTO MUBAR **UA553** PBL SVMI

746.60 nm / 1382.71 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 39000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
MPTO APT	– –	9.07136 -79.38346	0 ft 0 m	–	Tocumen Intl
MUBAR FIX	– –	8.85481 -78.97678	9,700 ft 2,957 m	27	–
ESEDA FIX	UA553 AWY-HI	9.02797 -77.41642	35,000 ft 10,668 m	93	–
MGN VOR	UA553 AWY-HI	9.28722 -74.84694	35,000 ft 10,668 m	153	MAGANGUE VOR-DME
UGOTA FIX	UA553 AWY-HI	9.42361 -73.90472	35,000 ft 10,668 m	56	–
SIDOS FIX	UA553 AWY-HI	9.53583 -73.11528	35,000 ft 10,668 m	47	–
DALEX FIX	UA553 AWY-HI	9.72142 -71.83536	35,000 ft 10,668 m	76	–
EKERI FIX	UA553 AWY-HI	9.76142 -71.53036	35,000 ft 10,668 m	18	–
IROSA FIX	UA553 AWY-HI	9.80808 -71.18203	35,000 ft 10,668 m	20	–
BODIS FIX	UA553 AWY-HI	9.82975 -71.02703	35,000 ft 10,668 m	9	–
BRM VOR	UA553 AWY-HI	10.04253 -69.35197	29,900 ft 9,114 m	99	BARQUISIMETO VOR-DME
PBL VOR	UA553 AWY-HI	10.48419 -68.07781	23,500 ft 7,163 m	79	PUERTO CABELLO VOR-DME
SVMI APT	– –	10.60312 -66.99059	0 ft 0 m	64	Caracas Simon Bolivar Intl

MPTO

Region: PANAMA
Timezone: AMERICA/PANAMA
Runways: 2

Elevation: 134 ft / 41 m
Location: 9.071400 -79.383500
Magnetic Var: 5.432 W

METAR

MPTO 190800Z VRB02KT 9999 FEW020 24/23 Q1009 NOSIG

TAF

TAF MPTO 190500Z 1906/2012 27006KT 9999 FEW020 TEMPO 1906/1910 VRB02KT TEMPO 1917/1921 15008KT SCT018TCU SCT090 T

Frequencies

REC - 127.70 MHz - ATIS
GND - 121.90 MHz - TOCUMEN GROUND
CLD - 129.80 MHz - CLEARANCE DELIVERY
APP - 123.30 MHz - PANAMA APPROACH
APP - 119.20 MHz - PANAMA APPROACH
TWR - 118.10 MHz - TOCUMEN TOWER
GND - 112.05 MHz - TOCUMEN GROUND
APP - 121.20 MHz - PANAMA APPROACH
APP - 119.70 MHz - PANAMA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03R	148 ft 45 m	10,049 ft 3,063 m	29.33 34.76	CONCRETE	0 ft 0 m	0 ft 0 m
21L	148 ft 45 m	10,049 ft 3,063 m	209.33 214.76	CONCRETE	0 ft 0 m	0 ft 0 m
03L	148 ft 45 m	8,832 ft 2,692 m	30.67 36.10	ASPHALT	814 ft 248 m	0 ft 0 m
21R	148 ft 45 m	8,832 ft 2,692 m	210.67 216.11	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03R	DME	INAT	110.70 MHz	18 nm 33 km	- -	-	50 ft 50 m
03R	LOC-ILS	INAT	110.70 MHz	18 nm 33 km	29.33 34.76	-	134 ft 134 m
03R	GS	INAT	110.70 MHz	10 nm 19 km	29.33 34.76	3.00	134 ft 134 m

SVMI

Region: VENEZUELA
Timezone: AMERICA/CARACAS
Runways: 2

Elevation: 234 ft / 71 m
Location: 10.603200 -66.990400
Magnetic Var: 12.859 W

METAR

UNKNOWN

TAF

TAF SVMI 190400Z 1906/2006 09002KT 9999 FEW016 TX25/1902Z TN24/1904Z TEMPO 1904/1906 09006KT 9999 SCT016 SCT100

Frequencies

CLD - 119.50 MHz - CLEARANCE DELIVERY
TWR - 118.40 MHz - MAIQUETIA TOWER
DEP - 120.10 MHz - MAIQUETIA DEPARTURE
GND - 121.90 MHz - MAIQUETIA GROUND
APP - 120.40 MHz - MAIQUETIA APPROACH
REC - 132.85 MHz - ATIS

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10	151 ft 46 m	11,494 ft 3,503 m	88.13 100.99	ASPHALT	0 ft 0 m	187 ft 57 m
28	151 ft 46 m	11,494 ft 3,503 m	268.13 280.99	ASPHALT	0 ft 0 m	187 ft 57 m
09	151 ft 46 m	9,523 ft 2,903 m	75.94 88.80	ASPHALT	0 ft 0 m	0 ft 0 m
27	151 ft 46 m	9,523 ft 2,903 m	255.95 268.81	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10	DME	IMIQ	110.10 MHz	18 nm 33 km	- -	-	235 ft 235 m
10	LOC-ILS	IMIQ	110.10 MHz	18 nm 33 km	87.90 100.76	-	235 ft 235 m
10	GS	IMIQ	110.10 MHz	10 nm 19 km	88.29 101.15	3.00	235 ft 235 m