KORD
CHICAGO OHARE INTL


-

KIND
Indianapolis Intl

2024/03/19 0221Z

KORD LUCIT KIND

154.60 nm / 286.32 km



Notes

Basic altitude profile:
- Ascent Rate: 1500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KORD APT	–	41.98274 -87.90631	0 ft 0 m	-	CHICAGO OHARE INTL
LUCIT FIX	–	41.23234 -87.42372	17,800 ft 5,425 m	50	-
KIND APT	–	39.71809 -86.29267	0 ft 0 m	104	Indianapolis Intl

KORD

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 6
Elevation: 680 ft / 207 m
Location: 41.973400 -87.906600
Magnetic Var: 4.102 W

METAR

KORD 190151Z 23005KT 10SM CLR 00/M08 A3006 RMK AO2 SLP188 T00001083

TAF

TAF KORD 182320Z 1900/2006 24011KT P6SM FEW050 SCT300 FM190600 23012G24KT P6SM BKN100 FM191400 26018G30KT P6SM SC

Frequencies

REC - 135.40 MHz - ATIS
CLD - 119.25 MHz - CLEARANCE DELIVERY
GND - 118.05 MHz - O'HARE GROUND
GND - 121.75 MHz - O'HARE GROUND
GND - 124.12 MHz - O'HARE GROUND
TWR - 120.75 MHz - O'HARE TOWER
TWR - 126.90 MHz - O'HARE TOWER
TWR - 132.70 MHz - O'HARE TOWER
TWR - 133.00 MHz - O'HARE TOWER
APP - 133.62 MHz - CHICAGO APPROACH
APP - 125.70 MHz - CHICAGO APPROACH
DEP - 125.40 MHz - CHICAGO DEPARTURE
DEP - 128.80 MHz - CHICAGO DEPARTURE
COM - 122.95 MHz - UNICOM
CLD - 121.60 MHz - CLEARANCE DELIVERY
GND - 121.67 MHz - O'HARE GROUND
GND - 121.90 MHz - O'HARE GROUND
GND - 134.12 MHz - O'HARE GROUND
TWR - 121.15 MHz - O'HARE TOWER
TWR - 127.92 MHz - O'HARE TOWER
TWR - 128.15 MHz - O'HARE TOWER
APP - 119.00 MHz - CHICAGO APPROACH
APP - 124.35 MHz - CHICAGO APPROACH
DEP - 125.00 MHz - CHICAGO DEPARTURE
DEP - 127.40 MHz - CHICAGO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10C	200 ft 61 m	10,789 ft 3,289 m	89.85 93.95	CONCRETE	0 ft 0 m	397 ft 121 m
28C	200 ft 61 m	10,789 ft 3,289 m	269.88 273.98	CONCRETE	0 ft 0 m	381 ft 116 m
10L	151 ft 46 m	12,996 ft 3,961 m	89.87 93.98	CONCRETE	0 ft 0 m	394 ft 120 m
28R	151 ft 46 m	12,996 ft 3,961 m	269.91 274.01	CONCRETE	0 ft 0 m	285 ft 87 m
04R	151 ft 46 m	8,074 ft 2,461 m	41.40 45.50	CONCRETE	0 ft 0 m	850 ft 259 m
22L	151 ft 46 m	8,074 ft 2,461 m	221.41 225.52	CONCRETE	0 ft 0 m	584 ft 178 m
09R	151 ft 46 m	7,949 ft 2,423 m	89.98 94.08	CONCRETE	0 ft 0 m	148 ft 45 m
27L	151 ft 46 m	7,949 ft 2,423 m	270.00 274.10	CONCRETE	0 ft 0 m	197 ft 60 m
09L	151 ft 46 m	7,484 ft 2,281 m	89.99 94.09	CONCRETE	0 ft 0 m	397 ft 121 m
27R	151 ft 46 m	7,484 ft 2,281 m	270.00 274.11	CONCRETE	0 ft 0 m	397 ft 121 m
10R	151 ft 46 m	7,484 ft 2,281 m	89.85 93.95	CONCRETE	0 ft 0 m	400 ft 122 m
28L	151 ft 46 m	7,484 ft 2,281 m	269.87 273.97	CONCRETE	0 ft 0 m	400 ft 122 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	ISAJ	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
10L	DME	IMED	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
27L	DME	IIAC	110.50 MHz	18 nm 33 km	– –	–	641 ft 641 m
27R	DME	IABU	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
28R	DME	ITSL	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
04R	LOC-ILS	IFJU	110.10 MHz	18 nm 33 km	41.41 45.51	–	680 ft 680 m
09L	LOC-ILS	ISAJ	111.75 MHz	18 nm 33 km	90.00 94.10	–	680 ft 680 m
09R	LOC-ILS	IJAV	110.50 MHz	18 nm 33 km	89.99 94.09	–	680 ft 680 m
10L	LOC-ILS	IMED	111.10 MHz	18 nm 33 km	89.89 93.99	–	680 ft 680 m
10C	LOC-ILS	ISXH	108.95 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
10R	LOC-ILS	IIZJ	110.75 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
22L	LOC-ILS	ILQQ	110.10 MHz	18 nm 33 km	221.41 225.51	–	680 ft 680 m
27L	LOC-ILS	IIAC	110.50 MHz	18 nm 33 km	269.99 274.09	–	680 ft 680 m
27R	LOC-ILS	IABU	111.75 MHz	18 nm 33 km	270.00 274.10	–	680 ft 680 m
28L	LOC-ILS	IVQX	110.75 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28C	LOC-ILS	IVZE	108.95 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28R	LOC-ILS	ITSL	111.10 MHz	18 nm 33 km	269.88 273.98	–	680 ft 680 m
04R	GS	IFJU	110.10 MHz	10 nm 19 km	41.41 45.51	3.00	680 ft 680 m
09L	GS	ISAJ	111.75 MHz	10 nm 19 km	90.00 94.10	3.00	680 ft 680 m
09R	GS	IJAV	110.50 MHz	10 nm 19 km	89.99 94.09	3.00	680 ft 680 m
10L	GS	IMED	111.10 MHz	10 nm 19 km	89.89 93.99	3.00	680 ft 680 m
10C	GS	ISXH	108.95 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
10R	GS	IIZJ	110.75 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
22L	GS	ILQQ	110.10 MHz	10 nm 19 km	221.41 225.51	3.00	680 ft 680 m
27L	GS	IIAC	110.50 MHz	10 nm 19 km	269.99 274.09	3.00	680 ft 680 m
27R	GS	IABU	111.75 MHz	10 nm 19 km	270.00 274.10	3.00	680 ft 680 m
28L	GS	IVQX	110.75 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28C	GS	IVZE	108.95 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28R	GS	ITSL	111.10 MHz	10 nm 19 km	269.88 273.98	3.00	680 ft 680 m

KIND

Region: UNITED STATES
Timezone: AMERICA/INDIANA/INDIANAPOLIS
Runways: 3
Elevation: 793 ft / 242 m
Location: 39.718200 -86.292800
Magnetic Var: 5.022 W

METAR

KIND 190154Z 29010KT 10SM OVC042 00/M08 A3015 RMK AO2 SLP217 T00001083

TAF

TAF AMD KIND 190214Z 1902/2006 30009KT P6SM BKN040 FM190500 26009KT P6SM FEW250 FM191300 23014G23KT P6SM FEW250 FM

Frequencies

REC - 124.40 MHz - ATIS
COM - 122.95 MHz - UNICOM
GND - 121.80 MHz - INDY GROUND
TWR - 120.90 MHz - INDY TOWER
APP - 119.30 MHz - INDIANAPOLIS APPROACH
APP - 127.15 MHz - INDIANAPOLIS APPROACH
DEP - 124.95 MHz - INDIANAPOLIS DEPARTURE
REC - 134.25 MHz - ATIS
CLD - 128.75 MHz - CLEARANCE DELIVERY
GND - 121.90 MHz - INDY GROUND
TWR - 127.82 MHz - INDY TOWER
APP - 124.65 MHz - INDIANAPOLIS APPROACH
DEP - 119.05 MHz - INDIANAPOLIS DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05L	151 ft 46 m	11,210 ft 3,417 m	44.43 49.45	CONCRETE	0 ft 0 m	0 ft 0 m
23R	151 ft 46 m	11,210 ft 3,417 m	224.45 229.47	CONCRETE	0 ft 0 m	0 ft 0 m
05R	151 ft 46 m	10,009 ft 3,051 m	44.45 49.47	CONCRETE	0 ft 0 m	0 ft 0 m
23L	151 ft 46 m	10,009 ft 3,051 m	224.47 229.49	CONCRETE	0 ft 0 m	0 ft 0 m
14	151 ft 46 m	7,284 ft 2,220 m	134.65 139.67	CONCRETE	0 ft 0 m	0 ft 0 m
32	151 ft 46 m	7,284 ft 2,220 m	314.66 319.69	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05L	DME	IIND	111.75 MHz	18 nm 33 km	- -	-	1,010 ft 1,010 m
05R	DME	IOQV	111.15 MHz	18 nm 33 km	- -	-	797 ft 797 m
23L	DME	IFVJ	111.15 MHz	18 nm 33 km	- -	-	797 ft 797 m
23R	DME	IUZK	111.75 MHz	18 nm 33 km	- -	-	1,010 ft 1,010 m
05L	LOC-ILS	IIND	111.75 MHz	18 nm 33 km	44.45 49.47	-	797 ft 797 m
05R	LOC-ILS	IOQV	111.15 MHz	18 nm 33 km	44.46 49.48	-	797 ft 797 m
14	LOC-ILS	IBJP	110.50 MHz	18 nm 33 km	134.67 139.69	-	797 ft 797 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
23L	LOC-ILS	IFVJ	111.15 MHz	18 nm	224.43	-	797 ft
				33 km	229.45		797 m
23R	LOC-ILS	IUZK	111.75 MHz	18 nm	224.42	-	797 ft
				33 km	229.44		797 m
32	LOC-ILS	ICOA	110.50 MHz	18 nm	314.66	-	797 ft
				33 km	319.68		797 m
05L	GS	IIND	111.75 MHz	10 nm	44.86	3.00	741 ft
				19 km	49.88		741 m
05R	GS	IOQV	111.15 MHz	10 nm	44.88	3.00	790 ft
				19 km	49.90		790 m
14	GS	IBJP	110.50 MHz	10 nm	135.34	3.00	797 ft
				19 km	140.36		797 m
23L	GS	IFVJ	111.15 MHz	10 nm	224.88	3.00	788 ft
				19 km	229.90		788 m
23R	GS	IUZK	111.75 MHz	10 nm	224.86	3.00	777 ft
				19 km	229.88		777 m
32	GS	ICOA	110.50 MHz	10 nm	315.34	3.00	797 ft
				19 km	320.36		797 m