KSBP
San Luis Co Rgnl


-

KLAX
Los Angeles Intl

2024/03/27 0504Z

KSBP 3500N12000W KLAX

135.83 nm / 251.56 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: no
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KSBP APT	–	35.23714 −120.64346	0 ft 0 m	–	San Luis Co Rgnl
3500N12000W LATLON	–	35.00000 −120.00000	11,300 ft 3,444 m	34	–
KLAX APT	–	33.94313 −118.40892	0 ft 0 m	101	Los Angeles Intl

KSBP

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 2
Elevation: 212 ft / 65 m
Location: 35.237200 -120.644000
Magnetic Var: 12.111 E

METAR

KSBP 270356Z 33012KT 10SM CLR 12/08 A3013 RMK AO2 SLP204 T01220083

TAF

KSBP 270000Z 2700/2724 31015G25KT P6SM SKC FM270300 31012KT P6SM SKC FM270600 VRB03KT P6SM SCT015 SCT250 FM272000

Frequencies

COM - 124.00 MHz - CTAF
REC - 120.60 MHz - ATIS
TWR - 124.00 MHz - SAN LUIS TOWER
DEP - 127.72 MHz - SANTA BARBARA DEPARTURE
COM - 122.95 MHz - SAN LUIS UNICOM
GND - 121.60 MHz - SAN LUIS GROUND
APP - 127.72 MHz - SANTA BARBARA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
11	150 ft 46 m	6,105 ft 1,861 m	124.88 112.77	ASPHALT	801 ft 244 m	594 ft 181 m
29	150 ft 46 m	6,105 ft 1,861 m	304.89 292.78	ASPHALT	502 ft 153 m	614 ft 187 m
07	100 ft 31 m	2,495 ft 760 m	89.79 77.68	ASPHALT	0 ft 0 m	0 ft 0 m
25	100 ft 31 m	2,495 ft 760 m	269.80 257.68	ASPHALT	0 ft 0 m	299 ft 91 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11	LOC-ILS	ISBP	109.70 MHz	18 nm 33 km	124.89 112.78	-	212 ft 212 m
11	GS	ISBP	109.70 MHz	10 nm 19 km	124.89 112.78	3.00	212 ft 212 m

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4
Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.452 E

METAR

KLAX 270353Z 24005KT 10SM CLR 13/09 A3010 RMK AO2 SLP190 T01280094

TAF

KLAX 270335Z 2704/2806 26008KT P6SM FEW250 FM270600 VRB03KT P6SM FEW250 FM271000 VRB03KT P6SM BKN015 FM271600 080

Frequencies

COM - 122.95 MHz - UNICOM
GND - 121.75 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER
REC - 135.65 MHz - D-ATIS
APP - 124.30 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH
DEP - 124.30 MHz - SOCAL DEPARTURE
GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 120.95 MHz - LOS ANGELES TOWER
REC - 133.80 MHz - D-ATIS
APP - 124.90 MHz - SOCAL APPROACH
APP - 124.50 MHz - SOCAL APPROACH
DEP - 125.20 MHz - SOCAL DEPARTURE
CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft 61 m	11,106 ft 3,385 m	82.96 71.51	CONCRETE	0 ft 0 m	381 ft 116 m
25L	200 ft 61 m	11,106 ft 3,385 m	262.98 251.53	CONCRETE	0 ft 0 m	381 ft 116 m
07L	151 ft 46 m	12,935 ft 3,943 m	82.95 71.50	CONCRETE	846 ft 258 m	374 ft 114 m
25R	151 ft 46 m	12,935 ft 3,943 m	262.98 251.52	CONCRETE	968 ft 295 m	197 ft 60 m
06R	151 ft 46 m	10,896 ft 3,321 m	82.95 71.49	CONCRETE	551 ft 168 m	384 ft 117 m
24L	151 ft 46 m	10,896 ft 3,321 m	262.97 251.52	CONCRETE	814 ft 248 m	384 ft 117 m
06L	151 ft 46 m	8,936 ft 2,724 m	82.95 71.50	CONCRETE	0 ft 0 m	0 ft 0 m
24R	151 ft 46 m	8,936 ft 2,724 m	262.96 251.51	CONCRETE	0 ft 0 m	285 ft 87 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm 33 km	- -	-	120 ft 120 m
06R	DME	IGPE	111.70 MHz	18 nm 33 km	- -	-	120 ft 120 m
07L	DME	IIAS	111.10 MHz	18 nm 33 km	- -	-	103 ft 103 m
07R	DME	IMKZ	109.90 MHz	18 nm 33 km	- -	-	103 ft 103 m
24L	DME	IHQB	111.70 MHz	18 nm 33 km	- -	-	133 ft 133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	– –	–	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	– –	–	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	– –	–	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.53	–	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.52	–	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.52	–	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.53	–	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.53	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.53	3.00	125 ft 125 m