
KORD – CYUL

CHICAGO OHARE INTL — Montreal Pierre E Trudeau Intl

2024/03/19 0637Z

KORD PMM **J547** FNT **J94** ECK **J546** MAVOD **J579** TUKIR CYUL

651.34 nm / 1206.29 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: no
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KORD APT	- -	41.98274 -87.90631	0 ft 0 m	-	CHICAGO OHARE INTL
PMM VOR	- -	42.46603 -86.10481	29,400 ft 8,961 m	85	PULLMAN VOR-DME
HASTE FIX	J547 AWY-HI	42.67095 -85.16736	35,000 ft 10,668 m	43	-
DEWIT FIX	J547 AWY-HI	42.80254 -84.55000	35,000 ft 10,668 m	28	-
FNT VOR	J547 AWY-HI	42.96678 -83.74697	35,000 ft 10,668 m	36	FLINT VORTAC
ABELE FIX	J94 AWY-HI	43.16594 -83.04264	35,000 ft 10,668 m	33	-
ECK VOR	J94 AWY-HI	43.25589 -82.71792	35,000 ft 10,668 m	15	PECK VORTAC
ECK24 FIX	J546 AWY-HI	43.40473 -82.20875	35,000 ft 10,668 m	23	-
DENGA FIX	J546 AWY-HI	43.47336 -81.97283	35,000 ft 10,668 m	11	-
HEIMS FIX	J546 AWY-HI	43.67783 -81.25681	35,000 ft 10,668 m	33	-
YSO VOR	J546 AWY-HI	44.23861 -79.17167	35,000 ft 10,668 m	96	-
AMERT FIX	J546 AWY-HI	44.66167 -77.88834	35,000 ft 10,668 m	60	-
MAVOD FIX	J546 AWY-HI	45.06667 -76.87333	27,800 ft 8,473 m	49	-
TUKIR FIX	J579 AWY-HI	45.19333 -76.23500	21,800 ft 6,645 m	28	-
CYUL APT	- -	45.46727 -73.74403	0 ft 0 m	106	Montreal Pierre E Trudeau Intl

KORD

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 6

Elevation: 680 ft / 207 m
Location: 41.973400 -87.906600
Magnetic Var: 4.102 W

METAR

KORD 190551Z 24012G20KT 10SM FEW120 SCT250 M01/M09 A2999 RMK AO2 SLP164 T10061089 10011 21006 400281044 56019

TAF

TAF KORD 190520Z 1906/2012 24012G24KT P6SM BKN100 FM191400 25020G33KT P6SM SCT250 FM191800 28018G28KT P6SM FEW050

Frequencies

REC - 135.40 MHz - ATIS
CLD - 119.25 MHz - CLEARANCE DELIVERY
GND - 118.05 MHz - O'HARE GROUND
GND - 121.75 MHz - O'HARE GROUND
GND - 124.12 MHz - O'HARE GROUND
TWR - 120.75 MHz - O'HARE TOWER
TWR - 126.90 MHz - O'HARE TOWER
TWR - 132.70 MHz - O'HARE TOWER
TWR - 133.00 MHz - O'HARE TOWER
APP - 133.62 MHz - CHICAGO APPROACH
APP - 125.70 MHz - CHICAGO APPROACH
DEP - 125.40 MHz - CHICAGO DEPARTURE
DEP - 128.80 MHz - CHICAGO DEPARTURE
COM - 122.95 MHz - UNICOM
CLD - 121.60 MHz - CLEARANCE DELIVERY
GND - 121.67 MHz - O'HARE GROUND
GND - 121.90 MHz - O'HARE GROUND
GND - 134.12 MHz - O'HARE GROUND
TWR - 121.15 MHz - O'HARE TOWER
TWR - 127.92 MHz - O'HARE TOWER
TWR - 128.15 MHz - O'HARE TOWER
APP - 119.00 MHz - CHICAGO APPROACH
APP - 124.35 MHz - CHICAGO APPROACH
DEP - 125.00 MHz - CHICAGO DEPARTURE
DEP - 127.40 MHz - CHICAGO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10C	200 ft 61 m	10,789 ft 3,289 m	89.85 93.95	CONCRETE	0 ft 0 m	397 ft 121 m
28C	200 ft 61 m	10,789 ft 3,289 m	269.88 273.98	CONCRETE	0 ft 0 m	381 ft 116 m
10L	151 ft 46 m	12,996 ft 3,961 m	89.87 93.98	CONCRETE	0 ft 0 m	394 ft 120 m
28R	151 ft 46 m	12,996 ft 3,961 m	269.91 274.01	CONCRETE	0 ft 0 m	285 ft 87 m
04R	151 ft 46 m	8,074 ft 2,461 m	41.40 45.50	CONCRETE	0 ft 0 m	850 ft 259 m
22L	151 ft 46 m	8,074 ft 2,461 m	221.41 225.52	CONCRETE	0 ft 0 m	584 ft 178 m
09R	151 ft 46 m	7,949 ft 2,423 m	89.98 94.08	CONCRETE	0 ft 0 m	148 ft 45 m
27L	151 ft 46 m	7,949 ft 2,423 m	270.00 274.10	CONCRETE	0 ft 0 m	197 ft 60 m
09L	151 ft 46 m	7,484 ft 2,281 m	89.99 94.09	CONCRETE	0 ft 0 m	397 ft 121 m
27R	151 ft 46 m	7,484 ft 2,281 m	270.00 274.11	CONCRETE	0 ft 0 m	397 ft 121 m
10R	151 ft 46 m	7,484 ft 2,281 m	89.85 93.95	CONCRETE	0 ft 0 m	400 ft 122 m
28L	151 ft 46 m	7,484 ft 2,281 m	269.87 273.97	CONCRETE	0 ft 0 m	400 ft 122 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	ISAJ	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
10L	DME	IMED	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
27L	DME	IIAC	110.50 MHz	18 nm 33 km	– –	–	641 ft 641 m
27R	DME	IABU	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
28R	DME	ITSL	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
04R	LOC-ILS	IFJU	110.10 MHz	18 nm 33 km	41.41 45.51	–	680 ft 680 m
09L	LOC-ILS	ISAJ	111.75 MHz	18 nm 33 km	90.00 94.10	–	680 ft 680 m
09R	LOC-ILS	IJAV	110.50 MHz	18 nm 33 km	89.99 94.09	–	680 ft 680 m
10L	LOC-ILS	IMED	111.10 MHz	18 nm 33 km	89.89 93.99	–	680 ft 680 m
10C	LOC-ILS	ISXH	108.95 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
10R	LOC-ILS	IIZJ	110.75 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
22L	LOC-ILS	ILQQ	110.10 MHz	18 nm 33 km	221.41 225.51	–	680 ft 680 m
27L	LOC-ILS	IIAC	110.50 MHz	18 nm 33 km	269.99 274.09	–	680 ft 680 m
27R	LOC-ILS	IABU	111.75 MHz	18 nm 33 km	270.00 274.10	–	680 ft 680 m
28L	LOC-ILS	IVQX	110.75 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28C	LOC-ILS	IVZE	108.95 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28R	LOC-ILS	ITSL	111.10 MHz	18 nm 33 km	269.88 273.98	–	680 ft 680 m
04R	GS	IFJU	110.10 MHz	10 nm 19 km	41.41 45.51	3.00	680 ft 680 m
09L	GS	ISAJ	111.75 MHz	10 nm 19 km	90.00 94.10	3.00	680 ft 680 m
09R	GS	IJAV	110.50 MHz	10 nm 19 km	89.99 94.09	3.00	680 ft 680 m
10L	GS	IMED	111.10 MHz	10 nm 19 km	89.89 93.99	3.00	680 ft 680 m
10C	GS	ISXH	108.95 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
10R	GS	IIZJ	110.75 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
22L	GS	ILQQ	110.10 MHz	10 nm 19 km	221.41 225.51	3.00	680 ft 680 m
27L	GS	IIAC	110.50 MHz	10 nm 19 km	269.99 274.09	3.00	680 ft 680 m
27R	GS	IABU	111.75 MHz	10 nm 19 km	270.00 274.10	3.00	680 ft 680 m
28L	GS	IVQX	110.75 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28C	GS	IVZE	108.95 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28R	GS	ITSL	111.10 MHz	10 nm 19 km	269.88 273.98	3.00	680 ft 680 m

CYUL

Region: CANADA
Timezone: AMERICA/MONTREAL
Runways: 3

Elevation: 118 ft / 36 m
Location: 45.467500 -73.743800
Magnetic Var: 13.906 W

METAR

CYUL 190600Z 28013KT 15SM FEW022 OVC027 M01/M05 A2963 RMK SC2SC6 SLP037

TAF

TAF CYUL 190540Z 1906/2006 28010G20KT P6SM OVC030 TEMPO 1906/1920 5SM -SHSN OVC020 FM192000 25010G20KT P6SM BKN03

Frequencies

TWR - 119.90 MHz - MONTREAL TOWER
TWR - 124.30 MHz - MONTREAL TOWER
GND - 121.90 MHz - MONTREAL GROUND
APP - 132.85 MHz - MONTREAL APPROACH
DEP - 124.65 MHz - MONTREAL DEPARTURE
REC - 133.70 MHz - ATIS
COM - 123.55 MHz - QUEBEC FIC
COM - 134.15 MHz - VFR ADVISORY

TWR - 119.30 MHz - MONTREAL TOWER
GND - 121.00 MHz - MONTREAL GROUND
CLD - 125.60 MHz - CLEARANCE DELIVERY
APP - 126.90 MHz - MONTREAL APPROACH
DEP - 120.42 MHz - MONTREAL DEPARTURE
REC - 127.50 MHz - ATIS
COM - 126.70 MHz - QUEBEC FIC

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06L	197 ft 60 m	11,010 ft 3,356 m	42.55 56.46	ASPHALT	0 ft 0 m	0 ft 0 m
24R	197 ft 60 m	11,010 ft 3,356 m	222.57 236.48	ASPHALT	0 ft 0 m	0 ft 0 m
06R	197 ft 60 m	9,608 ft 2,929 m	42.59 56.49	CONCRETE	0 ft 0 m	0 ft 0 m
24L	197 ft 60 m	9,608 ft 2,929 m	222.60 236.51	CONCRETE	0 ft 0 m	0 ft 0 m
10	197 ft 60 m	7,008 ft 2,136 m	87.61 101.52	ASPHALT	0 ft 0 m	0 ft 0 m
28	197 ft 60 m	7,008 ft 2,136 m	267.63 281.53	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	LOC-ILS	IUL	109.30 MHz	18 nm 33 km	42.57 56.48	-	118 ft 118 m
06R	LOC-ILS	IOA	110.50 MHz	18 nm 33 km	42.60 56.51	-	118 ft 118 m
10	LOC-ILS	IDO	110.10 MHz	18 nm 33 km	87.62 101.53	-	118 ft 118 m
24L	LOC-ILS	IMQ	110.50 MHz	18 nm 33 km	222.60 236.51	-	118 ft 118 m
24R	LOC-ILS	IZZ	111.90 MHz	18 nm 33 km	222.57 236.48	-	118 ft 118 m
06L	GS	IUL	109.30 MHz	10 nm 19 km	42.57 56.48	3.00	118 ft 118 m
06R	GS	IOA	110.50 MHz	10 nm 19 km	42.60 56.51	3.00	118 ft 118 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10	GS	IDO	110.10 MHz	10 nm 19 km	87.62 101.53	3.00	118 ft 118 m
24L	GS	IMQ	110.50 MHz	10 nm 19 km	222.60 236.51	3.00	118 ft 118 m
24R	GS	IZZ	111.90 MHz	10 nm 19 km	222.57 236.48	3.00	118 ft 118 m