
PHOG
Kahului

PHKO
Kona Intl At Keahole

2024/03/28 2243Z

PHOG MYNAH PHKO

73.02 nm / 135.24 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
PHOG APT	–	20.89897 −156.43046	0 ft 0 m	–	Kahului
MYNAH FIX	–	19.81189 −156.08586	1,000 ft 305 m	68	–
PHKO APT	–	19.73934 −156.04576	0 ft 0 m	4	Kona Intl At Keahole

PHOG

Region: USA (HAWAII)
Timezone: PACIFIC/HONOLULU
Runways: 2

Elevation: 53 ft / 16 m
Location: 20.898600 -156.430000
Magnetic Var: 9.311 E

METAR

PHOG 282154Z 03025G36KT 10SM FEW030 SCT045 27/18 A3016

TAF

TAF AMD PHOG 281927Z 2819/2918 04020G35KT P6SM FEW025 SCT050 FM282000 06024G36KT P6SM FEW035 SCT050 FM290700 0501

Frequencies

REC - 128.60 MHz - ATIS
TWR - 118.70 MHz - MAUI TOWER
APP - 119.50 MHz - MAUI APPROACH
DEP - 119.50 MHz - MAUI DEPARTURE
COM - 122.95 MHz - KAHULUI UNICOM

GND - 121.90 MHz - MAUI GROUND
CLD - 120.60 MHz - MAUI CLEARANCE
APP - 120.20 MHz - MAUI APPROACH
DEP - 120.20 MHz - MAUI DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
02	150 ft 46 m	7,017 ft 2,139 m	34.83 25.52	ASPHALT	0 ft 0 m	226 ft 69 m
20	150 ft 46 m	7,017 ft 2,139 m	214.83 205.52	ASPHALT	0 ft 0 m	397 ft 121 m
05	150 ft 46 m	4,983 ft 1,519 m	64.87 55.56	ASPHALT	0 ft 0 m	0 ft 0 m
23	150 ft 46 m	4,983 ft 1,519 m	244.88 235.57	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
02	DME	IOGG	110.10 MHz	18 nm 33 km	- -	-	46 ft 46 m
02	LOC-ILS	IOGG	110.10 MHz	18 nm 33 km	34.83 25.52	-	53 ft 53 m
02	GS	IOGG	110.10 MHz	10 nm 19 km	34.83 25.52	3.10	53 ft 53 m

PHKO

Region: USA (HAWAII)
Timezone: PACIFIC/HONOLULU
Runways: 1

Elevation: 47 ft / 14 m
Location: 19.738800 -156.046000
Magnetic Var: 9.239 E

METAR

PHKO 282153Z 23010KT 10SM SCT045 28/19 A3013

TAF

TAF PHKO 281725Z 2818/2918 19010KT P6SM VCSH FEW025 BKN040 FM282000 22013KT P6SM FEW030 SCT060 FM290700 VRB05KT P6

Frequencies

REC - 127.40 MHz - ATIS
CLD - 118.60 MHz - CLEARANCE DELIVERY
GND - 121.90 MHz - KONA GROUND
DEP - 126.00 MHz - HONOLULU CENTER

COM - 120.30 MHz - CTAF
TWR - 120.30 MHz - KONA TOWER
APP - 126.00 MHz - HONOLULU CENTER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
17	150 ft 46 m	11,052 ft 3,369 m	184.78 175.54	ASPHALT	0 ft 0 m	400 ft 122 m
35	150 ft 46 m	11,052 ft 3,369 m	4.78 355.54	ASPHALT	0 ft 0 m	404 ft 123 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
17	DME	IKOA	109.70 MHz	18 nm 33 km	- -	-	43 ft 43 m
17	LOC-ILS	IKOA	109.70 MHz	18 nm 33 km	184.78 175.54	-	47 ft 47 m
17	GS	IKOA	109.70 MHz	10 nm 19 km	184.78 175.54	3.00	47 ft 47 m