LRCL
Avram Iancu


-

LROP
Bucharest Henri Coanda

2024/03/29 0549Z

LRCL MOBRA LROP

167.29 nm / 309.82 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 270ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LRCL APT	–	46.78920 23.69220	0 ft 0 m	–	Avram Iancu
MOBRA FIX	–	45.86440 24.81940	200 ft 61 m	72	–
LROP APT	–	44.57230 26.10230	0 ft 0 m	94	Bucharest Henri Coanda

LRCL

Region: ROMANIA
Timezone: EUROPE/BUCHAREST
Runways: 1

Elevation: 1,039 ft / 317 m
Location: 46.789200 23.692200
Magnetic Var: 6.247 E

METAR

LRCL 290530Z 28013KT CAVOK 11/03 Q1012

TAF

UNKNOWN

Frequencies

TWR - 134.40 MHz - CLUJ TOWER
REC - 125.52 MHz - CLUJ ATIS

APP - 126.42 MHz - NAPOC APROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07	148 ft 45 m	6,674 ft 2,034 m	71.77 65.52	CONCRETE	774 ft 236 m	0 ft 0 m
25	148 ft 45 m	6,674 ft 2,034 m	251.79 245.54	CONCRETE	0 ft 0 m	443 ft 135 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
25	DME	ICL	110.30 MHz	18 nm 33 km	- -	-	1,100 ft 1,100 m
25	LOC-ILS	ICX	111.90 MHz	18 nm 33 km	251.78 245.53	-	1,039 ft 1,039 m
25	GS	ICX	111.90 MHz	10 nm 19 km	251.78 245.53	3.00	1,039 ft 1,039 m

LROP

Region: ROMANIA
Timezone: EUROPE/BUCHAREST
Runways: 2

Elevation: 313 ft / 95 m
Location: 44.572300 26.102300
Magnetic Var: 6.278 E

METAR

LROP 290530Z 26007KT CAVOK 12/06 Q1014 NOSIG

TAF

TAF LROP 282300Z 2900/3000 25010KT CAVOK PROB40 TEMPO 2909/2915 26016G26KT BECMG 2915/2917 VRB04KT

Frequencies

REC - 118.50 MHz - OTOPENI ATIS
TWR - 121.85 MHz - OTOPENI TWR
GND - 121.70 MHz - OTOPENI GND
APP - 118.25 MHz - BUCHAREST APP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08R	148 ft 45 m	11,494 ft 3,503 m	83.90 77.62	ASPHALT	0 ft 0 m	0 ft 0 m
26L	148 ft 45 m	11,494 ft 3,503 m	263.93 257.65	ASPHALT	0 ft 0 m	0 ft 0 m
08L	148 ft 45 m	11,493 ft 3,503 m	83.91 77.63	ASPHALT	0 ft 0 m	0 ft 0 m
26R	148 ft 45 m	11,493 ft 3,503 m	263.94 257.66	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08L	DME	ILL	110.90 MHz	18 nm 33 km	- -	-	400 ft 400 m
08R	DME	IOP	110.30 MHz	18 nm 33 km	- -	-	400 ft 400 m
26L	DME	IOE	109.10 MHz	18 nm 33 km	- -	-	314 ft 314 m
26R	DME	IRR	110.70 MHz	18 nm 33 km	- -	-	400 ft 400 m
08L	LOC-ILS	ILL	110.90 MHz	18 nm 33 km	83.74 77.46	-	314 ft 314 m
08R	LOC-ILS	IOP	110.30 MHz	18 nm 33 km	83.74 77.46	-	303 ft 303 m
26L	LOC-ILS	IOE	109.10 MHz	18 nm 33 km	264.11 257.83	-	314 ft 314 m
26R	LOC-ILS	IRR	110.70 MHz	18 nm 33 km	264.12 257.84	-	314 ft 314 m
08L	GS	ILL	110.90 MHz	10 nm 19 km	84.84 78.56	3.00	314 ft 314 m
08R	GS	IOP	110.30 MHz	10 nm 19 km	84.81 78.53	2.70	314 ft 314 m
26L	GS	IOE	109.10 MHz	10 nm 19 km	264.81 258.53	2.70	303 ft 303 m
26R	GS	IRR	110.70 MHz	10 nm 19 km	264.84 258.56	3.00	314 ft 314 m