LCLK
Larnaca Airport


-

OLBA
Beirut Rafic Hariri

2024/03/28 0914Z

LCLK REXAL OLBA

111.99 nm / 207.41 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: no
- Use PACOTS: no
- Use low airways: yes
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LCLK APT	–	34.87380 33.62390	0 ft 0 m	–	Larnaca Airport
REXAL FIX	–	34.72330 33.89500	5,700 ft 1,737 m	16	–
OLBA APT	–	33.82050 35.48770	0 ft 0 m	95	Beirut Rafic Hariri

LCLK

Region: CYPRUS
Timezone: ASIA/NICOSIA
Runways: 1

Elevation: 11 ft / 3 m
Location: 34.873800 33.624000
Magnetic Var: 5.536 E

METAR

LCLK 280900Z 06011KT CAVOK 23/16 Q1017 NOSIG

TAF

TAF TAF LCLK 280530Z 2806/2906 06012KT CAVOK PROB30 TEMPO 2806/2807 5000 BR BKN003 BECMG 2815/2817 36008KT

Frequencies

REC - 126.55 MHz - LARNACA ATIS
GND - 119.40 MHz - LARNACA GROUND
TWR - 121.20 MHz - LARNACA TOWER
APP - 130.20 MHz - LARNACA APPROACH

CLD - 120.57 MHz - LARNACA CLEARANCE DELIVERY
GND - 121.90 MHz - LARNACA GROUND
TWR - 130.20 MHz - LARNACA TOWER
APP - 121.20 MHz - LARNACA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04	148 ft 45 m	9,832 ft 2,997 m	45.08 39.54	ASPHALT	0 ft 0 m	0 ft 0 m
22	148 ft 45 m	9,832 ft 2,997 m	225.09 219.56	ASPHALT	627 ft 191 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
22	DME	ILC	110.30 MHz	18 nm 33 km	- -	-	20 ft 20 m
22	LOC-ILS	ILC	110.30 MHz	18 nm 33 km	225.09 219.55	-	11 ft 11 m
22	GS	ILC	110.30 MHz	10 nm 19 km	225.09 219.55	2.75	11 ft 11 m

OLBA

Region: LEBANON
Timezone: UNKNOWN
Runways: 3

Elevation: 84 ft / 26 m
Location: 33.820500 35.487600
Magnetic Var: 5.433 E

METAR

OLBA 280900Z 29003KT 260V320 6000 NSC 24/12 Q1018 NOSIG

TAF

TAF OLBA 280400Z 2806/2912 VRB03KT 7000 FEW030 BKN090 PROB30 TEMPO 2806/2906 5000 HZ BECMG 2815/2817 02010KT BECMG

Frequencies

REC - 120.60 MHz - ATIS
GND - 121.90 MHz - BEIRUT HARIRI GROUND
APP - 120.30 MHz - BEIRUT APPROACH

TWR - 118.90 MHz - BEIRUT HARIRI TOWER
APP - 119.30 MHz - BEIRUT APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03	148 ft 45 m	12,484 ft 3,805 m	32.77 27.33	CONCRETE	1,821 ft 555 m	390 ft 119 m
21	148 ft 45 m	12,484 ft 3,805 m	212.78 207.35	CONCRETE	3,268 ft 996 m	390 ft 119 m
16	148 ft 45 m	11,168 ft 3,404 m	166.99 161.55	CONCRETE	591 ft 180 m	394 ft 120 m
34	148 ft 45 m	11,168 ft 3,404 m	346.99 341.56	CONCRETE	0 ft 0 m	341 ft 104 m
17	148 ft 45 m	10,623 ft 3,238 m	176.90 171.47	ASPHALT	0 ft 0 m	154 ft 47 m
35	148 ft 45 m	10,623 ft 3,238 m	356.90 351.47	ASPHALT	2,697 ft 822 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03	DME	IKK	110.70 MHz	18 nm 33 km	- -	-	43 ft 43 m
16	DME	IBB	110.10 MHz	18 nm 33 km	- -	-	10 ft 10 m
03	LOC-ILS	IKK	110.70 MHz	18 nm 33 km	32.78 27.35	-	84 ft 84 m
16	LOC-ILS	IBB	110.10 MHz	18 nm 33 km	166.99 161.56	-	84 ft 84 m
17	LOC-ILS	BIL	109.50 MHz	18 nm 33 km	176.90 171.47	-	84 ft 84 m
03	GS	IKK	110.70 MHz	10 nm 19 km	32.78 27.35	3.00	84 ft 84 m
16	GS	IBB	110.10 MHz	10 nm 19 km	166.99 161.56	3.00	84 ft 84 m
17	GS	BIL	109.50 MHz	10 nm 19 km	176.90 171.47	3.00	84 ft 84 m