
RCTP
Taiwan Taoyuan Intl

RJSK
AKITA

2024/03/29 0809Z

RCTP AISAR **A1** IGMON **Z40** ESBIS **OTR30** FUE **V28** DGC **Y14** SAMON **Z17** NOMAS REALU RJSK

1314.68 nm / 2434.78 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
RCTP APT	–	25.07790 121.23400	0 ft 0 m	–	Taiwan Taoyuan Intl
AISAR FIX	–	25.94750 122.49300	30,600 ft 9,327 m	85	–
OSTAR FIX	A1 AWY-HI	26.33170 123.00000	35,000 ft 10,668 m	35	–
BULAN FIX	A1 AWY-HI	27.09170 124.00000	35,000 ft 10,668 m	70	–
IGMON FIX	A1 AWY-HI	27.62210 124.72100	35,000 ft 10,668 m	49	–
ESBIS FIX	Z40 AWY-HI	31.25350 127.38100	35,000 ft 10,668 m	258	–
FUE VOR	OTR30 AWY-HI	32.66860 128.82700	35,000 ft 10,668 m	112	FUKUE
DGC VOR	V28 AWY-HI	33.67620 130.39000	35,000 ft 10,668 m	99	FUKUOKA
STOUT FIX	Y14 AWY-HI	34.19070 131.01600	35,000 ft 10,668 m	43	–
HALNA FIX	Y14 AWY-HI	34.53380 131.53600	35,000 ft 10,668 m	33	–
MIHOU FIX	Y14 AWY-HI	35.53110 133.09400	35,000 ft 10,668 m	97	–
DRIPS FIX	Y14 AWY-HI	35.90890 133.83600	35,000 ft 10,668 m	42	–
SAMON FIX	Y14 AWY-HI	36.24290 134.50300	35,000 ft 10,668 m	38	–
CELCA FIX	Z17 AWY-HI	37.48850 136.10100	35,000 ft 10,668 m	107	–
NOMAS FIX	Z17 AWY-HI	38.91380 138.03800	24,600 ft 7,498 m	125	–
REALU FIX	–	38.81680 138.29000	21,800 ft 6,645 m	13	–
RJSK APT	–	39.61560 140.21900	0 ft 0 m	101	AKITA

RCTP

Region: REPUBLIC OF CHINA (TAIWAN)
Timezone: ASIA/TAIPEI
Runways: 2

Elevation: 108 ft / 33 m
Location: 25.077900 121.234000
Magnetic Var: 4.980 W

METAR

RCTP 290730Z 03009KT 360V060 9999 FEW015 SCT200 26/19 Q1012 NOSIG RMK A2990

TAF

TAF RCTP 290500Z 2906/3012 03010KT 9999 FEW012 BKN032 BECMG 2910/2912 10008KT BECMG 2916/2918 24005KT TEMPO 3000/

Frequencies

REC - 127.60 MHz - ATIS
TWR - 118.70 MHz - TAIPEI TOWER
GND - 121.60 MHz - TAIPEI GROUND
APP - 119.50 MHz - TAIPEI APPROACH
APP - 119.70 MHz - TAIPEI APPROACH
APP - 123.60 MHz - TAIPEI APPROACH
APP - 125.10 MHz - TAIPEI APPROACH
APP - 125.60 MHz - TAIPEI APPROACH

TWR - 129.30 MHz - TAIPEI TOWER
GND - 121.70 MHz - TAIPEI GROUND
CLD - 121.80 MHz - TAIPEI CLEARANCE DELIVERY
APP - 119.60 MHz - TAIPEI APPROACH
APP - 123.50 MHz - TAIPEI APPROACH
APP - 124.20 MHz - TAIPEI APPROACH
APP - 125.50 MHz - TAIPEI APPROACH
APP - 128.50 MHz - TAIPEI APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05L	197 ft 60 m	12,020 ft 3,664 m	49.01 53.99	ASPHALT	0 ft 0 m	420 ft 128 m
23R	197 ft 60 m	12,020 ft 3,664 m	229.02 234.00	ASPHALT	0 ft 0 m	390 ft 119 m
05R	197 ft 60 m	12,478 ft 3,803 m	49.01 53.99	ASPHALT	328 ft 100 m	404 ft 123 m
23L	197 ft 60 m	12,478 ft 3,803 m	229.02 234.00	ASPHALT	1,148 ft 350 m	394 ft 120 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05L	DME	ITIA	111.10 MHz	18 nm 33 km	- -	-	106 ft 106 m
05R	DME	ICKS	110.70 MHz	18 nm 33 km	- -	-	106 ft 106 m
23R	DME	ITYA	109.30 MHz	18 nm 33 km	- -	-	106 ft 106 m
23L	DME	ICJN	111.90 MHz	18 nm 33 km	- -	-	106 ft 106 m
05L	LOC-ILS	ITIA	111.10 MHz	18 nm 33 km	49.02 54.00	-	108 ft 108 m
05R	LOC-ILS	ICKS	110.70 MHz	18 nm 33 km	49.02 54.00	-	108 ft 108 m
23L	LOC-ILS	ICJN	111.90 MHz	18 nm 33 km	229.02 234.00	-	108 ft 108 m
23R	LOC-ILS	ITYA	109.30 MHz	18 nm 33 km	229.02 234.00	-	108 ft 108 m
05L	GS	ITIA	111.10 MHz	10 nm 19 km	49.02 54.00	3.00	108 ft 108 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05R	GS	ICKS	110.70 MHz	10 nm	49.02	3.00	108 ft
				19 km	54.00		108 m
23L	GS	ICJN	111.90 MHz	10 nm	229.02	3.00	108 ft
				19 km	234.00		108 m
23R	GS	ITYA	109.30 MHz	10 nm	229.02	3.00	108 ft
				19 km	234.00		108 m

RJSK

Region: JAPAN
Timezone: ASIA/TOKYO
Runways: 1

Elevation: 312 ft / 95 m
Location: 39.615600 140.219000
Magnetic Var: 8.980 W

METAR

RJSK 290700Z 26016KT 9999 FEW003 SCT005 BKN006 11/10 Q1004

TAF

TAF RJSK 290513Z 2906/3012 24014KT 8000 FEW008 BKN015 TEMPO 2906/2910 FEW003 BKN005 BECMG 2910/2912 14004KT TEMPO

Frequencies

REC - 127.10 MHz - SAPPORO INFO
TWR - 118.60 MHz -

TWR - 126.20 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10	197 ft 60 m	8,184 ft 2,494 m	96.62 105.60	ASPHALT	0 ft 0 m	200 ft 61 m
28	197 ft 60 m	8,184 ft 2,494 m	276.64 285.62	ASPHALT	0 ft 0 m	200 ft 61 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
28	DME	IUW	108.90 MHz	18 nm 33 km	- -	-	328 ft 328 m
28	LOC-ILS	IUW	108.90 MHz	18 nm 33 km	276.62 285.60	-	286 ft 286 m
28	GS	IUW	108.90 MHz	10 nm 19 km	277.26 286.24	3.00	300 ft 300 m