KRDD
Redding Muni


-

KCIC
CHICO MUNI

2024/03/29 0647Z

KRDD HOMAN KCIC

48.41 nm / 89.65 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KRDD APT	–	40.50870 -122.29300	0 ft 0 m	–	Redding Muni
HOMAN FIX	–	40.40500 -122.12900	3,400 ft 1,036 m	9	–
KCIC APT	–	39.79530 -121.85900	0 ft 0 m	38	CHICO MUNI

KRDD

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 2

Elevation: 504 ft / 154 m
Location: 40.508700 -122.293000
Magnetic Var: 13.412 E

METAR

KRDD 290553Z 20003KT 10SM FEW090 12/06 A2993 RMK AO2 SLP132 T01170056 10150 20111 58000

TAF

KRDD 290535Z 2906/3006 19009KT P6SM SCT060 BKN080 BKN100 FM291900 17006KT P6SM -RA OVC050

Frequencies

REC - 124.10 MHz - ATIS
TWR - 119.80 MHz - REDDING TOWER
COM - 122.95 MHz - REDDING UNICOM
APP - 132.20 MHz - OAKLAND CENTER

COM - 119.80 MHz - CTAF
TWR - 121.70 MHz - REDDING GROUND
DEP - 132.20 MHz - OAKLAND CENTER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
12	150 ft 46 m	5,067 ft 1,544 m	140.21 126.80	ASPHALT	0 ft 0 m	0 ft 0 m
30	150 ft 46 m	5,067 ft 1,544 m	320.21 306.80	ASPHALT	0 ft 0 m	0 ft 0 m
16	155 ft 47 m	7,015 ft 2,138 m	180.07 166.66	ASPHALT	0 ft 0 m	197 ft 60 m
34	155 ft 47 m	7,015 ft 2,138 m	0.07 346.66	ASPHALT	0 ft 0 m	200 ft 61 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
34	LOC-ILS	IRDD	108.70 MHz	18 nm 33 km	0.07 346.66	-	504 ft 504 m
34	GS	IRDD	108.70 MHz	10 nm 19 km	0.07 346.66	3.00	504 ft 504 m

KCIC

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 2

Elevation: 240 ft / 73 m
Location: 39.795300 -121.859000
Magnetic Var: 13.201 E

METAR

KCIC 290635Z AUTO 12007KT 10SM FEW070 10/05 A2996 RMK AO1

TAF

UNKNOWN

Frequencies

REC - 119.67 MHz - ATIS
GND - 121.90 MHz - CHICO GROUND

COM - 122.95 MHz - CHICO UNICOM
TWR - 121.00 MHz - CHICO TOWER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
13L	150 ft 46 m	6,729 ft 2,051 m	147.53 134.33	ASPHALT	0 ft 0 m	197 ft 60 m
31R	150 ft 46 m	6,729 ft 2,051 m	327.54 314.34	ASPHALT	0 ft 0 m	200 ft 61 m
13R	60 ft 18 m	2,999 ft 914 m	147.65 134.45	ASPHALT	0 ft 0 m	0 ft 0 m
31L	60 ft 18 m	2,999 ft 914 m	327.65 314.45	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
13L	LOC-ILS	ICIC	111.30 MHz	18 nm 33 km	147.54 134.34	-	240 ft 240 m
13L	GS	ICIC	111.30 MHz	10 nm 19 km	147.54 134.34	3.00	240 ft 240 m