


2024/05/02 1254Z

YSSY WOL **H65** RAZZI **Q29** LIZZI YMML

386.35 nm / 715.52 km



Notes

Requested: YSSY WOL H65 RAZZI Q29 LIZZI YMML

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
YSSY	-	-33.94610	0 ft	-	Sydney Kingsford Smith
APT	-	151.17700	0 m	-	
WOL	-	-34.55790	0 ft	41	WOLLONGONG
NDB	-	150.79100	0 m	-	
RAZZI	H65	-35.05420	0 ft	50	-
FIX	AWY-HI	149.96000	0 m	-	
TANTA	Q29	-35.88070	0 ft	85	-
FIX	AWY-HI	148.53200	0 m	-	
RUMIE	Q29	-36.32980	0 ft	47	-
FIX	AWY-HI	147.72800	0 m	-	
NABBA	Q29	-36.70530	0 ft	40	-
FIX	AWY-HI	147.04200	0 m	-	
BULLA	Q29	-37.07780	0 ft	40	-
FIX	AWY-HI	146.34700	0 m	-	
TAREX	Q29	-37.30600	0 ft	24	-
FIX	AWY-HI	145.91400	0 m	-	
LIZZI	Q29	-37.45060	0 ft	15	-
FIX	AWY-HI	145.63800	0 m	-	
YMML	-	-37.66550	0 ft	40	Melbourne Intl
APT	-	144.83700	0 m	-	

YSSY

Region: AUSTRALIA
Timezone: AUSTRALIA/SYDNEY
Runways: 3

Elevation: 21 ft / 6 m
Location: -33.946100 151.177000
Magnetic Var: 12.671 E

METAR

YSSY 021230Z AUTO 21008KT 9999 // SCT039 BKN054 BKN069 15/14 Q1030

TAF

TAF AMD YSSY 021116Z 0212/0318 19010KT 9999 -SHRA BKN020 FM030000 17014KT 9999 -SHRA BKN025 FM031000 22008KT 9999

Frequencies

REC - 118.55 MHz - ATIS	REC - 126.55 MHz - ATIS
TWR - 124.70 MHz - SYDNEY TOWER	TWR - 120.50 MHz - SYDNEY TOWER
GND - 126.50 MHz - SYDNEY GROUND	GND - 121.70 MHz - SYDNEY GROUND
GND - 130.95 MHz - ANSETT APRON	GND - 127.60 MHz - SYDNEY COORDINATOR
CLD - 133.80 MHz - SYDNEY CLEARANCE DELIVERY	APP - 124.40 MHz - SYDNEY APPROACH
APP - 128.30 MHz - SYDNEY APPROACH	APP - 135.90 MHz - SYDNEY APPROACH
APP - 126.10 MHz - SYDNEY DIRECT	APP - 125.30 MHz - SYDNEY DIRECT
APP - 133.95 MHz - ILS MONITOR	APP - 119.45 MHz - ILS MONITOR
DEP - 129.70 MHz - SYDNEY DEPARTURE	DEP - 128.30 MHz - SYDNEY DEPARTURE
DEP - 123.00 MHz - SYDNEY DEPARTURE	DEP - 118.40 MHz - SYDNEY DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16L	148 ft	8,018 ft	167.85	ASPHALT	758 ft	295 ft
	45 m	2,444 m	155.18		231 m	90 m
34R	148 ft	8,018 ft	347.85	ASPHALT	125 ft	295 ft
	45 m	2,444 m	335.18		38 m	90 m
07	148 ft	8,285 ft	74.14	ASPHALT	0 ft	489 ft
	45 m	2,525 m	61.46		0 m	149 m
25	148 ft	8,285 ft	254.12	ASPHALT	331 ft	197 ft
	45 m	2,525 m	241.45		101 m	60 m
16R	148 ft	13,029 ft	167.86	ASPHALT	279 ft	299 ft
	45 m	3,971 m	155.19		85 m	91 m
34L	148 ft	13,029 ft	347.85	ASPHALT	0 ft	620 ft
	45 m	3,971 m	335.18		0 m	189 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07	DME	ISY	109.90 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
16L	DME	ISS	110.90 MHz	18 nm	-	-	30 ft
				33 km	-		30 m
25	DME	ISW	109.70 MHz	18 nm	-	-	33 ft
				33 km	-		33 m
34R	DME	IKN	109.30 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
07	LOC-ILS	ISY	109.90 MHz	18 nm	74.13	-	21 ft
				33 km	61.46		21 m
16L	LOC-ILS	ISS	110.90 MHz	18 nm	167.85	-	21 ft
				33 km	155.18		21 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16R	LOC-ILS	IKS	109.50 MHz	18 nm	167.86	-	21 ft
				33 km	155.19		21 m
25	LOC-ILS	ISW	109.70 MHz	18 nm	254.13	-	21 ft
				33 km	241.46		21 m
34L	LOC-ILS	ISN	110.10 MHz	18 nm	347.86	-	21 ft
				33 km	335.19		21 m
34R	LOC-ILS	IKN	109.30 MHz	18 nm	347.85	-	21 ft
				33 km	335.18		21 m
07	GS	ISY	109.90 MHz	10 nm	74.13	3.00	21 ft
				19 km	61.46		21 m
16L	GS	ISS	110.90 MHz	10 nm	167.85	3.00	21 ft
				19 km	155.18		21 m
16R	GS	IKS	109.50 MHz	10 nm	167.86	3.00	21 ft
				19 km	155.19		21 m
25	GS	ISW	109.70 MHz	10 nm	254.13	3.00	21 ft
				19 km	241.46		21 m
34L	GS	ISN	110.10 MHz	10 nm	347.86	3.00	21 ft
				19 km	335.19		21 m
34R	GS	IKN	109.30 MHz	10 nm	347.85	3.00	21 ft
				19 km	335.18		21 m

YMML

Region: AUSTRALIA
Timezone: AUSTRALIA/MELBOURNE
Runways: 2

Elevation: 433 ft / 132 m
Location: -37.665500 144.837000
Magnetic Var: 11.562 E

METAR

YMML 021230Z 30007KT 9999 FEW040 09/07 Q1031 HAZE

TAF

TAF AMD YMML 021117Z 0212/0318 33006KT CAVOK FM021800 35004KT 9999 BKN006 FM022300 24003KT 9999 BKN010 BECMG 0300

Frequencies

REC - 132.67 MHz - YMML ATIS
GND - 121.70 MHz - MELBOURNE GND
APP - 132.00 MHz - MELBOURNE APP

CLD - 127.20 MHz - MELBOURNE INTL CLD
TWR - 120.50 MHz - MELBOURNE TWR
DEP - 118.90 MHz - MELBOURNE DEP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	148 ft	7,513 ft	94.00	ASPHALT	0 ft	197 ft
	45 m	2,290 m	82.44		0 m	60 m
27	148 ft	7,513 ft	273.98	ASPHALT	0 ft	174 ft
	45 m	2,290 m	262.42		0 m	53 m
16	155 ft	12,012 ft	171.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	160.04		0 m	61 m
34	155 ft	12,012 ft	351.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	340.04		0 m	61 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	LOC-ILS	IMS	109.70 MHz	18 nm	171.60	-	433 ft
				33 km	160.04		433 m
27	LOC-ILS	IMW	109.30 MHz	18 nm	273.99	-	433 ft
				33 km	262.43		433 m
16	GS	IMS	109.70 MHz	10 nm	171.60	3.00	433 ft
				19 km	160.04		433 m
27	GS	IMW	109.30 MHz	10 nm	273.99	3.00	433 ft
				19 km	262.43		433 m