KORD
Chicago Ohare Intl


-

KSAW
Sawyer Intl

2024/03/19 0129Z

KORD R0295 KSAW

261.28 nm / 483.89 km



Notes

Generated

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KORD APT	–	42.00283 −87.92668	0 ft 0 m	–	–
R0295 FIX	–	46.33687 −87.39917	0 ft 0 m	261	–
KSAW APT	–	46.33687 −87.39917	0 ft 0 m	0	–

KORD

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 6
Elevation: 680 ft / 207 m
Location: 41.973400 -87.906600
Magnetic Var: 4.102 W

METAR

KORD 190051Z 24004KT 10SM FEW045 FEW300 01/M09 A3007 RMK AO2 SLP189 T00061089

TAF

TAF KORD 182320Z 1900/2006 24011KT P6SM FEW050 SCT300 FM190600 23012G24KT P6SM BKN100 FM191400 26018G30KT P6SM SC

Frequencies

REC - 135.40 MHz - ATIS
CLD - 119.25 MHz - CLEARANCE DELIVERY
GND - 118.05 MHz - O'HARE GROUND
GND - 121.75 MHz - O'HARE GROUND
GND - 124.12 MHz - O'HARE GROUND
TWR - 120.75 MHz - O'HARE TOWER
TWR - 126.90 MHz - O'HARE TOWER
TWR - 132.70 MHz - O'HARE TOWER
TWR - 133.00 MHz - O'HARE TOWER
APP - 133.62 MHz - CHICAGO APPROACH
APP - 125.70 MHz - CHICAGO APPROACH
DEP - 125.40 MHz - CHICAGO DEPARTURE
DEP - 128.80 MHz - CHICAGO DEPARTURE
COM - 122.95 MHz - UNICOM
CLD - 121.60 MHz - CLEARANCE DELIVERY
GND - 121.67 MHz - O'HARE GROUND
GND - 121.90 MHz - O'HARE GROUND
GND - 134.12 MHz - O'HARE GROUND
TWR - 121.15 MHz - O'HARE TOWER
TWR - 127.92 MHz - O'HARE TOWER
TWR - 128.15 MHz - O'HARE TOWER
APP - 119.00 MHz - CHICAGO APPROACH
APP - 124.35 MHz - CHICAGO APPROACH
DEP - 125.00 MHz - CHICAGO DEPARTURE
DEP - 127.40 MHz - CHICAGO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10C	200 ft 61 m	10,789 ft 3,289 m	89.85 93.95	CONCRETE	0 ft 0 m	397 ft 121 m
28C	200 ft 61 m	10,789 ft 3,289 m	269.88 273.98	CONCRETE	0 ft 0 m	381 ft 116 m
10L	151 ft 46 m	12,996 ft 3,961 m	89.87 93.98	CONCRETE	0 ft 0 m	394 ft 120 m
28R	151 ft 46 m	12,996 ft 3,961 m	269.91 274.01	CONCRETE	0 ft 0 m	285 ft 87 m
04R	151 ft 46 m	8,074 ft 2,461 m	41.40 45.50	CONCRETE	0 ft 0 m	850 ft 259 m
22L	151 ft 46 m	8,074 ft 2,461 m	221.41 225.52	CONCRETE	0 ft 0 m	584 ft 178 m
09R	151 ft 46 m	7,949 ft 2,423 m	89.98 94.08	CONCRETE	0 ft 0 m	148 ft 45 m
27L	151 ft 46 m	7,949 ft 2,423 m	270.00 274.10	CONCRETE	0 ft 0 m	197 ft 60 m
09L	151 ft 46 m	7,484 ft 2,281 m	89.99 94.09	CONCRETE	0 ft 0 m	397 ft 121 m
27R	151 ft 46 m	7,484 ft 2,281 m	270.00 274.11	CONCRETE	0 ft 0 m	397 ft 121 m
10R	151 ft 46 m	7,484 ft 2,281 m	89.85 93.95	CONCRETE	0 ft 0 m	400 ft 122 m
28L	151 ft 46 m	7,484 ft 2,281 m	269.87 273.97	CONCRETE	0 ft 0 m	400 ft 122 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	ISAJ	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
10L	DME	IMED	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
27L	DME	IIAC	110.50 MHz	18 nm 33 km	– –	–	641 ft 641 m
27R	DME	IABU	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
28R	DME	ITSL	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
04R	LOC-ILS	IFJU	110.10 MHz	18 nm 33 km	41.41 45.51	–	680 ft 680 m
09L	LOC-ILS	ISAJ	111.75 MHz	18 nm 33 km	90.00 94.10	–	680 ft 680 m
09R	LOC-ILS	IJAV	110.50 MHz	18 nm 33 km	89.99 94.09	–	680 ft 680 m
10L	LOC-ILS	IMED	111.10 MHz	18 nm 33 km	89.89 93.99	–	680 ft 680 m
10C	LOC-ILS	ISXH	108.95 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
10R	LOC-ILS	IIZJ	110.75 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
22L	LOC-ILS	ILQQ	110.10 MHz	18 nm 33 km	221.41 225.51	–	680 ft 680 m
27L	LOC-ILS	IIAC	110.50 MHz	18 nm 33 km	269.99 274.09	–	680 ft 680 m
27R	LOC-ILS	IABU	111.75 MHz	18 nm 33 km	270.00 274.10	–	680 ft 680 m
28L	LOC-ILS	IVQX	110.75 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28C	LOC-ILS	IVZE	108.95 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28R	LOC-ILS	ITSL	111.10 MHz	18 nm 33 km	269.88 273.98	–	680 ft 680 m
04R	GS	IFJU	110.10 MHz	10 nm 19 km	41.41 45.51	3.00	680 ft 680 m
09L	GS	ISAJ	111.75 MHz	10 nm 19 km	90.00 94.10	3.00	680 ft 680 m
09R	GS	IJAV	110.50 MHz	10 nm 19 km	89.99 94.09	3.00	680 ft 680 m
10L	GS	IMED	111.10 MHz	10 nm 19 km	89.89 93.99	3.00	680 ft 680 m
10C	GS	ISXH	108.95 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
10R	GS	IIZJ	110.75 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
22L	GS	ILQQ	110.10 MHz	10 nm 19 km	221.41 225.51	3.00	680 ft 680 m
27L	GS	IIAC	110.50 MHz	10 nm 19 km	269.99 274.09	3.00	680 ft 680 m
27R	GS	IABU	111.75 MHz	10 nm 19 km	270.00 274.10	3.00	680 ft 680 m
28L	GS	IVQX	110.75 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28C	GS	IVZE	108.95 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28R	GS	ITSL	111.10 MHz	10 nm 19 km	269.88 273.98	3.00	680 ft 680 m

KSAW

Region: UNITED STATES
Timezone: AMERICA/DETROIT
Runways: 1
Elevation: 1,221 ft / 372 m
Location: 46.353600 -87.395400
Magnetic Var: 5.147 W

METAR

KSAW 190047Z 20003KT 10SM OVC110 M04/M09 A2985

TAF

KSAW 182336Z 1900/1924 24004KT P6SM OVC100 FM190500 22005KT 3SM -SN OVC028 TEMPO 1905/1907 2SM -SN FM190700 22007K

Frequencies

REC - 118.37 MHz - AWOS 3
COM - 122.70 MHz - UNICOM
TWR - 119.97 MHz -
COM - 119.97 MHz - CTAF
GND - 121.65 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01	151 ft 46 m	12,377 ft 3,772 m	8.93 14.07	ASPHALT	0 ft 0 m	928 ft 283 m
19	151 ft 46 m	12,377 ft 3,772 m	188.93 194.08	ASPHALT	0 ft 0 m	1,001 ft 305 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01	LOC-ILS	ISOU	110.10 MHz	18 nm 33 km	8.94 14.08	-	1,221 ft 1,221 m
01	GS	ISOU	110.10 MHz	10 nm 19 km	9.86 15.01	3.00	1,221 ft 1,221 m