


2024/05/07 0638Z

EHAM RTM EHRD

24.38 nm / 45.16 km



Notes

Basic altitude profile:

- Ascent Rate: 1000ft/min
- Ascent Speed: 120kts
- Cruise Altitude: 1000ft
- Cruise Speed: 120kts
- Descent Rate: 100ft/min
- Descent Speed: 90kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EHAM	-	52.30810	0 ft	-	Amsterdam Schiphol
APT	-	4.76417	0 m		
RTM	-	51.97370	0 ft	22	ROTTERDAM
VOR	-	4.48097	0 m		
EHRD	-	51.95750	0 ft	1	Rotterdam The Hague
APT	-	4.44169	0 m		

EHAM

Region: NETHERLANDS
Timezone: EUROPE/AMSTERDAM
Runways: 6

Elevation: -11 ft / -3 m
Location: 52.308100 4.764170
Magnetic Var: 2.042 E

METAR

EHAM 070555Z 04005KT 020V080 CAVOK 13/10 Q1017 NOSIG

TAF

TAF TAF EHAM 070443Z 0706/0812 03007KT CAVOK BECMG 0709/0712 35010KT BECMG 0719/0722 BKN012 PROB30 0721/0805 BKN0

Frequencies

GND - 121.55 MHz - SCHIPHOL GROUND	GND - 121.70 MHz - SCHIPHOL GROUND
GND - 121.80 MHz - SCHIPHOL GROUND	GND - 121.90 MHz - SCHIPHOL GROUND
GND - 121.60 MHz - SCHIPHOL GROUND	TWR - 119.22 MHz - SCHIPHOL TOWER
TWR - 118.10 MHz - SCHIPHOL TOWER	TWR - 118.27 MHz - SCHIPHOL TOWER
TWR - 119.90 MHz - SCHIPHOL TOWER	APP - 118.80 MHz - AMSTERDAM RADAR
APP - 120.55 MHz - AMSTERDAM RADAR	APP - 127.78 MHz - AMSTERDAM RADAR
APP - 119.05 MHz - SCHIPHOL APPROACH	APP - 118.08 MHz - SCHIPHOL APPROACH
APP - 126.68 MHz - SCHIPHOL APPROACH	APP - 118.40 MHz - SCHIPHOL ARRIVAL
APP - 131.15 MHz - SCHIPHOL ARRIVAL	DEP - 121.20 MHz - SCHIPHOL DEPARTURE
REC - 122.20 MHz - SCHIPHOL ATIS	

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	145 ft	11,319 ft	86.77	ASPHALT	325 ft	0 ft
	44 m	3,450 m	84.73		99 m	0 m
27	145 ft	11,319 ft	266.81	ASPHALT	0 ft	0 ft
	44 m	3,450 m	264.77		0 m	0 m
18L	150 ft	11,150 ft	183.24	ASPHALT	1,886 ft	0 ft
	46 m	3,399 m	181.20		575 m	0 m
36R	150 ft	11,150 ft	3.24	ASPHALT	0 ft	0 ft
	46 m	3,399 m	1.20		0 m	0 m
18C	145 ft	10,813 ft	183.22	ASPHALT	0 ft	0 ft
	44 m	3,296 m	181.18		0 m	0 m
36C	145 ft	10,813 ft	3.22	ASPHALT	1,473 ft	0 ft
	44 m	3,296 m	1.17		449 m	0 m
18R	190 ft	12,467 ft	183.19	ASPHALT	886 ft	0 ft
	58 m	3,800 m	181.15		270 m	0 m
36L	190 ft	12,467 ft	3.19	ASPHALT	0 ft	0 ft
	58 m	3,800 m	1.15		0 m	0 m
06	150 ft	11,288 ft	57.85	ASPHALT	814 ft	0 ft
	46 m	3,441 m	55.81		248 m	0 m
24	150 ft	11,288 ft	237.89	ASPHALT	0 ft	0 ft
	46 m	3,441 m	235.85		0 m	0 m
04	140 ft	6,624 ft	41.18	ASPHALT	0 ft	0 ft
	43 m	2,019 m	39.14		0 m	0 m
22	140 ft	6,624 ft	221.20	ASPHALT	0 ft	0 ft
	43 m	2,019 m	219.16		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	DME	KAG	110.55 MHz	18 nm 33 km	- -	-	-11 ft -11 m
18R	DME	VPB	110.10 MHz	18 nm 33 km	- -	-	-11 ft -11 m
22	DME	SCH	109.15 MHz	18 nm 33 km	- -	-	-11 ft -11 m
27	DME	BVB	111.55 MHz	18 nm 33 km	- -	-	-11 ft -11 m
36C	DME	MSA	108.75 MHz	18 nm 33 km	- -	-	-11 ft -11 m
36R	DME	ABA	111.95 MHz	18 nm 33 km	- -	-	-11 ft -11 m
06	LOC-ILS	KAG	110.55 MHz	18 nm 33 km	57.88 55.84	-	-11 ft -11 m
18C	LOC-ILS	ZWA	109.50 MHz	18 nm 33 km	183.22 181.18	-	-11 ft -11 m
18R	LOC-ILS	VPB	110.10 MHz	18 nm 33 km	183.19 181.15	-	-11 ft -11 m
22	LOC-ILS	SCH	109.15 MHz	18 nm 33 km	221.20 219.16	-	-11 ft -11 m
27	LOC-ILS	BVB	111.55 MHz	18 nm 33 km	266.79 264.75	-	-11 ft -11 m
36C	LOC-ILS	MSA	108.75 MHz	18 nm 33 km	3.22 1.18	-	-11 ft -11 m
36R	LOC-ILS	ABA	111.95 MHz	18 nm 33 km	3.24 1.20	-	-11 ft -11 m
06	GS	KAG	110.55 MHz	10 nm 19 km	57.88 55.84	3.00	-11 ft -11 m
18C	GS	ZWA	109.50 MHz	10 nm 19 km	183.22 181.18	3.00	-11 ft -11 m
18R	GS	VPB	110.10 MHz	10 nm 19 km	183.19 181.15	3.00	-11 ft -11 m
22	GS	SCH	109.15 MHz	10 nm 19 km	221.20 219.16	3.00	-11 ft -11 m
27	GS	BVB	111.55 MHz	10 nm 19 km	266.79 264.75	3.00	-11 ft -11 m
36C	GS	MSA	108.75 MHz	10 nm 19 km	3.22 1.18	3.00	-11 ft -11 m
36R	GS	ABA	111.95 MHz	10 nm 19 km	3.24 1.20	3.00	-11 ft -11 m

EHRD

Region: NETHERLANDS
Timezone: EUROPE/AMSTERDAM
Runways: 1

Elevation: -15 ft / -5 m
Location: 51.957500 4.441690
Magnetic Var: 1.951 E

METAR

EHRD 070555Z AUTO 05007KT 010V080 9999 NSC 12/09 Q1016 NOSIG

TAF

TAF EHRD 070443Z 0706/0812 04006KT CAVOK BECMG 0709/0712 35010KT BECMG 0720/0723 BKN012 PROB30 0721/0805 BKN008 B

Frequencies

TWR - 118.20 MHz - ROTTERDAM TOWER
REC - 110.40 MHz - ROTTERDAM ATIS
GND - 122.17 MHz - ROTTERDAM GROUND

APP - 127.02 MHz - ROTTERDAM APPROACH
CLD - 128.80 MHz - ROTTERDAM DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	148 ft	7,198 ft	57.03	ASPHALT	643 ft	0 ft
	45 m	2,194 m	55.08		196 m	0 m
24	148 ft	7,198 ft	237.05	ASPHALT	646 ft	0 ft
	45 m	2,194 m	235.10		197 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	DME	ROS	110.90 MHz	18 nm	-	-	-15 ft
				33 km	-		-15 m
24	DME	RSV	110.90 MHz	18 nm	-	-	-15 ft
				33 km	-		-15 m
06	LOC-ILS	ROS	109.10 MHz	18 nm	56.94	-	-15 ft
				33 km	54.99		-15 m
24	LOC-ILS	RSV	110.90 MHz	18 nm	236.94	-	-15 ft
				33 km	234.99		-15 m