WADD

Denpasar Ngurah Rai Intl

-


WIII

Jakarta Soekarno-Hatta Intl

2024/03/28 0947Z

WADD RABOL **W33** SBR **M766** IMU WIII

549.33 nm / 1017.36 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: no
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
WADD APT	–	-8.74840 115.16700	0 ft 0 m	–	Denpasar Ngurah Rai Intl
RABOL FIX	–	-8.02142 113.89600	31,100 ft 9,479 m	87	–
SBR VOR	W33 AWY-HI	-7.37394 112.77100	35,000 ft 10,668 m	77	SURABAYA
LASEM FIX	M766 AWY-HI	-6.61833 111.61500	35,000 ft 10,668 m	82	–
CUCUT FIX	M766 AWY-HI	-6.29500 111.10000	35,000 ft 10,668 m	36	–
MADIN FIX	M766 AWY-HI	-6.29833 110.38300	35,000 ft 10,668 m	42	–
KIDET FIX	M766 AWY-HI	-6.30083 109.32700	34,200 ft 10,424 m	63	–
IMU VOR	M766 AWY-HI	-6.30420 108.33900	21,600 ft 6,584 m	58	INDRAMAYU
WIII APT	–	-6.12569 106.65700	0 ft 0 m	100	Jakarta Soekarno-Hatta Intl

WADD

Region: INDONESIA
Timezone: ASIA/MAKASSAR
Runways: 1

Elevation: 14 ft / 4 m
Location: -8.748400 115.167000
Magnetic Var: 0.618 E

METAR

WADD 280900Z 12009KT 9999 TS FEW015CB BKN016 30/26 Q1010 TEMPO TL1000 TS RMK CB IN APCH

TAF

TAF WADD 280500Z 2806/2906 13008KT 9999 FEW016 TEMPO 2807/2810 5000 RA FEW014CB SCT016

Frequencies

REC - 126.20 MHz - ATIS
TWR - 118.10 MHz - NGURAH TOWER

GND - 118.80 MHz - NGURAH GROUND
APP - 119.70 MHz - BALI DIRECTOR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	148 ft 45 m	9,828 ft 2,996 m	87.66 87.04	ASPHALT	0 ft 0 m	0 ft 0 m
27	148 ft 45 m	9,828 ft 2,996 m	267.66 267.04	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
27	DME	IDPS	110.30 MHz	18 nm 33 km	- -	-	14 ft 14 m
27	LOC-ILS	IDPS	110.30 MHz	18 nm 33 km	267.70 267.09	-	10 ft 10 m
27	GS	IDPS	110.30 MHz	10 nm 19 km	268.41 267.79	3.00	12 ft 12 m

WIII

Region: INDONESIA
Timezone: ASIA/JAKARTA
Runways: 3

Elevation: 34 ft / 10 m
Location: -6.119810 106.657000
Magnetic Var: 0.531 E

METAR

WIII 280930Z 34005KT 9999 FEW020 31/24 Q1009 NOSIG

TAF

TAF WIII 280500Z 2806/2912 02010KT 9000 SCT020 BECMG 2810/2812 34003KT 5000 HZ BECMG 2816/2818 23005KT BECMG 2823/

Frequencies

REC - 126.85 MHz - ATIS
CLD - 124.25 MHz - SOEKARNO-HATTA CLEARANCE DELIVERY
GND - 121.60 MHz - SOEKARNO-HATTA GROUND
GND - 128.85 MHz - SOEKARNO-HATTA GROUND
TWR - 118.20 MHz - SOEKARNO-HATTA TOWER
TWR - 119.30 MHz - SOEKARNO-HATTA TOWER
APP - 124.20 MHz - JAKARTA ARRIVAL
APP - 119.75 MHz - JAKARTA DIRECTOR
APP - 124.55 MHz - JAKARTA DIRECTOR
APP - 125.05 MHz - JAKARTA DIRECTOR
APP - 124.15 MHz - JAKARTA RADAR
APP - 125.35 MHz - JAKARTA RADAR
APP - 127.95 MHz - JAKARTA RADAR

CLD - 121.95 MHz - SOEKARNO-HATTA CLEARANCE DELIVERY
CLD - 125.15 MHz - SOEKARNO-HATTA CLEARANCE DELIVERY
GND - 121.00 MHz - SOEKARNO-HATTA GROUND
GND - 128.95 MHz - SOEKARNO-HATTA GROUND
TWR - 118.75 MHz - SOEKARNO-HATTA TOWER
TWR - 120.25 MHz - SOEKARNO-HATTA TOWER
APP - 125.45 MHz - JAKARTA ARRIVAL
APP - 123.75 MHz - JAKARTA DIRECTOR
APP - 124.95 MHz - JAKARTA DIRECTOR
APP - 127.90 MHz - JAKARTA DIRECTOR
APP - 124.35 MHz - JAKARTA RADAR
APP - 126.45 MHz - JAKARTA RADAR
APP - 130.10 MHz - JAKARTA RADAR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	150 ft 46 m	8,202 ft 2,500 m	68.13 67.60	ASPHALT	328 ft 100 m	846 ft 258 m
24	150 ft 46 m	8,202 ft 2,500 m	248.13 247.60	ASPHALT	0 ft 0 m	0 ft 0 m
07L	197 ft 60 m	11,820 ft 3,603 m	68.15 67.62	ASPHALT	0 ft 0 m	0 ft 0 m
25R	197 ft 60 m	11,820 ft 3,603 m	248.15 247.61	ASPHALT	0 ft 0 m	0 ft 0 m
07R	197 ft 60 m	12,015 ft 3,662 m	68.12 67.59	ASPHALT	0 ft 0 m	0 ft 0 m
25L	197 ft 60 m	12,015 ft 3,662 m	248.12 247.59	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07L	LOC-ILS	ICHL	111.50 MHz	18 nm 33 km	68.13 67.60	-	21 ft 21 m
07R	LOC-ILS	ICHR	110.50 MHz	18 nm 33 km	68.13 67.60	-	27 ft 27 m
25L	LOC-ILS	ICGL	111.10 MHz	18 nm 33 km	248.12 247.59	-	34 ft 34 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
25R	LOC-ILS	ICGR	110.90 MHz	18 nm 33 km	248.13 247.60	-	29 ft 29 m
07L	GS	ICHL	111.50 MHz	10 nm 19 km	68.25 67.72	3.00	29 ft 29 m
07R	GS	ICHR	110.50 MHz	10 nm 19 km	68.24 67.71	3.00	34 ft 34 m
25L	GS	ICGL	111.10 MHz	10 nm 19 km	248.24 247.71	3.00	27 ft 27 m
25R	GS	ICGR	110.90 MHz	10 nm 19 km	248.25 247.72	3.00	21 ft 21 m