KMIA
Miami Intl


1367

KEYW
Key West Intl

2024/03/29 0143Z

KMIA DHP KEYW

110.26 nm / 204.20 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KMIA APT	–	25.79620 −80.28970	0 ft 0 m	–	Miami Intl
DHP VOR	–	25.80000 −80.34900	1,100 ft 335 m	3	DOLPHIN (MIAMI)
KEYW APT	–	24.55610 −81.75960	0 ft 0 m	107	Key West Intl

KMIA

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 4

Elevation: 11 ft / 3 m
Location: 25.796200 -80.289700
Magnetic Var: 7.262 W

METAR

KMIA 290053Z 31006KT 10SM FEW075 FEW250 25/12 A2994 RMK AO2 SLP138 T02500122

TAF

TAF KMIA 282320Z 2900/3006 33012G20KT P6SM SKC FM291400 03012G20KT P6SM FEW030 FM300000 05007KT P6SM SKC

Frequencies

REC - 119.15 MHz - D-ATIS
COM - 123.00 MHz - UNICOM
GND - 121.80 MHz - MIAMI GROUND
TWR - 118.30 MHz - MIAMI TOWER
APP - 120.50 MHz - MIAMI APPROACH
APP - 125.75 MHz - MIAMI APPROACH
DEP - 125.50 MHz - MIAMI DEPARTURE

REC - 133.67 MHz - D-ATIS
CLD - 135.35 MHz - CLEARANCE DELIVERY
GND - 127.50 MHz - MIAMI GROUND
TWR - 123.90 MHz - MIAMI TOWER
APP - 124.85 MHz - MIAMI APPROACH
DEP - 119.45 MHz - MIAMI DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	151 ft 46 m	13,027 ft 3,971 m	87.37 94.63	CONCRETE	1,371 ft 418 m	384 ft 117 m
27	151 ft 46 m	13,027 ft 3,971 m	267.39 274.65	CONCRETE	276 ft 84 m	374 ft 114 m
08R	200 ft 61 m	10,515 ft 3,205 m	87.38 94.64	CONCRETE	0 ft 0 m	407 ft 124 m
26L	200 ft 61 m	10,515 ft 3,205 m	267.39 274.65	CONCRETE	0 ft 0 m	407 ft 124 m
08L	151 ft 46 m	8,607 ft 2,624 m	87.38 94.64	CONCRETE	0 ft 0 m	387 ft 118 m
26R	151 ft 46 m	8,607 ft 2,624 m	267.39 274.65	CONCRETE	0 ft 0 m	387 ft 118 m
12	151 ft 46 m	9,366 ft 2,855 m	119.61 126.87	CONCRETE	0 ft 0 m	397 ft 121 m
30	151 ft 46 m	9,366 ft 2,855 m	299.62 306.88	CONCRETE	948 ft 289 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08L	DME	IROY	109.30 MHz	18 nm 33 km	- -	-	8 ft 8 m
08R	DME	IMFA	110.30 MHz	18 nm 33 km	- -	-	8 ft 8 m
12	DME	IGEM	108.90 MHz	18 nm 33 km	- -	-	14 ft 14 m
26L	DME	IVIN	109.10 MHz	18 nm 33 km	- -	-	12 ft 12 m
26R	DME	ICNV	109.30 MHz	18 nm 33 km	- -	-	8 ft 8 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
30	DME	IDCX	111.70 MHz	18 nm 33 km	- -	-	8 ft 8 m
08R	LOC-ILS	IMFA	110.30 MHz	18 nm 33 km	87.37 94.63	-	4 ft 4 m
09	LOC-ILS	IBUL	110.90 MHz	18 nm 33 km	87.37 94.63	-	4 ft 4 m
12	LOC-ILS	IGEM	108.90 MHz	18 nm 33 km	119.60 126.86	-	4 ft 4 m
26L	LOC-ILS	IVIN	109.10 MHz	18 nm 33 km	267.37 274.63	-	4 ft 4 m
27	LOC-ILS	IMIA	109.50 MHz	18 nm 33 km	267.37 274.63	-	4 ft 4 m
30	LOC-ILS	IDCX	111.70 MHz	18 nm 33 km	299.60 306.86	-	4 ft 4 m
08L	LOC-LOC	IROY	109.30 MHz	18 nm 33 km	87.36 94.62	-	4 ft 4 m
26R	LOC-LOC	ICNV	109.30 MHz	18 nm 33 km	267.36 274.62	-	4 ft 4 m
08R	GS	IMFA	110.30 MHz	10 nm 19 km	87.37 94.63	3.00	4 ft 4 m
09	GS	IBUL	110.90 MHz	10 nm 19 km	87.37 94.63	3.00	4 ft 4 m
12	GS	IGEM	108.90 MHz	10 nm 19 km	119.60 126.86	3.00	4 ft 4 m
26L	GS	IVIN	109.10 MHz	10 nm 19 km	267.37 274.63	3.00	4 ft 4 m
27	GS	IMIA	109.50 MHz	10 nm 19 km	267.37 274.63	3.00	4 ft 4 m
30	GS	IDCX	111.70 MHz	10 nm 19 km	299.60 306.86	3.00	4 ft 4 m