

KLAX

Los Angeles Intl


NZAA

Auckland Intl

2024/05/05 0145Z

KLAX MALIT **C1177** FICKY **B200** AKLOM **G594** KENNE NZAA

5675.38 nm / 10510.80 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KLAX	-	33.94310	0 ft	-	Los Angeles Intl
APT	-	-118.40900	0 m		
MALIT	-	32.47560	35,000 ft	106	-
FIX	-	-119.59100	10,668 m		
ROSIN	C1177	31.94210	35,000 ft	47	-
FIX	AWY-HI	-120.26800	10,668 m		
FICKY	C1177	31.55760	35,000 ft	61	-
FIX	AWY-HI	-121.39200	10,668 m		
TONYS	B200	30.33080	35,000 ft	104	-
FIX	AWY-HI	-122.82100	10,668 m		
AMATT	B200	23.26030	35,000 ft	578	-
FIX	AWY-HI	-130.16400	10,668 m		
BENTS	B200	16.88530	35,000 ft	501	-
FIX	AWY-HI	-135.90000	10,668 m		
CARLS	B200	10.35610	35,000 ft	501	-
FIX	AWY-HI	-141.25800	10,668 m		
ANJJE	B200	5.00000	35,000 ft	406	-
FIX	AWY-HI	-145.43000	10,668 m		
BISOX	B200	-0.32167	35,000 ft	401	-
FIX	AWY-HI	-149.49200	10,668 m		
PUMIS	B200	-5.00000	35,000 ft	353	-
FIX	AWY-HI	-153.06200	10,668 m		
MEGOG	B200	-10.05670	35,000 ft	383	-
FIX	AWY-HI	-157.00000	10,668 m		
ASORO	B200	-15.00000	35,000 ft	378	-
FIX	AWY-HI	-161.00700	10,668 m		
OSUGA	B200	-20.00000	35,000 ft	388	-
FIX	AWY-HI	-165.31800	10,668 m		
SAMAD	B200	-25.00000	35,000 ft	397	-
FIX	AWY-HI	-170.02000	10,668 m		
TATAS	B200	-30.00000	35,000 ft	411	-
FIX	AWY-HI	-175.29500	10,668 m		
AKLOM	B200	-35.35790	35,000 ft	452	-
FIX	AWY-HI	178.39400	10,668 m		
KENNE	G594	-36.64250	9,800 ft	154	-
FIX	AWY-HI	175.63000	2,987 m		
NZAA	-	-37.00810	0 ft	45	Auckland Intl
APT	-	174.79200	0 m		

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4

Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.442 E

METAR

KLAX 050053Z 26014KT 10SM SCT013 BKN029 BKN034 16/11 A2991 RMK A02 SLP129 T01560111

TAF

KLAX 050003Z 0500/0606 27018G25KT P6SM BKN025 FM050600 26018G25KT P6SM VCSH BKN025 OVC050 FM051100 28015G22KT P6SM

Frequencies

COM - 122.95 MHz - UNICOM	GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.75 MHz - LOS ANGELES GROUND	GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER	TWR - 120.95 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER	REC - 133.80 MHz - D-ATIS
REC - 135.65 MHz - D-ATIS	APP - 124.90 MHz - SOCAL APPROACH
APP - 124.30 MHz - SOCAL APPROACH	APP - 124.50 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH	DEP - 125.20 MHz - SOCAL DEPARTURE
DEP - 124.30 MHz - SOCAL DEPARTURE	CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft	11,106 ft	82.96	CONCRETE	0 ft	381 ft
	61 m	3,385 m	71.51		0 m	116 m
25L	200 ft	11,106 ft	262.98	CONCRETE	0 ft	381 ft
	61 m	3,385 m	251.53		0 m	116 m
07L	151 ft	12,935 ft	82.95	CONCRETE	846 ft	374 ft
	46 m	3,943 m	71.51		258 m	114 m
25R	151 ft	12,935 ft	262.98	CONCRETE	968 ft	197 ft
	46 m	3,943 m	251.53		295 m	60 m
06R	151 ft	10,896 ft	82.95	CONCRETE	551 ft	384 ft
	46 m	3,321 m	71.50		168 m	117 m
24L	151 ft	10,896 ft	262.97	CONCRETE	814 ft	384 ft
	46 m	3,321 m	251.52		248 m	117 m
06L	151 ft	8,936 ft	82.95	CONCRETE	0 ft	0 ft
	46 m	2,724 m	71.51		0 m	0 m
24R	151 ft	8,936 ft	262.96	CONCRETE	0 ft	285 ft
	46 m	2,724 m	251.52		0 m	87 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
06R	DME	IGPE	111.70 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
07L	DME	IIAS	111.10 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
07R	DME	IMKZ	109.90 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
24L	DME	IHQB	111.70 MHz	18 nm	-	-	133 ft
				33 km	-		133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	- -	-	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	- -	-	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	- -	-	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.54	-	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.54	-	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.54	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.54	3.00	125 ft 125 m

NZAA

Region: NEW ZEALAND AND ANTARCTICA
Timezone: PACIFIC/AUCKLAND
Runways: 1

Elevation: 23 ft / 7 m
Location: -37.008100 174.792000
Magnetic Var: 20.178 E

METAR

NZAA 050130Z AUTO 01007KT 340V050 9999 FEW039/// 19/10 Q1022

TAF

TAF NZAA 042309Z 0500/0606 06010KT 9999 FEW050 BECMG 0508/0510 VRB02KT FM052300 02010KT 9999 -SHRA SCT025 BKN050

Frequencies

REC - 127.80 MHz - ATIS	REC - 127.00 MHz - ATIS
GND - 121.90 MHz - AUCKLAND GROUND	TWR - 118.70 MHz - AUCKLAND TOWER
TWR - 120.95 MHz - AUCKLAND TOWER	CLD - 128.20 MHz - CLEARANCE DELIVERY
APP - 120.10 MHz - AUCKLAND APPROACH	APP - 124.30 MHz - AUCKLAND APPROACH
APP - 129.50 MHz - AUCKLAND APPROACH	APP - 129.60 MHz - AUCKLAND APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05R	151 ft	12,040 ft	70.92	CONCRETE	1,250 ft	0 ft
	46 m	3,670 m	50.75		381 m	0 m
23L	151 ft	12,040 ft	250.90	CONCRETE	0 ft	131 ft
	46 m	3,670 m	230.72		0 m	40 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05R	DME	IAA	110.30 MHz	18 nm	-	-	23 ft
				33 km	-		23 m
23L	DME	IMG	109.90 MHz	18 nm	-	-	23 ft
				33 km	-		23 m
05R	LOC-ILS	IAA	110.30 MHz	18 nm	70.91	-	23 ft
				33 km	50.73		23 m
23L	LOC-ILS	IMG	109.90 MHz	18 nm	250.91	-	23 ft
				33 km	230.73		23 m
05R	GS	IAA	110.30 MHz	10 nm	70.91	3.00	23 ft
				19 km	50.73		23 m
23L	GS	IMG	109.90 MHz	10 nm	250.91	3.00	23 ft
				19 km	230.73		23 m