

# YSSY

Sydney Kingsford Smith Intl


# YMML

Melbourne Intl

2024/05/18 0134Z

YSSY BUNGO V169 WAZZA YMML

381.44 nm / 706.43 km



## Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1000ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes



## Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
YSSY APT	-	-33.94610 151.17700	0 ft 0 m	-	Sydney Kingsford Smith Intl
BUNGO FIX	-	-34.89200 149.85600	30,900 ft 9,418 m	86	-
CB VOR	V169 AWY-LO	-35.28140 149.19600	35,000 ft 10,668 m	39	CANBERRA
DUBUS FIX	V169 AWY-LO	-36.14850 147.86200	24,400 ft 7,437 m	83	-
WAZZA FIX	V169 AWY-LO	-36.79910 146.63000	14,300 ft 4,359 m	71	-
YMML APT	-	-37.66550 144.83700	0 ft 0 m	100	Melbourne Intl

## YSSY

Region: AUSTRALIA  
Timezone: AUSTRALIA/SYDNEY  
Runways: 3

Elevation: 21 ft / 6 m  
Location: -33.946100 151.177000  
Magnetic Var: 12.672 E

## METAR

YSSY 180100Z 20026KT 9999 FEW028 SCT045 14/10 Q1022 RF00.0/000.0

## TAF

TAF AMD YSSY 172323Z 1800/1906 20027KT 9999 -SHRA SCT030 FM180800 20020KT 9999 -SHRA SCT025 FM181300 21018KT 9999

## Frequencies

REC - 118.55 MHz - ATIS	REC - 126.55 MHz - ATIS
TWR - 124.70 MHz - SYDNEY TOWER	TWR - 120.50 MHz - SYDNEY TOWER
GND - 126.50 MHz - SYDNEY GROUND	GND - 121.70 MHz - SYDNEY GROUND
GND - 130.95 MHz - ANSETT APRON	GND - 127.60 MHz - SYDNEY COORDINATOR
CLD - 133.80 MHz - SYDNEY CLEARANCE DELIVERY	APP - 124.40 MHz - SYDNEY APPROACH
APP - 128.30 MHz - SYDNEY APPROACH	APP - 135.90 MHz - SYDNEY APPROACH
APP - 126.10 MHz - SYDNEY DIRECT	APP - 125.30 MHz - SYDNEY DIRECT
APP - 133.95 MHz - ILS MONITOR	APP - 119.45 MHz - ILS MONITOR
DEP - 129.70 MHz - SYDNEY DEPARTURE	DEP - 128.30 MHz - SYDNEY DEPARTURE
DEP - 123.00 MHz - SYDNEY DEPARTURE	DEP - 118.40 MHz - SYDNEY DEPARTURE

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16L	148 ft	8,018 ft	167.85	ASPHALT	758 ft	295 ft
	45 m	2,444 m	155.18		231 m	90 m
34R	148 ft	8,018 ft	347.85	ASPHALT	125 ft	295 ft
	45 m	2,444 m	335.18		38 m	90 m
07	148 ft	8,285 ft	74.14	ASPHALT	0 ft	489 ft
	45 m	2,525 m	61.46		0 m	149 m
25	148 ft	8,285 ft	254.12	ASPHALT	331 ft	197 ft
	45 m	2,525 m	241.45		101 m	60 m
16R	148 ft	13,029 ft	167.86	ASPHALT	279 ft	299 ft
	45 m	3,971 m	155.19		85 m	91 m
34L	148 ft	13,029 ft	347.85	ASPHALT	0 ft	620 ft
	45 m	3,971 m	335.18		0 m	189 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07	DME	ISY	109.90 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
16L	DME	ISS	110.90 MHz	18 nm	-	-	30 ft
				33 km	-		30 m
25	DME	ISW	109.70 MHz	18 nm	-	-	33 ft
				33 km	-		33 m
34R	DME	IKN	109.30 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
07	LOC-ILS	ISY	109.90 MHz	18 nm	74.13	-	21 ft
				33 km	61.46		21 m
16L	LOC-ILS	ISS	110.90 MHz	18 nm	167.85	-	21 ft
				33 km	155.18		21 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16R	LOC-ILS	IKS	109.50 MHz	18 nm	167.86	-	21 ft
				33 km	155.19		21 m
25	LOC-ILS	ISW	109.70 MHz	18 nm	254.13	-	21 ft
				33 km	241.46		21 m
34L	LOC-ILS	ISN	110.10 MHz	18 nm	347.86	-	21 ft
				33 km	335.19		21 m
34R	LOC-ILS	IKN	109.30 MHz	18 nm	347.85	-	21 ft
				33 km	335.18		21 m
07	GS	ISY	109.90 MHz	10 nm	74.13	3.00	21 ft
				19 km	61.46		21 m
16L	GS	ISS	110.90 MHz	10 nm	167.85	3.00	21 ft
				19 km	155.18		21 m
16R	GS	IKS	109.50 MHz	10 nm	167.86	3.00	21 ft
				19 km	155.19		21 m
25	GS	ISW	109.70 MHz	10 nm	254.13	3.00	21 ft
				19 km	241.46		21 m
34L	GS	ISN	110.10 MHz	10 nm	347.86	3.00	21 ft
				19 km	335.19		21 m
34R	GS	IKN	109.30 MHz	10 nm	347.85	3.00	21 ft
				19 km	335.18		21 m

## YMML

Region: AUSTRALIA  
Timezone: AUSTRALIA/MELBOURNE  
Runways: 2

Elevation: 433 ft / 132 m  
Location: -37.665500 144.837000  
Magnetic Var: 11.562 E

## METAR

YMML 180100Z 16013KT 9999 FEW040 12/01 Q1033

## TAF

TAF YMML 172320Z 1800/1906 16012KT 9999 SCT040 FM181000 25005KT 9999 SCT040 FM182200 27011KT 9999 SCT020

## Frequencies

REC - 132.67 MHz - YMML ATIS  
GND - 121.70 MHz - MELBOURNE GND  
APP - 132.00 MHz - MELBOURNE APP

CLD - 127.20 MHz - MELBOURNE INTL CLD  
TWR - 120.50 MHz - MELBOURNE TWR  
DEP - 118.90 MHz - MELBOURNE DEP

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	148 ft	7,513 ft	94.00	ASPHALT	0 ft	197 ft
	45 m	2,290 m	82.44		0 m	60 m
27	148 ft	7,513 ft	273.98	ASPHALT	0 ft	174 ft
	45 m	2,290 m	262.42		0 m	53 m
16	155 ft	12,012 ft	171.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	160.04		0 m	61 m
34	155 ft	12,012 ft	351.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	340.04		0 m	61 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	LOC-ILS	IMS	109.70 MHz	18 nm	171.60	-	433 ft
				33 km	160.04		433 m
27	LOC-ILS	IMW	109.30 MHz	18 nm	273.99	-	433 ft
				33 km	262.43		433 m
16	GS	IMS	109.70 MHz	10 nm	171.60	3.00	433 ft
				19 km	160.04		433 m
27	GS	IMW	109.30 MHz	10 nm	273.99	3.00	433 ft
				19 km	262.43		433 m