KLAX - KVNY

Los Angeles Intl

Van Nuys

2024/03/29 0526Z

KLAX +33.95_-118.29 +34.04_-118.39 +34.12_-118.48 KVNY

22.85 nm / 42.32 km





Notes

Departing runway 8 KLAX. Arriving runway 17 KVNY.

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KLAX APT	- -	33.93990 -118.37984	0 ft 0 m	-	-
+33.95_-118.29 LATLON	- -	33.94871 -118.29326	100 ft 30 m	4	-
+34.04_-118.39 LATLON	- -	34.03678 -118.38781	100 ft 30 m	7	-
+34.12_-118.48 LATLON	- -	34.12485 -118.48236	100 ft 30 m	7	-
KVNY APT	- -	34.19699 -118.48917	0 ft 0 m	4	-

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4

Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.451 E

METAR

KLAX 290453Z 27009KT 10SM FEW050 13/09 A3001 RMK AO2 SLP161 T01280094 $

TAF

KLAX 290255Z 2903/3006 24015KT P6SM FEW012 FM290400 25010KT P6SM BKN250 FM291200 25006KT P6SM BKN100 FM291900 220

Frequencies

COM - 122.95 MHz - UNICOM
GND - 121.75 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER
REC - 135.65 MHz - D-ATIS
APP - 124.30 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH
DEP - 124.30 MHz - SOCAL DEPARTURE
GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 120.95 MHz - LOS ANGELES TOWER
REC - 133.80 MHz - D-ATIS
APP - 124.90 MHz - SOCAL APPROACH
APP - 124.50 MHz - SOCAL APPROACH
DEP - 125.20 MHz - SOCAL DEPARTURE
CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft 61 m	11,106 ft 3,385 m	82.96 71.51	CONCRETE	0 ft 0 m	381 ft 116 m
25L	200 ft 61 m	11,106 ft 3,385 m	262.98 251.53	CONCRETE	0 ft 0 m	381 ft 116 m
07L	151 ft 46 m	12,935 ft 3,943 m	82.95 71.50	CONCRETE	846 ft 258 m	374 ft 114 m
25R	151 ft 46 m	12,935 ft 3,943 m	262.98 251.52	CONCRETE	968 ft 295 m	197 ft 60 m
06R	151 ft 46 m	10,896 ft 3,321 m	82.95 71.50	CONCRETE	551 ft 168 m	384 ft 117 m
24L	151 ft 46 m	10,896 ft 3,321 m	262.97 251.52	CONCRETE	814 ft 248 m	384 ft 117 m
06L	151 ft 46 m	8,936 ft 2,724 m	82.95 71.50	CONCRETE	0 ft 0 m	0 ft 0 m
24R	151 ft 46 m	8,936 ft 2,724 m	262.96 251.51	CONCRETE	0 ft 0 m	285 ft 87 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm 33 km	- -	-	120 ft 120 m
06R	DME	IGPE	111.70 MHz	18 nm 33 km	- -	-	120 ft 120 m
07L	DME	IIAS	111.10 MHz	18 nm 33 km	- -	-	103 ft 103 m
07R	DME	IMKZ	109.90 MHz	18 nm 33 km	- -	-	103 ft 103 m
24L	DME	IHQB	111.70 MHz	18 nm 33 km	- -	-	133 ft 133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	- -	-	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	- -	-	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	- -	-	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.52	-	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.52	-	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.53	-	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.52	-	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.52	-	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.52	-	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.52	-	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.53	-	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.53	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.52	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.52	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.53	3.00	125 ft 125 m

KVNY

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 2

Elevation: 802 ft / 244 m
Location: 34.210700 -118.490000
Magnetic Var: 11.517 E

METAR

KVNY 290451Z 20003KT 10SM SCT034 13/00 A2998 RMK AO2 SLP149 T01280000

TAF

KVNY 282350Z 2900/2924 17010KT P6SM SCT050 FM290500 VRB03KT P6SM BKN025 FM291900 17008KT P6SM BKN100

Frequencies

REC - 127.55 MHz - ATIS
COM - 122.95 MHz - UNICOM
GND - 121.70 MHz - VAN NUYS GROUND
TWR - 119.30 MHz - VAN NUYS TOWER
APP - 134.20 MHz - SOCAL APPROACH
DEP - 120.40 MHz - SOCAL APPROACH
COM - 119.30 MHz - CTAF
CLD - 126.60 MHz - CLEARANCE DELIVERY
TWR - 120.20 MHz - VAN NUYS TOWER
APP - 124.60 MHz - SOCAL APPROACH
APP - 135.05 MHz - SOCAL APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16R	151 ft 46 m	8,027 ft 2,447 m	175.52 164.01	ASPHALT	1,430 ft 436 m	151 ft 46 m
34L	151 ft 46 m	8,027 ft 2,447 m	355.52 344.01	ASPHALT	0 ft 0 m	174 ft 53 m
16L	75 ft 23 m	4,026 ft 1,227 m	175.53 164.02	ASPHALT	1,437 ft 438 m	0 ft 0 m
34R	75 ft 23 m	4,026 ft 1,227 m	355.53 344.02	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16R	LOC-ILS	IVNY	111.30 MHz	18 nm 33 km	175.52 164.00	-	802 ft 802 m
16R	GS	IVNY	111.30 MHz	10 nm 19 km	175.52 164.00	3.50	802 ft 802 m