YSCB
Canberra


-

NZAA
Auckland International

2024/03/29 0557Z

YSCB SADEM NZAA

1240.86 nm / 2298.08 km



Notes

Generated

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
YSCB APT	–	-35.29060 149.19447	0 ft 0 m	–	–
SADEM FIX	–	-37.01630 174.69125	0 ft 0 m	1237	–
NZAA APT	–	-37.01438 174.77090	0 ft 0 m	3	–

YSCB

Region: AUSTRALIA
Timezone: AUSTRALIA/SYDNEY
Runways: 2

Elevation: 1,886 ft / 575 m
Location: -35.305500 149.193000
Magnetic Var: 12.469 E

METAR

YSCB 290530Z AUTO 05005KT 020V090 9999 // NCD 27/11 Q1024 RF00.0/000.0

TAF

TAF YSCB 290227Z 2903/3000 35008KT 9999 FEW040 FM290700 06005KT CAVOK FM291200 VRB03KT CAVOK PROB30 2917/2921 030

Frequencies

REC - 127.45 MHz - CANBERRA ATIS
TWR - 118.70 MHz - CANBERRA TOWER
DEP - 125.90 MHz - CANBERRA DEPARTURE
APP - 125.90 MHz - CANBERRA APPROACH

GND - 121.70 MHz - CANBERRA GROUND
COM - 118.70 MHz - CANBERRA CTAF
DEP - 124.50 MHz - CANBERRA DEPARTURE
APP - 124.50 MHz - CANBERRA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
17	148 ft 45 m	10,795 ft 3,290 m	179.99 167.52	ASPHALT	0 ft 0 m	148 ft 45 m
35	148 ft 45 m	10,795 ft 3,290 m	359.99 347.52	ASPHALT	1,968 ft 600 m	92 ft 28 m
12	148 ft 45 m	5,501 ft 1,677 m	130.00 117.53	ASPHALT	0 ft 0 m	0 ft 0 m
30	148 ft 45 m	5,501 ft 1,677 m	310.00 297.53	ASPHALT	213 ft 65 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
35	DME	ICB	109.50 MHz	18 nm 33 km	- -	-	1,888 ft 1,888 m
35	LOC-ILS	ICB	109.50 MHz	18 nm 33 km	359.99 347.52	-	1,886 ft 1,886 m
35	GS	ICB	109.50 MHz	10 nm 19 km	359.99 347.52	3.00	1,886 ft 1,886 m

NZAA

Region: NEW ZEALAND AND ANTARCTICA
Timezone: PACIFIC/AUCKLAND
Runways: 1
Elevation: 23 ft / 7 m
Location: -37.008100 174.792000
Magnetic Var: 20.172 E

METAR

NZAA 290530Z AUTO 22018KT 9999 SCT043/// SCT060/// 17/09 Q1009

TAF

TAF NZAA 290209Z 2903/3006 24020KT 9999 -SHRA FEW030 BKN050 FM290900 18010KT 9999 FEW030 BECMG 2920/2922 20020KT

Frequencies

REC - 127.80 MHz - ATIS
GND - 121.90 MHz - AUCKLAND GROUND
TWR - 120.95 MHz - AUCKLAND TOWER
APP - 120.10 MHz - AUCKLAND APPROACH
APP - 129.50 MHz - AUCKLAND APPROACH
REC - 127.00 MHz - ATIS
TWR - 118.70 MHz - AUCKLAND TOWER
CLD - 128.20 MHz - CLEARANCE DELIVERY
APP - 124.30 MHz - AUCKLAND APPROACH
APP - 129.60 MHz - AUCKLAND APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05R	151 ft 46 m	12,040 ft 3,670 m	70.92 50.75	CONCRETE	1,250 ft 381 m	0 ft 0 m
23L	151 ft 46 m	12,040 ft 3,670 m	250.90 230.73	CONCRETE	0 ft 0 m	131 ft 40 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05R	DME	IAA	110.30 MHz	18 nm 33 km	- -	-	23 ft 23 m
23L	DME	IMG	109.90 MHz	18 nm 33 km	- -	-	23 ft 23 m
05R	LOC-ILS	IAA	110.30 MHz	18 nm 33 km	70.91 50.74	-	23 ft 23 m
23L	LOC-ILS	IMG	109.90 MHz	18 nm 33 km	250.91 230.74	-	23 ft 23 m
05R	GS	IAA	110.30 MHz	10 nm 19 km	70.91 50.74	3.00	23 ft 23 m
23L	GS	IMG	109.90 MHz	10 nm 19 km	250.91 230.74	3.00	23 ft 23 m