

MPTO

Tocumen Intl


SKBO

El Dorado Intl

2024/05/21 2202Z

MPTO PML **UG447** RNG **UQ121** ISVAT SKBO

410.00 nm / 759.32 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
MPTO	-	9.07140	0 ft	-	Tocumen Intl
APT	-	-79.38350	0 m		
PML	-	8.40622	30,000 ft	84	LA PALMA
VOR	-	-78.13860	9,144 m		
ARORO	UG447	7.73472	35,000 ft	60	-
FIX	AWY-HI	-77.39140	10,668 m		
RNG	UG447	5.98056	23,100 ft	157	RIONEGRO (MEDELLIN)
VOR	AWY-HI	-75.41830	7,041 m		
ISVAT	UQ121	5.69472	17,900 ft	24	-
FIX	AWY-HI	-75.12500	5,456 m		
SKBO	-	4.70160	0 ft	83	El Dorado Intl
APT	-	-74.14700	0 m		

MPTO

Region: PANAMA
Timezone: AMERICA/PANAMA
Runways: 2

Elevation: 134 ft / 41 m
Location: 9.071400 -79.383500
Magnetic Var: 5.457 W

METAR

MPTO 212100Z 16004KT 9999 SCT016CB SCT090 28/25 Q1007 TEMPO TS

TAF

TAF MPTO 211700Z 2118/2224 15006KT 9999 SCT018TCU SCT090 PROB30 TEMPO 2118/2122 30005KT 5000 TSRA SCT016CB BKN080

Frequencies

REC - 127.70 MHz - ATIS	TWR - 118.10 MHz - TOCUMEN TOWER
GND - 121.90 MHz - TOCUMEN GROUND	GND - 112.05 MHz - TOCUMEN GROUND
CLD - 129.80 MHz - CLEARANCE DELIVERY	APP - 121.20 MHz - PANAMA APPROACH
APP - 123.30 MHz - PANAMA APPROACH	APP - 119.70 MHz - PANAMA APPROACH
APP - 119.20 MHz - PANAMA APPROACH	

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03R	148 ft	10,049 ft	29.33	CONCRETE	0 ft	0 ft
	45 m	3,063 m	34.78		0 m	0 m
21L	148 ft	10,049 ft	209.33	CONCRETE	0 ft	0 ft
	45 m	3,063 m	214.79		0 m	0 m
03L	148 ft	8,832 ft	30.67	ASPHALT	814 ft	0 ft
	45 m	2,692 m	36.13		248 m	0 m
21R	148 ft	8,832 ft	210.67	ASPHALT	0 ft	0 ft
	45 m	2,692 m	216.13		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03R	DME	INAT	110.70 MHz	18 nm	-	-	50 ft
				33 km	-		50 m
03R	LOC-ILS	INAT	110.70 MHz	18 nm	29.33	-	134 ft
				33 km	34.79		134 m
03R	GS	INAT	110.70 MHz	10 nm	29.33	3.00	134 ft
				19 km	34.79		134 m

SKBO

Region: COLOMBIA
Timezone: AMERICA/BOGOTA
Runways: 2

Elevation: 8,358 ft / 2,548 m
Location: 4.701600 -74.147000
Magnetic Var: 8.197 W

METAR

SKBO 212100Z 17012KT 9999 VCSH SCT023 19/11 Q1025 NOSIG

TAF

TAF SKBO 211630Z 2118/2218 16012KT 9999 BKN020 TEMPO 2119/2123 DZ BKN017TCU BECMG 2201/2203 VRB02KT TX21/2118Z TN

Frequencies

REC - 127.80 MHz - ATIS	TWR - 118.10 MHz - EL DORADO TOWER
TWR - 118.25 MHz - EL DORADO TOWER	GND - 121.80 MHz - EL DORADO GROUND
GND - 122.75 MHz - EL DORADO GROUND	APP - 121.30 MHz - BOGOTA APPROACH
APP - 119.50 MHz - BOGOTA APPROACH	APP - 119.65 MHz - BOGOTA APPROACH
APP - 119.95 MHz - BOGOTA APPROACH	

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
13R	151 ft	12,479 ft	127.23	ASPHALT	0 ft	203 ft
	46 m	3,804 m	135.43		0 m	62 m
31L	151 ft	12,479 ft	307.24	ASPHALT	0 ft	203 ft
	46 m	3,804 m	315.43		0 m	62 m
13L	151 ft	12,479 ft	127.24	ASPHALT	0 ft	98 ft
	46 m	3,804 m	135.43		0 m	30 m
31R	151 ft	12,479 ft	307.24	ASPHALT	0 ft	98 ft
	46 m	3,804 m	315.44		0 m	30 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
13L	DME	IEDR	111.30 MHz	18 nm	-	-	8,361 ft
				33 km	-		8,361 m
13R	DME	IADO	110.70 MHz	18 nm	-	-	8,361 ft
				33 km	-		8,361 m
13L	LOC-ILS	IEDR	111.30 MHz	18 nm	127.24	-	8,358 ft
				33 km	135.44		8,358 m
13R	LOC-ILS	IADO	110.70 MHz	18 nm	127.24	-	8,358 ft
				33 km	135.44		8,358 m
13L	GS	IEDR	111.30 MHz	10 nm	127.24	3.00	8,358 ft
				19 km	135.44		8,358 m
13R	GS	IADO	110.70 MHz	10 nm	127.24	3.00	8,358 ft
				19 km	135.44		8,358 m