


2024/05/08 0130Z

VIDP SP VISM

155.44 nm / 287.88 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
VIDP	-	28.56650	0 ft	-	INDIRA GANDHI INTL
APT	-	77.10309	0 m		
SP	-	29.99991	14,400 ft	87	SARSAWA NDB
NDB	-	77.43201	4,389 m		
VISM	-	31.08180	0 ft	67	SHIMLA
APT	-	77.06797	0 m		

VIDP

Region: INDIA
Timezone: ASIA/KOLKATA
Runways: 3

Elevation: 778 ft / 237 m
Location: 28.558500 77.097900
Magnetic Var: 1.600 E

METAR

VIDP 080100Z 09008KT 2800 HZ FEW035 28/21 Q1007 NOSIG

TAF

TAF VIDP 072300Z 0800/0906 09010KT 2000 HZ SCT100 BECMG 0803/0805 3000 HZ BECMG 0807/0809 5000 HZ BECMG 0816/0818

Frequencies

REC - 126.40 MHz - DELHI ATIS
TWR - 118.10 MHz - DELHI TOWER
APP - 124.20 MHz - DELHI APPROACH
GND - 121.90 MHz - DELHI GROUND
APP - 126.35 MHz - DELHI APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
11	197 ft	14,509 ft	103.69	ASPHALT	2,106 ft	0 ft
	60 m	4,422 m	102.09		642 m	0 m
29	197 ft	14,509 ft	283.72	ASPHALT	4,780 ft	0 ft
	60 m	4,422 m	282.12		1,457 m	0 m
10	150 ft	12,511 ft	104.69	ASPHALT	0 ft	883 ft
	46 m	3,813 m	103.09		0 m	269 m
28	150 ft	12,511 ft	284.71	ASPHALT	0 ft	476 ft
	46 m	3,813 m	283.11		0 m	145 m
09	150 ft	9,219 ft	91.44	ASPHALT	0 ft	197 ft
	46 m	2,810 m	89.84		0 m	60 m
27	150 ft	9,219 ft	271.46	ASPHALT	499 ft	0 ft
	46 m	2,810 m	269.86		152 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
10	DME	DEL	109.50 MHz	18 nm	-	-	777 ft
				33 km	-		777 m
27	DME	IDLH	110.50 MHz	18 nm	-	-	777 ft
				33 km	-		777 m
28	DME	IPLM	110.30 MHz	18 nm	-	-	777 ft
				33 km	-		777 m
09	LOC-ILS	IDIA	108.50 MHz	18 nm	91.45	-	778 ft
				33 km	89.85		778 m
10	LOC-ILS	IDEL	109.50 MHz	18 nm	104.70	-	778 ft
				33 km	103.10		778 m
27	LOC-ILS	IDLH	110.50 MHz	18 nm	271.45	-	778 ft
				33 km	269.85		778 m
28	LOC-ILS	IPLM	110.30 MHz	18 nm	284.70	-	778 ft
				33 km	283.10		778 m
11	LOC-ILS	IDMR	111.30 MHz	18 nm	103.71	-	778 ft
				33 km	102.11		778 m
29	LOC-ILS	IDGM	110.90 MHz	18 nm	283.71	-	778 ft
				33 km	282.11		778 m
09	GS	IDIA	108.50 MHz	10 nm	91.45	3.00	778 ft

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
				19 km	89.85		778 m
10	GS	IDEL	109.50 MHz	10 nm	104.70	3.00	778 ft
				19 km	103.10		778 m
27	GS	IDLH	110.50 MHz	10 nm	271.45	3.00	778 ft
				19 km	269.85		778 m
28	GS	IPLM	110.30 MHz	10 nm	284.70	3.00	778 ft
				19 km	283.10		778 m
11	GS	IDMR	111.30 MHz	10 nm	103.71	3.00	778 ft
				19 km	102.11		778 m
29	GS	IDGM	110.90 MHz	10 nm	283.71	3.00	778 ft
				19 km	282.11		778 m