

KMKE

General Mitchell Intl


KORD

Chicago O'Hare International

2024/05/18 0218Z

KMKE KENW OBK CHIKO KORD

58.73 nm / 108.77 km



Notes

Requested: KMKE KENW OBK CHIKO PANME KORD

Unmatched points: PANME

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KMKE APT	- -	42.94790 -87.89650	0 ft 0 m	-	General Mitchell Intl
KENW APT	- -	42.59570 -87.92780	0 ft 0 m	21	KENOSHA RGNL
OBK VOR	- -	42.22140 -87.95160	0 ft 0 m	22	NORTHBROOK
CHIKO FIX	- -	42.20160 -87.94840	0 ft 0 m	1	-
KORD APT	- -	41.97340 -87.90660	0 ft 0 m	13	Chicago O'Hare International

KMKE

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 5

Elevation: 728 ft / 222 m
Location: 42.947900 -87.896500
Magnetic Var: 4.242 W

METAR

KMKE 180152Z 16005KT 10SM CLR 15/11 A2979 RMK A02 SLP085 T01500111

TAF

KMKE 172338Z 1800/1906 10005KT P6SM FEW250 FM180500 VRB03KT 3SM BR SCT025 FM181300 VRB04KT P6SM FEW030 FM181500 1

Frequencies

REC - 126.40 MHz - D-ATIS
GND - 121.80 MHz - MILWAUKEE GROUND
CLD - 120.80 MHz - MILWAUKEE CLEARANCE DELIVERY
DEP - 135.87 MHz - MILWAUKEE DEPARTURE
APP - 126.50 MHz - MILWAUKEE APPROACH
COM - 122.95 MHz - MILWAUKEE UNICOM
TWR - 124.57 MHz - MILWAUKEE TOWER
DEP - 125.35 MHz - MILWAUKEE DEPARTURE
APP - 118.00 MHz - MILWAUKEE APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01L	200 ft	10,006 ft	7.14	CONCRETE	302 ft	407 ft
	61 m	3,050 m	11.38		92 m	124 m
19R	200 ft	10,006 ft	187.14	CONCRETE	791 ft	289 ft
	61 m	3,050 m	191.38		241 m	88 m
01R	150 ft	4,187 ft	7.13	ASPHALT	0 ft	0 ft
	46 m	1,276 m	11.37		0 m	0 m
19L	150 ft	4,187 ft	187.13	ASPHALT	0 ft	0 ft
	46 m	1,276 m	191.37		0 m	0 m
13	150 ft	5,539 ft	132.37	ASPHALT	741 ft	0 ft
	46 m	1,688 m	136.61		226 m	0 m
31	150 ft	5,539 ft	312.38	ASPHALT	207 ft	325 ft
	46 m	1,688 m	316.62		63 m	99 m
07L	100 ft	4,789 ft	71.58	ASPHALT	0 ft	0 ft
	30 m	1,460 m	75.83		0 m	0 m
25R	100 ft	4,789 ft	251.59	ASPHALT	0 ft	0 ft
	30 m	1,460 m	255.84		0 m	0 m
07R	150 ft	8,286 ft	71.57	CONCRETE	0 ft	200 ft
	46 m	2,526 m	75.81		0 m	61 m
25L	150 ft	8,286 ft	251.59	CONCRETE	433 ft	246 ft
	46 m	2,526 m	255.83		132 m	75 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07R	DME	IGMF	111.50 MHz	18 nm	-	-	730 ft
				33 km	-		730 m
25L	DME	IPXY	111.50 MHz	18 nm	-	-	723 ft
				33 km	-		723 m
01L	LOC-ILS	IMKE	110.30 MHz	18 nm	7.14	-	728 ft
				33 km	11.38		728 m
07R	LOC-ILS	IGMF	111.50 MHz	18 nm	71.58	-	728 ft
				33 km	75.82		728 m
19R	LOC-ILS	IBLY	110.30 MHz	18 nm	187.14	-	728 ft

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
				33 km	191.38		728 m
25L	LOC-LOC	IPXY	111.50 MHz	18 nm	251.58	-	728 ft
				33 km	255.82		728 m
01L	GS	IMKE	110.30 MHz	10 nm	7.14	3.00	728 ft
				19 km	11.38		728 m
07R	GS	IGMF	111.50 MHz	10 nm	71.58	3.00	728 ft
				19 km	75.82		728 m
19R	GS	IBLY	110.30 MHz	10 nm	187.14	3.00	728 ft
				19 km	191.38		728 m

KORD

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 6

Elevation: 680 ft / 207 m
Location: 41.973400 -87.906600
Magnetic Var: 4.112 W

METAR

KORD 180151Z 08006KT 10SM CLR 19/12 A2978 RMK A02 SLP082 T01940117

TAF

TAF KORD 172320Z 1800/1906 09008KT P6SM FEW070 FM180400 15003KT 6SM BR SKC FM181400 20009KT P6SM FEW050 FM190100 1

Frequencies

REC - 135.40 MHz - ATIS	COM - 122.95 MHz - UNICOM
CLD - 119.25 MHz - CLEARANCE DELIVERY	CLD - 121.60 MHz - CLEARANCE DELIVERY
GND - 118.05 MHz - O'HARE GROUND	GND - 121.67 MHz - O'HARE GROUND
GND - 121.75 MHz - O'HARE GROUND	GND - 121.90 MHz - O'HARE GROUND
GND - 124.12 MHz - O'HARE GROUND	GND - 134.12 MHz - O'HARE GROUND
TWR - 120.75 MHz - O'HARE TOWER	TWR - 121.15 MHz - O'HARE TOWER
TWR - 126.90 MHz - O'HARE TOWER	TWR - 127.92 MHz - O'HARE TOWER
TWR - 132.70 MHz - O'HARE TOWER	TWR - 128.15 MHz - O'HARE TOWER
TWR - 133.00 MHz - O'HARE TOWER	APP - 119.00 MHz - CHICAGO APPROACH
APP - 133.62 MHz - CHICAGO APPROACH	APP - 124.35 MHz - CHICAGO APPROACH
APP - 125.70 MHz - CHICAGO APPROACH	DEP - 125.00 MHz - CHICAGO DEPARTURE
DEP - 125.40 MHz - CHICAGO DEPARTURE	DEP - 127.40 MHz - CHICAGO DEPARTURE
DEP - 128.80 MHz - CHICAGO DEPARTURE	

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10C	200 ft	10,789 ft	89.85	CONCRETE	0 ft	397 ft
	61 m	3,289 m	93.96		0 m	121 m
28C	200 ft	10,789 ft	269.88	CONCRETE	0 ft	381 ft
	61 m	3,289 m	273.99		0 m	116 m
10L	151 ft	12,996 ft	89.87	CONCRETE	0 ft	394 ft
	46 m	3,961 m	93.99		0 m	120 m
28R	151 ft	12,996 ft	269.91	CONCRETE	0 ft	285 ft
	46 m	3,961 m	274.02		0 m	87 m
04R	151 ft	8,074 ft	41.40	CONCRETE	0 ft	850 ft
	46 m	2,461 m	45.51		0 m	259 m
22L	151 ft	8,074 ft	221.41	CONCRETE	0 ft	584 ft
	46 m	2,461 m	225.53		0 m	178 m
09R	151 ft	7,949 ft	89.98	CONCRETE	0 ft	148 ft
	46 m	2,423 m	94.09		0 m	45 m
27L	151 ft	7,949 ft	270.00	CONCRETE	0 ft	197 ft
	46 m	2,423 m	274.11		0 m	60 m
09L	151 ft	7,484 ft	89.99	CONCRETE	0 ft	397 ft
	46 m	2,281 m	94.10		0 m	121 m
27R	151 ft	7,484 ft	270.00	CONCRETE	0 ft	397 ft
	46 m	2,281 m	274.12		0 m	121 m
10R	151 ft	7,484 ft	89.85	CONCRETE	0 ft	400 ft
	46 m	2,281 m	93.96		0 m	122 m
28L	151 ft	7,484 ft	269.87	CONCRETE	0 ft	400 ft
	46 m	2,281 m	273.98		0 m	122 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	ISAJ	111.75 MHz	18 nm	-	-	668 ft
				33 km	-		668 m
10L	DME	IMED	111.10 MHz	18 nm	-	-	678 ft
				33 km	-		678 m
27L	DME	IIAC	110.50 MHz	18 nm	-	-	641 ft
				33 km	-		641 m
27R	DME	IABU	111.75 MHz	18 nm	-	-	668 ft
				33 km	-		668 m
28R	DME	ITSL	111.10 MHz	18 nm	-	-	678 ft
				33 km	-		678 m
04R	LOC-ILS	IFJU	110.10 MHz	18 nm	41.41	-	680 ft
				33 km	45.52		680 m
09L	LOC-ILS	ISAJ	111.75 MHz	18 nm	90.00	-	680 ft
				33 km	94.11		680 m
09R	LOC-ILS	IJAV	110.50 MHz	18 nm	89.99	-	680 ft
				33 km	94.10		680 m
10L	LOC-ILS	IMED	111.10 MHz	18 nm	89.89	-	680 ft
				33 km	94.00		680 m
10C	LOC-ILS	ISXH	108.95 MHz	18 nm	89.86	-	680 ft
				33 km	93.97		680 m
10R	LOC-ILS	IIZJ	110.75 MHz	18 nm	89.86	-	680 ft
				33 km	93.97		680 m
22L	LOC-ILS	ILQQ	110.10 MHz	18 nm	221.41	-	680 ft
				33 km	225.52		680 m
27L	LOC-ILS	IIAC	110.50 MHz	18 nm	269.99	-	680 ft
				33 km	274.10		680 m
27R	LOC-ILS	IABU	111.75 MHz	18 nm	270.00	-	680 ft
				33 km	274.11		680 m
28L	LOC-ILS	IVQX	110.75 MHz	18 nm	269.87	-	680 ft
				33 km	273.98		680 m
28C	LOC-ILS	IVZE	108.95 MHz	18 nm	269.87	-	680 ft
				33 km	273.98		680 m
28R	LOC-ILS	ITSL	111.10 MHz	18 nm	269.88	-	680 ft
				33 km	273.99		680 m
04R	GS	IFJU	110.10 MHz	10 nm	41.41	3.00	680 ft
				19 km	45.52		680 m
09L	GS	ISAJ	111.75 MHz	10 nm	90.00	3.00	680 ft
				19 km	94.11		680 m
09R	GS	IJAV	110.50 MHz	10 nm	89.99	3.00	680 ft
				19 km	94.10		680 m
10L	GS	IMED	111.10 MHz	10 nm	89.89	3.00	680 ft
				19 km	94.00		680 m
10C	GS	ISXH	108.95 MHz	10 nm	89.86	3.00	680 ft
				19 km	93.97		680 m
10R	GS	IIZJ	110.75 MHz	10 nm	89.86	3.00	680 ft
				19 km	93.97		680 m
22L	GS	ILQQ	110.10 MHz	10 nm	221.41	3.00	680 ft
				19 km	225.52		680 m
27L	GS	IIAC	110.50 MHz	10 nm	269.99	3.00	680 ft
				19 km	274.10		680 m
27R	GS	IABU	111.75 MHz	10 nm	270.00	3.00	680 ft
				19 km	274.11		680 m
28L	GS	IVQX	110.75 MHz	10 nm	269.87	3.00	680 ft
				19 km	273.98		680 m
28C	GS	IVZE	108.95 MHz	10 nm	269.87	3.00	680 ft
				19 km	273.98		680 m
28R	GS	ITSL	111.10 MHz	10 nm	269.88	3.00	680 ft
				19 km	273.99		680 m