
EIDW – KATL

Dublin — Hartsfield Jackson Atlanta Intl

2024/03/19 0520Z

EIDW RINUS **UL975** DEVOL **UN544** DOGAL **B** DOTTY **N111B** TOPPS **J581** BGR **J80** BAF **J77** SAX **J6** BWZ **J77** PTW **J48** ODF KATL

3427.24 nm / 6347.24 km



Notes

Using NAT tracks from 15/5/2014
Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EIDW APT	-	53.42826 -6.25955	0 ft 0 m	-	Dublin
RINUS FIX	-	53.64417 -7.66222	18,400 ft 5,608 m	51	-
DEVOL FIX	UL975 AWY-HI	53.89028 -10.43417	34,000 ft 10,363 m	99	-
BABAN FIX	UN544 AWY-HI	54.00000 -12.00000	34,000 ft 10,363 m	55	-
DOGAL FIX	UN544 AWY-HI	54.00000 -15.00000	34,000 ft 10,363 m	105	-
54/20 LATLON	B NAT	54.00000 -20.00000	35,000 ft 10,668 m	176	-
54/30 LATLON	B NAT	54.00000 -30.00000	35,000 ft 10,668 m	352	-
54/40 LATLON	B NAT	54.00000 -40.00000	35,000 ft 10,668 m	352	-
52/50 LATLON	B NAT	52.00000 -50.00000	35,000 ft 10,668 m	380	-
CRONO FIX	B NAT	51.37917 -52.71389	35,000 ft 10,668 m	107	-
DOTTY FIX	B NAT	50.63334 -55.58333	35,000 ft 10,668 m	117	-
TOPPS FIX	N111B AWY-HI	45.34018 -67.73864	34,000 ft 10,363 m	581	-
BGR VOR	J581 AWY-HI	44.84181 -68.87397	34,000 ft 10,363 m	56	BANGOR VORTAC
BAF VOR	J80 AWY-HI	42.16197 -72.71619	34,000 ft 10,363 m	232	BARNES VORTAC
BIGGO FIX	J77 AWY-HI	41.95581 -73.06794	30,000 ft 9,144 m	19	-
GANDE FIX	J77 AWY-HI	41.51018 -73.81445	30,000 ft 9,144 m	42	-
SAX VOR	J77 AWY-HI	41.06756 -74.53831	30,000 ft 9,144 m	42	SPARTA VORTAC
BWZ VOR	J6 AWY-HI	40.79844 -74.82183	34,000 ft 10,363 m	20	BROADWAY VOR-DME
PTW VOR	J77 AWY-HI	40.22225 -75.56025	34,000 ft 10,363 m	48	POTTSTOWN VORTAC
BYRDD FIX	J48 AWY-HI	40.09220 -75.81869	34,000 ft 10,363 m	14	-
HAAGN FIX	J48 AWY-HI	39.96150 -76.07620	34,000 ft 10,363 m	14	-
PENSY FIX	J48 AWY-HI	39.90721 -76.18254	34,000 ft 10,363 m	5	-
EMI VOR	J48 AWY-HI	39.49500 -76.97858	34,000 ft 10,363 m	44	WESTMINSTER VORTAC
CSN VOR	J48 AWY-HI	38.64119 -77.86550	34,000 ft 10,363 m	65	CASANOVA VORTAC
MOL VOR	J48 AWY-HI	37.90053 -79.10689	34,000 ft 10,363 m	73	MONTEBELLO VOR-DME
JOINN FIX	J48 AWY-HI	37.01776 -80.31628	34,000 ft 10,363 m	78	-
ODF	J48	34.69586	18,100 ft	201	FOOTHILLS VORTAC

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
VOR	AWY-HI	-83.29767	5,517 m		
KATL	-	33.63662	0 ft	84	Hartsfield Jackson Atlanta Intl
APT	-	-84.42821	0 m		

EIDW

Region: IRELAND
Timezone: EUROPE/DUBLIN
Runways: 2

Elevation: 240 ft / 73 m
Location: 53.424900 -6.263080
Magnetic Var: 1.999 W

METAR

EIDW 190500Z 23006KT 190V280 9999 FEW012 BKN022 09/06 Q1006 NOSIG

TAF

TAF AMD EIDW 190107Z 1901/1924 24010KT 9999 FEW012 BKN020 PROB30 TEMPO 1901/1909 -SHRA BKN012 BECMG 1914/1916 VRB

Frequencies

REC - 124.52 MHz - ATIS
GND - 118.75 MHz - DUBLIN GROUND
CLD - 121.87 MHz - CLEARANCE DELIVERY
APP - 121.10 MHz - DUBLIN APPROACH
APP - 119.55 MHz - DUBLIN APPROACH

TWR - 118.60 MHz - DUBLIN TOWER
GND - 121.80 MHz - DUBLIN GROUND
APP - 133.27 MHz - DUBLIN APPROACH
APP - 119.92 MHz - DUBLIN APPROACH
REC - 118.50 MHz - DUBLIN INFORMATION

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10R	148 ft 45 m	8,660 ft 2,640 m	95.26 97.26	ASPHALT	0 ft 0 m	0 ft 0 m
28L	148 ft 45 m	8,660 ft 2,640 m	275.29 277.29	ASPHALT	0 ft 0 m	0 ft 0 m
16	190 ft 58 m	6,805 ft 2,074 m	156.64 158.64	ASPHALT	0 ft 0 m	0 ft 0 m
34	190 ft 58 m	6,805 ft 2,074 m	336.65 338.65	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	DME	IAC	111.50 MHz	18 nm 33 km	- -	-	200 ft 200 m
10R	LOC-ILS	IDE	108.90 MHz	18 nm 33 km	95.26 97.26	-	242 ft 242 m
16	LOC-ILS	IAC	111.50 MHz	18 nm 33 km	156.64 158.64	-	242 ft 242 m
28L	LOC-ILS	IDW	111.35 MHz	18 nm 33 km	275.26 277.26	-	242 ft 242 m
10R	GS	IDE	108.90 MHz	10 nm 19 km	95.26 97.26	3.00	242 ft 242 m
16	GS	IAC	111.50 MHz	10 nm 19 km	156.64 158.64	3.00	242 ft 242 m
28L	GS	IDW	111.35 MHz	10 nm 19 km	275.26 277.26	3.00	242 ft 242 m

KATL

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 5

Elevation: 1,026 ft / 313 m
Location: 33.636600 -84.428000
Magnetic Var: 5.618 W

METAR

KATL 190452Z 32013KT 10SM CLR 04/M10 A3013 RMK AO2 SLP206 T00441100 401610044 $

TAF

TAF AMD KATL 190353Z 1904/2006 32012G22KT P6SM SKC FM191000 32008KT P6SM SKC FM191700 27010KT P6SM SKC

Frequencies

REC - 119.65 MHz - D-ATIS
COM - 122.95 MHz - UNICOM
GND - 121.65 MHz - ATLANTA GROUND
GND - 121.90 MHz - ATLANTA GROUND
TWR - 119.30 MHz - ATLANTA TOWER
TWR - 123.85 MHz - ATLANTA TOWER
APP - 127.90 MHz - ATLANTA APPROACH
DEP - 125.65 MHz - ATLANTA DEPARTURE
DEP - 135.37 MHz - ATLANTA DEPARTURE

REC - 125.55 MHz - D-ATIS
CLD - 118.10 MHz - CLEARANCE DELIVERY
GND - 121.75 MHz - ATLANTA GROUND
TWR - 119.10 MHz - ATLANTA TOWER
TWR - 119.50 MHz - ATLANTA TOWER
TWR - 125.32 MHz - ATLANTA TOWER
APP - 128.00 MHz - ATLANTA APPROACH
DEP - 125.70 MHz - ATLANTA DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09L	151 ft 46 m	12,400 ft 3,780 m	89.99 95.61	CONCRETE	0 ft 0 m	0 ft 0 m
27R	151 ft 46 m	12,400 ft 3,780 m	270.01 275.63	CONCRETE	518 ft 158 m	0 ft 0 m
09R	151 ft 46 m	9,008 ft 2,746 m	89.98 95.59	CONCRETE	0 ft 0 m	0 ft 0 m
27L	151 ft 46 m	9,008 ft 2,746 m	269.99 275.61	CONCRETE	0 ft 0 m	0 ft 0 m
08L	151 ft 46 m	9,008 ft 2,746 m	89.98 95.60	CONCRETE	0 ft 0 m	0 ft 0 m
26R	151 ft 46 m	9,008 ft 2,746 m	269.99 275.61	CONCRETE	0 ft 0 m	0 ft 0 m
10	151 ft 46 m	9,008 ft 2,746 m	89.97 95.59	CONCRETE	0 ft 0 m	0 ft 0 m
28	151 ft 46 m	9,008 ft 2,746 m	269.99 275.61	CONCRETE	0 ft 0 m	0 ft 0 m
08R	151 ft 46 m	10,009 ft 3,051 m	89.98 95.59	CONCRETE	0 ft 0 m	0 ft 0 m
26L	151 ft 46 m	10,009 ft 3,051 m	269.99 275.61	CONCRETE	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08L	DME	IHFW	109.30 MHz	18 nm 33 km	- -	-	993 ft 993 m
08R	DME	IATL	109.90 MHz	18 nm 33 km	- -	-	1,026 ft 1,026 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	IHZK	110.50 MHz	18 nm 33 km	– –	–	978 ft 978 m
09R	DME	IFUN	108.90 MHz	18 nm 33 km	– –	–	987 ft 987 m
10	DME	IOMO	111.55 MHz	18 nm 33 km	– –	–	970 ft 970 m
26L	DME	IBRU	108.70 MHz	18 nm 33 km	– –	–	1,026 ft 1,026 m
26R	DME	IGXZ	110.10 MHz	18 nm 33 km	– –	–	1,000 ft 1,000 m
27L	DME	IFSQ	108.50 MHz	18 nm 33 km	– –	–	1,020 ft 1,020 m
27R	DME	IAFA	111.30 MHz	18 nm 33 km	– –	–	978 ft 978 m
28	DME	IPKU	111.75 MHz	18 nm 33 km	– –	–	970 ft 970 m
08L	LOC-ILS	IHFW	109.30 MHz	18 nm 33 km	89.98 95.60	–	1,026 ft 1,026 m
08R	LOC-ILS	IATL	109.90 MHz	18 nm 33 km	89.99 95.61	–	1,026 ft 1,026 m
09L	LOC-ILS	IHZK	110.50 MHz	18 nm 33 km	90.01 95.63	–	968 ft 968 m
09R	LOC-ILS	IFUN	108.90 MHz	18 nm 33 km	89.98 95.60	–	1,026 ft 1,026 m
10	LOC-ILS	IOMO	111.55 MHz	18 nm 33 km	89.98 95.60	–	970 ft 970 m
26L	LOC-ILS	IBRU	108.70 MHz	18 nm 33 km	269.98 275.60	–	1,026 ft 1,026 m
26R	LOC-ILS	IGXZ	110.10 MHz	18 nm 33 km	269.98 275.60	–	1,026 ft 1,026 m
27L	LOC-ILS	IFSQ	108.50 MHz	18 nm 33 km	269.98 275.60	–	1,026 ft 1,026 m
27R	LOC-ILS	IAFA	111.30 MHz	18 nm 33 km	270.00 275.61	–	1,026 ft 1,026 m
28	LOC-ILS	IPKU	111.75 MHz	18 nm 33 km	269.97 275.59	–	970 ft 970 m
08L	GS	IHFW	109.30 MHz	10 nm 19 km	90.96 96.58	3.00	1,008 ft 1,008 m
08R	GS	IATL	109.90 MHz	10 nm 19 km	90.96 96.58	3.00	1,012 ft 1,012 m
09L	GS	IHZK	110.50 MHz	10 nm 19 km	90.02 95.64	3.00	1,017 ft 1,017 m
09R	GS	IFUN	108.90 MHz	10 nm 19 km	90.96 96.58	3.00	1,021 ft 1,021 m
10	GS	IOMO	111.55 MHz	10 nm 19 km	90.94 96.56	3.00	985 ft 985 m
26L	GS	IBRU	108.70 MHz	10 nm 19 km	270.96 276.58	3.00	992 ft 992 m
26R	GS	IGXZ	110.10 MHz	10 nm 19 km	270.96 276.58	3.00	984 ft 984 m
27L	GS	IFSQ	108.50 MHz	10 nm 19 km	270.96 276.58	3.00	990 ft 990 m
27R	GS	IAFA	111.30 MHz	10 nm 19 km	270.02 275.64	3.00	981 ft 981 m
28	GS	IPKU	111.75 MHz	10 nm 19 km	270.94 276.56	3.00	990 ft 990 m