WIPP
Sultan Mahmud Badaruddin II


-

WIDD
Batam Hang Nadim

2024/03/29 0808Z

WIPP PLB **G579** PARDI WIDD

245.74 nm / 455.12 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 30000ft
- Cruise Speed: 320kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
WIPP APT	–	-2.89742 104.69800	0 ft 0 m	–	Sultan Mahmud Badaruddin II
PLB VOR	–	-2.87859 104.65300	1,300 ft 396 m	2	PALEMBANG
PARDI FIX	G579 AWY-HI	-0.56667 104.21700	28,500 ft 8,687 m	141	–
WIDD APT	–	1.12095 104.11900	0 ft 0 m	101	Batam Hang Nadim

WIPP

Region: INDONESIA
Timezone: ASIA/JAKARTA
Runways: 1

Elevation: 48 ft / 15 m
Location: -2.897420 104.698000
Magnetic Var: 0.394 E

METAR

WIPP 290730Z 17006KT 130V230 9999 TS FEW010CB BKN010 29/25 Q1009 NOSIG

TAF

TAF TAF WIPP 290500Z 2906/3006 15008KT 9999 SCT010 TEMPO 2906/2910 3000 RA FEW010CB BKN010 TEMPO 2920/2924 2000 BR

Frequencies

TWR - 118.10 MHz - MAHMUD TOWER
REC - 127.20 MHz - ATIS

APP - 119.20 MHz - PALEMBANG RADAR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
11	148 ft 45 m	9,852 ft 3,003 m	112.87 112.48	ASPHALT	0 ft 0 m	187 ft 57 m
29	148 ft 45 m	9,852 ft 3,003 m	292.87 292.48	ASPHALT	0 ft 0 m	190 ft 58 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11	LOC-ILS	IPLM	111.10 MHz	18 nm 33 km	112.87 112.48	-	48 ft 48 m
29	LOC-ILS	IPLB	110.50 MHz	18 nm 33 km	292.87 292.48	-	48 ft 48 m
11	GS	IPLM	111.10 MHz	10 nm 19 km	112.87 112.48	3.00	48 ft 48 m
29	GS	IPLB	110.50 MHz	10 nm 19 km	292.87 292.48	3.00	48 ft 48 m

WIDD

Region: INDONESIA
Timezone: ASIA/JAKARTA
Runways: 1

Elevation: 123 ft / 37 m
Location: 1.120950 104.119000
Magnetic Var: 0.214 E

METAR

WIDD 290730Z 06010KT 9999 FEW014 32/24 Q1010 NOSIG

TAF

TAF WIDD 290500Z 2906/3006 07009KT 9999 SCT014=

Frequencies

REC - 126.25 MHz - ATIS
TWR - 118.30 MHz - HANG NADIM TOWER
APP - 130.20 MHz - TANJUNG PINANG APPROACH

GND - 121.95 MHz - HANG NADIM GROUND
TWR - 118.70 MHz - HANG NADIM TOWER
APP - 120.30 MHz - SINGAPORE APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04	148 ft 45 m	13,258 ft 4,041 m	41.35 41.14	ASPHALT	0 ft 0 m	207 ft 63 m
22	148 ft 45 m	13,258 ft 4,041 m	221.35 221.14	ASPHALT	0 ft 0 m	190 ft 58 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04	DME	IBTM	110.10 MHz	18 nm 33 km	- -	-	69 ft 69 m
04	LOC-ILS	IBTM	110.10 MHz	18 nm 33 km	41.35 41.14	-	123 ft 123 m
04	GS	IBTM	110.10 MHz	10 nm 19 km	41.35 41.14	3.00	123 ft 123 m