

KPHL

Philadelphia Intl


CYYZ

Toronto Lester B Pearson Intl

2024/05/03 1758Z

KPHL DIANO **V164** SFK **J220** ELZ **V164** BENEE CYYZ

304.09 nm / 563.18 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 30000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KPHL APT	-	39.87387 -75.23739	0 ft 0 m	-	Philadelphia Intl
DIANO FIX	-	41.00055 -76.22605	29,000 ft 8,839 m	81	-
FQM VOR	V164 AWY-LO	41.33856 -76.77486	35,000 ft 10,668 m	32	WILLIAMSPORT VOR-DME
SFK VOR	V164 AWY-LO	41.69525 -77.41992	33,100 ft 10,089 m	36	STONYFORK VOR-DME
ELZ VOR	J220 AWY-HI	42.08964 -77.99956	25,600 ft 7,803 m	35	WELLSVILLE VORTAC
BENEE FIX	V164 AWY-LO	42.51499 -78.32474	19,300 ft 5,883 m	29	-
CYYZ APT	-	43.67613 -79.62767	0 ft 0 m	90	Toronto Lester B Pearson Intl

KPHL

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 4

Elevation: 36 ft / 11 m
Location: 39.874100 -75.236800
Magnetic Var: 11.990 W

METAR

KPHL 031654Z 07011KT 10SM SCT025 SCT035 BKN080 BKN260 17/09 A3018 RMK A02 SLP219 T01670094

TAF

TAF AMD KPHL 031601Z 0316/0418 08012KT P6SM BKN020 FM031800 10010KT P6SM SCT015 BKN250 FM040400 08007KT P6SM BKN250

Frequencies

REC - 133.40 MHz - D-ATIS	REC - 135.92 MHz - D-ATIS
COM - 122.95 MHz - PHILADELPHIA UNICOM	GND - 121.65 MHz - PHILADELPHIA GROUND
GND - 121.90 MHz - PHILADELPHIA GROUND	TWR - 118.50 MHz - PHILADELPHIA TOWER
TWR - 135.10 MHz - PHILADELPHIA TOWER	CLD - 118.85 MHz - CLEARANCE DELIVERY
DEP - 119.75 MHz - PHILADELPHIA DEPARTURE	DEP - 124.35 MHz - PHILADELPHIA DEPARTURE
APP - 123.80 MHz - PHILADELPHIA APPROACH	APP - 124.35 MHz - PHILADELPHIA APPROACH
APP - 126.85 MHz - PHILADELPHIA APPROACH	APP - 127.35 MHz - PHILADELPHIA APPROACH
APP - 128.40 MHz - PHILADELPHIA APPROACH	APP - 133.87 MHz - PHILADELPHIA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09R	200 ft	11,981 ft	75.41	ASPHALT	0 ft	292 ft
	61 m	3,652 m	87.40		0 m	89 m
27L	200 ft	11,981 ft	255.44	ASPHALT	1,909 ft	397 ft
	61 m	3,652 m	267.43		582 m	121 m
09L	150 ft	9,482 ft	75.42	ASPHALT	0 ft	413 ft
	46 m	2,890 m	87.41		0 m	126 m
27R	150 ft	9,482 ft	255.44	ASPHALT	0 ft	397 ft
	46 m	2,890 m	267.43		0 m	121 m
17	150 ft	6,508 ft	159.13	ASPHALT	0 ft	200 ft
	46 m	1,984 m	171.12		0 m	61 m
35	150 ft	6,508 ft	339.14	ASPHALT	0 ft	200 ft
	46 m	1,984 m	351.13		0 m	61 m
08	150 ft	4,992 ft	75.44	ASPHALT	0 ft	197 ft
	46 m	1,521 m	87.43		0 m	60 m
26	150 ft	4,992 ft	255.45	ASPHALT	0 ft	0 ft
	46 m	1,521 m	267.44		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	IVII	108.95 MHz	18 nm	-	-	38 ft
				33 km	-		38 m
09R	DME	IPHL	109.30 MHz	18 nm	-	-	18 ft
				33 km	-		18 m
26	DME	ILLH	111.55 MHz	18 nm	-	-	38 ft
				33 km	-		38 m
27L	DME	IGLC	109.30 MHz	18 nm	-	-	38 ft
				33 km	-		38 m
27R	DME	IPDP	108.95 MHz	18 nm	-	-	38 ft
				33 km	-		38 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	LOC-ILS	IVII	108.95 MHz	18 nm	75.43	-	36 ft
				33 km	87.42		36 m
09R	LOC-ILS	IPHL	109.30 MHz	18 nm	75.43	-	36 ft
				33 km	87.42		36 m
17	LOC-ILS	IMMY	108.75 MHz	18 nm	159.14	-	36 ft
				33 km	171.13		36 m
27L	LOC-ILS	IGLC	109.30 MHz	18 nm	255.43	-	36 ft
				33 km	267.42		36 m
27R	LOC-ILS	IPDP	108.95 MHz	18 nm	255.43	-	36 ft
				33 km	267.42		36 m
09L	GS	IVII	108.95 MHz	10 nm	75.43	3.00	36 ft
				19 km	87.42		36 m
09R	GS	IPHL	109.30 MHz	10 nm	75.43	3.00	36 ft
				19 km	87.42		36 m
17	GS	IMMY	108.75 MHz	10 nm	159.14	3.00	36 ft
				19 km	171.13		36 m
27L	GS	IGLC	109.30 MHz	10 nm	255.43	3.00	36 ft
				19 km	267.42		36 m
27R	GS	IPDP	108.95 MHz	10 nm	255.43	3.00	36 ft
				19 km	267.42		36 m

CYYZ

Region: CANADA
Timezone: AMERICA/TORONTO
Runways: 5

Elevation: 564 ft / 172 m
Location: 43.676100 -79.627700
Magnetic Var: 10.261 W

METAR

CYYZ 031734Z 11005KT 15SM -RA OVC085 15/09 A3006 RMK AC8 SLP184

TAF

TAF CYYZ 031440Z 0315/0418 08012KT P6SM SCT050 BKN150 TEMPO 0315/0316 P6SM -SHRA BKN050 OVC150 FM031600 09012KT P

Frequencies

TWR - 118.35 MHz - TORONTO TOWER	TWR - 118.70 MHz - TORONTO TOWER
GND - 119.10 MHz - TORONTO GROUND	GND - 121.65 MHz - TORONTO GROUND
GND - 121.90 MHz - TORONTO GROUND	REC - 120.82 MHz - ATIS
REC - 133.10 MHz - ATIS	CLD - 121.30 MHz - CLEARANCE DELIVERY
APP - 132.80 MHz - TORONTO APPROACH	APP - 124.47 MHz - TORONTO APPROACH
APP - 125.40 MHz - TORONTO APPROACH	APP - 123.27 MHz - LONDON RADIO
DEP - 127.57 MHz - TORONTO DEPARTURE	DEP - 128.80 MHz - TORONTO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06L	197 ft	9,707 ft	46.43	ASPHALT	0 ft	131 ft
	60 m	2,959 m	56.69		0 m	40 m
24R	197 ft	9,707 ft	226.45	ASPHALT	194 ft	98 ft
	60 m	2,959 m	236.71		59 m	30 m
06R	197 ft	9,007 ft	46.43	ASPHALT	0 ft	95 ft
	60 m	2,745 m	56.69		0 m	29 m
24L	197 ft	9,007 ft	226.45	ASPHALT	0 ft	95 ft
	60 m	2,745 m	236.71		0 m	29 m
05	197 ft	11,128 ft	46.39	ASPHALT	141 ft	141 ft
	60 m	3,392 m	56.65		43 m	43 m
23	197 ft	11,128 ft	226.41	ASPHALT	492 ft	141 ft
	60 m	3,392 m	236.67		150 m	43 m
15L	197 ft	11,061 ft	136.64	ASPHALT	0 ft	92 ft
	60 m	3,372 m	146.90		0 m	28 m
33R	197 ft	11,061 ft	316.66	ASPHALT	0 ft	89 ft
	60 m	3,372 m	326.92		0 m	27 m
15R	197 ft	9,097 ft	136.62	ASPHALT	597 ft	0 ft
	60 m	2,773 m	146.88		182 m	0 m
33L	197 ft	9,097 ft	316.64	ASPHALT	591 ft	0 ft
	60 m	2,773 m	326.90		180 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24L	DME	IIDP	111.95 MHz	18 nm	-	-	568 ft
				33 km	-		568 m
24R	DME	INV	109.30 MHz	18 nm	-	-	546 ft
				33 km	-		546 m
05	LOC-ILS	ITX	109.70 MHz	18 nm	46.40	-	564 ft
				33 km	56.66		564 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	LOC-ILS	IJS	109.10 MHz	18 nm 33 km	46.44 56.70	-	564 ft 564 m
06R	LOC-ILS	ICV	111.95 MHz	18 nm 33 km	46.44 56.70	-	564 ft 564 m
15L	LOC-ILS	IRW	110.50 MHz	18 nm 33 km	136.65 146.91	-	564 ft 564 m
15R	LOC-ILS	ILP	110.95 MHz	18 nm 33 km	136.63 146.89	-	564 ft 564 m
23	LOC-ILS	IYZ	111.50 MHz	18 nm 33 km	226.40 236.66	-	564 ft 564 m
24L	LOC-ILS	IDP	111.95 MHz	18 nm 33 km	226.44 236.70	-	564 ft 564 m
24R	LOC-ILS	INV	109.30 MHz	18 nm 33 km	226.44 236.70	-	564 ft 564 m
33L	LOC-ILS	ITO	110.95 MHz	18 nm 33 km	316.63 326.89	-	564 ft 564 m
33R	LOC-ILS	ILE	110.30 MHz	18 nm 33 km	316.65 326.91	-	564 ft 564 m
05	GS	ITX	109.70 MHz	10 nm 19 km	46.40 56.66	3.00	564 ft 564 m
06L	GS	IJS	109.10 MHz	10 nm 19 km	46.44 56.70	3.00	564 ft 564 m
06R	GS	ICV	111.95 MHz	10 nm 19 km	46.44 56.70	3.00	564 ft 564 m
15L	GS	IRW	110.50 MHz	10 nm 19 km	136.65 146.91	3.00	564 ft 564 m
15R	GS	ILP	110.95 MHz	10 nm 19 km	136.63 146.89	3.00	564 ft 564 m
23	GS	IYZ	111.50 MHz	10 nm 19 km	226.40 236.66	3.00	564 ft 564 m
24L	GS	IIDP	111.95 MHz	10 nm 19 km	226.44 236.70	3.00	564 ft 564 m
24R	GS	INV	109.30 MHz	10 nm 19 km	226.44 236.70	3.00	564 ft 564 m
33L	GS	ITO	110.95 MHz	10 nm 19 km	316.63 326.89	3.00	564 ft 564 m
33R	GS	ILE	110.30 MHz	10 nm 19 km	316.65 326.91	3.00	564 ft 564 m