



Notes

Requested: KTUS KLUF

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KTUS	-	32.11690	0 ft	-	Tucson Intl
APT	-	-110.94200	0 m		
KLUF	-	33.53500	0 ft	111	Luke AFB
APT	-	-112.38300	0 m		

KTUS

Region: UNITED STATES
Timezone: AMERICA/PHOENIX
Runways: 3

Elevation: 2,643 ft / 806 m
Location: 32.116900 -110.942000
Magnetic Var: 9.196 E

METAR

KTUS 081753Z 28007KT 10SM CLR 27/M05 A2982 RMK A02 SLP053 T02721050 10278 20150 58009

TAF

KTUS 081722Z 0818/0918 24008KT P6SM SKC FM082000 27015G24KT P6SM SKC FM090300 27008KT P6SM SKC FM090800 14006KT P

Frequencies

REC - 123.80 MHz - ATIS	COM - 122.95 MHz - UNICOM
CLD - 126.65 MHz - CLNC DEL	GND - 124.40 MHz -
TWR - 119.00 MHz -	TWR - 118.30 MHz -
APP - 119.40 MHz - APP/DEP	APP - 125.10 MHz - APP/DEP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
11L	151 ft	11,008 ft	135.17	CONCRETE	0 ft	3,104 ft
	46 m	3,355 m	125.97		0 m	946 m
29R	151 ft	11,008 ft	315.18	CONCRETE	0 ft	1,017 ft
	46 m	3,355 m	305.99		0 m	310 m
11R	75 ft	8,417 ft	135.16	ASPHALT	1,404 ft	0 ft
	23 m	2,566 m	125.96		428 m	0 m
29L	75 ft	8,417 ft	315.17	ASPHALT	0 ft	0 ft
	23 m	2,566 m	305.97		0 m	0 m
03	151 ft	7,008 ft	44.91	CONCRETE	860 ft	0 ft
	46 m	2,136 m	35.71		262 m	0 m
21	151 ft	7,008 ft	224.92	CONCRETE	0 ft	197 ft
	46 m	2,136 m	215.72		0 m	60 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11L	DME	ITUS	111.70 MHz	25 nm	-	-	2,660 ft
				46 km	-		2,660 m
11L	LOC-ILS	ITUS	111.70 MHz	18 nm	135.18	-	2,660 ft
				33 km	125.98		2,660 m
11L	GS	ITUS	111.70 MHz	10 nm	135.33	3.00	2,600 ft
				19 km	126.14		2,600 m

KLUF

Region: UNITED STATES
Timezone: AMERICA/PHOENIX
Runways: 2

Elevation: 1,083 ft / 330 m
Location: 33.535000 -112.383000
Magnetic Var: 9.851 E

METAR

KLUF 081755Z AUTO 23005KT 10SM CLR 27/M02 A2973 RMK A02 SLP055 T02711018 10271 20188 58003 \$

TAF

TAF KLUF 081200Z 0812/0918 VRB06KT 9999 SKC QNH2968INS BECMG 0820/0821 23010G15KT 9999 SKC QNH2958INS TEMPO 0823/

Frequencies

REC - 134.92 MHz - ATIS
GND - 133.17 MHz - GROUND
APP - 120.70 MHz - APPROACH
CLD - 126.25 MHz - CLEARANCE DELIVERY
TWR - 119.10 MHz - TOWER

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03L	150 ft	10,019 ft	42.42	ASPHALT	0 ft	1,001 ft
	46 m	3,054 m	32.57		0 m	305 m
21R	150 ft	10,019 ft	222.44	ASPHALT	0 ft	1,001 ft
	46 m	3,054 m	212.59		0 m	305 m
03R	150 ft	9,909 ft	42.43	CONCRETE	0 ft	1,001 ft
	46 m	3,020 m	32.58		0 m	305 m
21L	150 ft	9,909 ft	222.45	CONCRETE	0 ft	1,050 ft
	46 m	3,020 m	212.60		0 m	320 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03R	LOC-ILS	ILUF	108.70 MHz	18 nm	42.44	-	1,086 ft
				33 km	32.59		1,086 m
21L	LOC-ILS	IEMJ	110.90 MHz	18 nm	222.43	-	1,072 ft
				33 km	212.58		1,072 m
03R	GS	ILUF	108.70 MHz	10 nm	42.88	3.00	1,069 ft
				19 km	33.03		1,069 m
21L	GS	IEMJ	110.90 MHz	10 nm	222.88	3.00	1,083 ft
				19 km	213.03		1,083 m