VTBS
Bangkok Suvarnabhumi Intl


-

VOMM
CHENNAI INTL

2024/03/28 0944Z

VTBS TANEK **R468** DWI **P762** PPB **P761** MMV VOMM

1244.81 nm / 2305.38 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
VTBS APT	–	13.68046 100.74751	0 ft 0 m	–	Bangkok Suvarnabhumi Intl
TANEK FIX	–	14.05153 98.97125	35,000 ft 10,668 m	105	–
DWI VOR	R468 AWY-LO	14.09819 98.19967	35,000 ft 10,668 m	45	DAWEI VOR-DME
LALIT FIX	P762 AWY-LO	12.87333 95.47667	35,000 ft 10,668 m	175	–
LULDA FIX	P762 AWY-LO	12.39742 94.41344	35,000 ft 10,668 m	68	–
LADER FIX	P762 AWY-LO	12.20000 94.04167	35,000 ft 10,668 m	24	–
PPB VOR	P762 AWY-LO	11.64967 92.74722	35,000 ft 10,668 m	82	PORT BLAIR VOR-DME
SADAP FIX	P761 AWY-LO	12.10156 88.68911	35,000 ft 10,668 m	240	–
IDASO FIX	P761 AWY-LO	12.65981 83.55639	35,000 ft 10,668 m	302	–
MMV VOR	P761 AWY-LO	12.99336 80.17069	0 ft 0 m	199	CHENNAI VOR-DME
VOMM APT	–	12.99386 80.17144	0 ft 0 m	0	CHENNAI INTL

VTBS

Region: THAILAND
Timezone: ASIA/BANGKOK
Runways: 2

Elevation: 4 ft / 1 m
Location: 13.680800 100.748000
Magnetic Var: 0.535 W

METAR

VTBS 280930Z 22009KT 190V250 9999 FEW020 33/21 Q1008 NOSIG

TAF

UNKNOWN

Frequencies

REC - 133.60 MHz - ATIS
TWR - 118.20 MHz - SUVARNABHUMI TOWER
GND - 121.65 MHz - SUVARNABHUMI GROUND
CLD - 135.80 MHz - BANGKOK CLEARANCE DELIVERY
CLD - 120.80 MHz - BANGKOK CLEARANCE DELIVERY
CLD - 133.80 MHz - BANGKOK CLEARANCE DELIVERY
APP - 125.20 MHz - BANGKOK ARRIVAL
APP - 120.30 MHz - BANGKOK APPROACH
APP - 121.70 MHz - BANGKOK ARRIVAL
APP - 133.60 MHz - SUVARNABHUMI ARRIVAL
APP - 133.40 MHz - SUVARNABHUMI ARRIVAL
TWR - 119.00 MHz - SUVARNABHUMI TOWER
GND - 121.95 MHz - SUVARNABHUMI GROUND
GND - 121.75 MHz - SUVARNABHUMI GROUND
CLD - 128.70 MHz - BANGKOK CLEARANCE DELIVERY
CLD - 125.80 MHz - DON MUEANG CLEARANCE DELIVERY
APP - 124.35 MHz - BANGKOK ARRIVAL
APP - 122.35 MHz - BANGKOK ARRIVAL
APP - 119.10 MHz - BANGKOK APPROACH
APP - 126.30 MHz - SUVARNABHUMI ARRIVAL
APP - 121.10 MHz - SUVARNABHUMI ARRIVAL
DEP - 119.25 MHz - SUVARNABHUMI DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01R	197 ft 60 m	13,189 ft 4,020 m	14.33 14.86	ASPHALT	0 ft 0 m	394 ft 120 m
19L	197 ft 60 m	13,189 ft 4,020 m	194.33 194.86	ASPHALT	0 ft 0 m	394 ft 120 m
01L	197 ft 60 m	12,201 ft 3,719 m	14.32 14.86	ASPHALT	0 ft 0 m	394 ft 120 m
19R	197 ft 60 m	12,201 ft 3,719 m	194.32 194.86	ASPHALT	0 ft 0 m	397 ft 121 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01L	DME	ISWS	109.10 MHz	18 nm 33 km	- -	-	5 ft 5 m
01R	DME	ISES	110.10 MHz	18 nm 33 km	- -	-	5 ft 5 m
19L	DME	ISEN	110.50 MHz	18 nm 33 km	- -	-	5 ft 5 m
19R	DME	ISWN	109.50 MHz	18 nm 33 km	- -	-	5 ft 5 m
01L	LOC-ILS	ISWS	109.10 MHz	18 nm 33 km	14.32 14.86	-	4 ft 4 m
01R	LOC-ILS	ISES	110.10 MHz	18 nm 33 km	14.33 14.87	-	4 ft 4 m
19L	LOC-ILS	ISEN	110.50 MHz	18 nm 33 km	194.33 194.87	-	4 ft 4 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
19R	LOC-ILS	ISWN	109.50 MHz	18 nm 33 km	194.32 194.86	-	4 ft 4 m
01L	GS	ISWS	109.10 MHz	10 nm 19 km	14.32 14.86	3.00	4 ft 4 m
01R	GS	ISES	110.10 MHz	10 nm 19 km	14.33 14.87	3.00	4 ft 4 m
19L	GS	ISEN	110.50 MHz	10 nm 19 km	194.33 194.87	3.00	4 ft 4 m
19R	GS	ISWN	109.50 MHz	10 nm 19 km	194.32 194.86	3.00	4 ft 4 m

VOMM

Region: INDIA
Timezone: ASIA/KOLKATA
Runways: 2

Elevation: 51 ft / 16 m
Location: 12.995100 80.169000
Magnetic Var: 0.786 W

METAR

VOMM 280930Z 14009KT 6000 FEW020 33/25 Q1009 NOSIG

TAF

TAF VOMM 280500Z 2806/2912 14010KT 6000 FEW020 SCT100 BECMG 2821/2822 29005KT 5000 BR BECMG 2900/2901 3000 BR BECM

Frequencies

REC - 127.45 MHz - ATIS
TWR - 118.10 MHz -
APP - 124.45 MHz -

GND - 121.90 MHz -
APP - 127.90 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07	148 ft 45 m	12,013 ft 3,661 m	68.92 69.71	ASPHALT	0 ft 0 m	476 ft 145 m
25	148 ft 45 m	12,013 ft 3,661 m	248.93 249.71	ASPHALT	0 ft 0 m	492 ft 150 m
12	148 ft 45 m	10,604 ft 3,232 m	117.74 118.52	ASPHALT	2,556 ft 779 m	0 ft 0 m
30	148 ft 45 m	10,604 ft 3,232 m	297.74 298.53	ASPHALT	1,135 ft 346 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07	DME	IMAS	110.30 MHz	18 nm 33 km	- -	-	52 ft 52 m
07	LOC-ILS	IMAS	110.30 MHz	18 nm 33 km	68.92 69.71	-	51 ft 51 m
25	LOC-ILS	ICHN	109.70 MHz	18 nm 33 km	248.92 249.71	-	51 ft 51 m
07	GS	IMAS	110.30 MHz	10 nm 19 km	68.92 69.71	3.00	51 ft 51 m
25	GS	ICHN	109.70 MHz	10 nm 19 km	248.92 249.71	3.00	51 ft 51 m