KMIA
Miami Intl


-

MMMX
Licenciado Benito Juarez Intl

2024/03/29 0549Z

KMIA JOVCU **B646** CANOA **UB646** ROBIN **UR522** NUBEL **UA509** NAU **UJ30** REXES MMMX

1136.58 nm / 2104.94 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 30000ft
- Cruise Speed: 315kts
- Descent Rate: 2000ft/min
- Descent Speed: 250kts

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KMIA APT	- -	25.79617 -80.28974	0 ft 0 m	-	Miami Intl
JOVCU FIX	- -	24.58333 -81.46667	30,000 ft 9,144 m	96	-
FIS NDB	B646 AWY-HI	24.54833 -81.78639	30,000 ft 9,144 m	17	FISH HOOK NDB
CANOA FIX	B646 AWY-HI	24.00044 -83.04982	30,000 ft 9,144 m	76	-
VINKA FIX	UB646 AWY-HI	23.20000 -84.80000	30,000 ft 9,144 m	107	-
LENUK FIX	UB646 AWY-HI	22.63333 -86.00000	30,000 ft 9,144 m	74	-
ROBIN FIX	UB646 AWY-HI	22.40041 -86.48307	30,000 ft 9,144 m	30	-
PARRA FIX	UR522 AWY-HI	22.24667 -87.64583	30,000 ft 9,144 m	65	-
EDGAR FIX	UR522 AWY-HI	22.17972 -88.12306	30,000 ft 9,144 m	26	-
IKURA FIX	UR522 AWY-HI	22.02637 -89.19519	30,000 ft 9,144 m	60	-
MESNA FIX	UR522 AWY-HI	21.95042 -89.70820	30,000 ft 9,144 m	28	-
LULIS FIX	UR522 AWY-HI	21.87528 -90.20417	30,000 ft 9,144 m	28	-
MARUS FIX	UR522 AWY-HI	21.81527 -90.59435	30,000 ft 9,144 m	22	-
AVTAS FIX	UR522 AWY-HI	21.74861 -91.01944	30,000 ft 9,144 m	24	-
MUNDA FIX	UR522 AWY-HI	21.59593 -91.96786	30,000 ft 9,144 m	53	-
NUBEL FIX	UR522 AWY-HI	21.01778 -95.28028	30,000 ft 9,144 m	188	-
NAU VOR	UA509 AWY-HI	20.19175 -96.74550	30,000 ft 9,144 m	96	NAUTLA VOR-DME
REXES FIX	UJ30 AWY-HI	19.91921 -97.56517	30,000 ft 9,144 m	49	-
MMMX APT	- -	19.43631 -99.07210	0 ft 0 m	90	Licenciado Benito Juarez Intl

KMIA

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 4

Elevation: 11 ft / 3 m
Location: 25.796200 -80.289700
Magnetic Var: 7.262 W

METAR

KMIA 290453Z 33006KT 10SM CLR 21/13 A3002 RMK AO2 SLP166 T02060133 403060206

TAF

KMIA 290258Z 2903/3006 33007KT P6SM SKC FM291400 03011G20KT P6SM FEW030 FM300000 05007KT P6SM SKC

Frequencies

REC - 119.15 MHz - D-ATIS
COM - 123.00 MHz - UNICOM
GND - 121.80 MHz - MIAMI GROUND
TWR - 118.30 MHz - MIAMI TOWER
APP - 120.50 MHz - MIAMI APPROACH
APP - 125.75 MHz - MIAMI APPROACH
DEP - 125.50 MHz - MIAMI DEPARTURE

REC - 133.67 MHz - D-ATIS
CLD - 135.35 MHz - CLEARANCE DELIVERY
GND - 127.50 MHz - MIAMI GROUND
TWR - 123.90 MHz - MIAMI TOWER
APP - 124.85 MHz - MIAMI APPROACH
DEP - 119.45 MHz - MIAMI DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	151 ft 46 m	13,027 ft 3,971 m	87.37 94.63	CONCRETE	1,371 ft 418 m	384 ft 117 m
27	151 ft 46 m	13,027 ft 3,971 m	267.39 274.65	CONCRETE	276 ft 84 m	374 ft 114 m
08R	200 ft 61 m	10,515 ft 3,205 m	87.38 94.64	CONCRETE	0 ft 0 m	407 ft 124 m
26L	200 ft 61 m	10,515 ft 3,205 m	267.39 274.65	CONCRETE	0 ft 0 m	407 ft 124 m
08L	151 ft 46 m	8,607 ft 2,624 m	87.38 94.64	CONCRETE	0 ft 0 m	387 ft 118 m
26R	151 ft 46 m	8,607 ft 2,624 m	267.39 274.65	CONCRETE	0 ft 0 m	387 ft 118 m
12	151 ft 46 m	9,366 ft 2,855 m	119.61 126.87	CONCRETE	0 ft 0 m	397 ft 121 m
30	151 ft 46 m	9,366 ft 2,855 m	299.62 306.88	CONCRETE	948 ft 289 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08L	DME	IROY	109.30 MHz	18 nm 33 km	- -	-	8 ft 8 m
08R	DME	IMFA	110.30 MHz	18 nm 33 km	- -	-	8 ft 8 m
12	DME	IGEM	108.90 MHz	18 nm 33 km	- -	-	14 ft 14 m
26L	DME	IVIN	109.10 MHz	18 nm 33 km	- -	-	12 ft 12 m
26R	DME	ICNV	109.30 MHz	18 nm 33 km	- -	-	8 ft 8 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
30	DME	IDCX	111.70 MHz	18 nm 33 km	- -	-	8 ft 8 m
08R	LOC-ILS	IMFA	110.30 MHz	18 nm 33 km	87.37 94.63	-	4 ft 4 m
09	LOC-ILS	IBUL	110.90 MHz	18 nm 33 km	87.37 94.63	-	4 ft 4 m
12	LOC-ILS	IGEM	108.90 MHz	18 nm 33 km	119.60 126.86	-	4 ft 4 m
26L	LOC-ILS	IVIN	109.10 MHz	18 nm 33 km	267.37 274.63	-	4 ft 4 m
27	LOC-ILS	IMIA	109.50 MHz	18 nm 33 km	267.37 274.63	-	4 ft 4 m
30	LOC-ILS	IDCX	111.70 MHz	18 nm 33 km	299.60 306.86	-	4 ft 4 m
08L	LOC-LOC	IROY	109.30 MHz	18 nm 33 km	87.36 94.62	-	4 ft 4 m
26R	LOC-LOC	ICNV	109.30 MHz	18 nm 33 km	267.36 274.62	-	4 ft 4 m
08R	GS	IMFA	110.30 MHz	10 nm 19 km	87.37 94.63	3.00	4 ft 4 m
09	GS	IBUL	110.90 MHz	10 nm 19 km	87.37 94.63	3.00	4 ft 4 m
12	GS	IGEM	108.90 MHz	10 nm 19 km	119.60 126.86	3.00	4 ft 4 m
26L	GS	IVIN	109.10 MHz	10 nm 19 km	267.37 274.63	3.00	4 ft 4 m
27	GS	IMIA	109.50 MHz	10 nm 19 km	267.37 274.63	3.00	4 ft 4 m
30	GS	IDCX	111.70 MHz	10 nm 19 km	299.60 306.86	3.00	4 ft 4 m

MMMX

Region: MEXICO
Timezone: AMERICA/MEXICO_CITY
Runways: 2

Elevation: 7,315 ft / 2,230 m
Location: 19.436300 -99.072100
Magnetic Var: 3.916 E

METAR

MMMX 290450Z 08003KT 7SM SKC 15/05 A3038 NOSIG RMK HZY

TAF

TAF MMMX 282253Z 2900/3000 10010KT 6SM HZ SKC TX28/2921Z TN11/2913Z TEMPO 2900/2904 16015KT FM290400 02005KT P6SM

Frequencies

REC - 127.65 MHz - D-ATIS
GND - 121.85 MHz - MEXICO GROUND
GND - 122.80 MHz - MEXICO GROUND
TWR - 118.70 MHz - MEXICO TOWER
APP - 119.75 MHz - MEXICO APPROACH
DEP - 129.10 MHz - MEXICO DEPARTURE

CLD - 122.10 MHz - CLEARANCE DELIVERY
GND - 121.00 MHz - MEXICO GROUND
TWR - 118.55 MHz - MEXICO TOWER
TWR - 118.15 MHz - MEXICO TOWER
APP - 121.20 MHz - MEXICO APPROACH
DEP - 120.50 MHz - MEXICO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05R	148 ft 45 m	13,427 ft 4,093 m	59.24 55.32	ASPHALT	1,841 ft 561 m	325 ft 99 m
23L	148 ft 45 m	13,427 ft 4,093 m	239.25 235.33	ASPHALT	289 ft 88 m	0 ft 0 m
05L	148 ft 45 m	12,912 ft 3,936 m	59.25 55.33	ASPHALT	1,568 ft 478 m	0 ft 0 m
23R	148 ft 45 m	12,912 ft 3,936 m	239.26 235.34	ASPHALT	1,670 ft 509 m	177 ft 54 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05R	DME	IMWX	109.10 MHz	18 nm 33 km	- -	-	7,316 ft 7,316 m
23L	DME	IMEX	109.70 MHz	18 nm 33 km	- -	-	7,316 ft 7,316 m
05R	LOC-ILS	IMWX	109.10 MHz	18 nm 33 km	59.25 55.33	-	7,315 ft 7,315 m
23L	LOC-ILS	IMEX	109.70 MHz	18 nm 33 km	239.25 235.33	-	7,315 ft 7,315 m
05R	GS	IMWX	109.10 MHz	10 nm 19 km	59.25 55.33	3.00	7,315 ft 7,315 m
23L	GS	IMEX	109.70 MHz	10 nm 19 km	239.25 235.33	3.00	7,315 ft 7,315 m