LIPZ
Venezia Tessera


-

LIRN
Naples Capodichino

2024/03/19 0114Z

LIPZ LANLI **L612** ANC **L982** PES LIRN

294.13 nm / 544.73 km



Notes

Basic altitude profile:
- Ascent Rate: 1800ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1800ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LIPZ APT	–	45.50479 12.34969	0 ft 0 m	–	Venezia Tessera
LANLI FIX	–	43.95722 13.18056	35,000 ft 10,668 m	99	–
ANC VOR	L612 AWY-LO	43.58639 13.47111	35,000 ft 10,668 m	25	ANCONA VOR-DME
ERDUX FIX	L982 AWY-LO	43.25083 13.68222	31,400 ft 9,571 m	22	–
PES VOR	L982 AWY-LO	42.43611 14.18444	19,900 ft 6,066 m	53	PESCARA VOR-DME
LIRN APT	–	40.88603 14.29078	0 ft 0 m	93	Naples Capodichino

LIPZ

Region: ITALY
Timezone: EUROPE/ROME
Runways: 2

Elevation: 4 ft / 1 m
Location: 45.504800 12.349700
Magnetic Var: 3.889 E

METAR

LIPZ 190050Z 27003KT 0100 R04R/0275N FG VV001 10/10 Q1015 NOSIG

TAF

TAF LIPZ 182300Z 1900/2006 VRB05KT 0200 FG NSC BECMG 1907/1910 6000

Frequencies

REC - 128.65 MHz - ATIS
TWR - 120.20 MHz - VENEZIA TOWER
APP - 118.25 MHz - VENEZIA APPROACH
GND - 121.70 MHz - VENEZIA GROUND
APP - 118.90 MHz - VENEZIA APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04R	148 ft 45 m	10,836 ft 3,303 m	42.03 38.14	ASPHALT	0 ft 0 m	0 ft 0 m
22L	148 ft 45 m	10,836 ft 3,303 m	222.05 218.16	ASPHALT	0 ft 0 m	0 ft 0 m
04L	148 ft 45 m	9,129 ft 2,782 m	42.03 38.14	ASPHALT	318 ft 97 m	0 ft 0 m
22R	148 ft 45 m	9,129 ft 2,782 m	222.05 218.16	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04R	DME	VTS	109.95 MHz	18 nm 33 km	- -	-	26 ft 26 m
04R	LOC-ILS	VTS	109.95 MHz	18 nm 33 km	42.04 38.15	-	4 ft 4 m
04R	GS	VTS	109.95 MHz	10 nm 19 km	42.04 38.15	3.00	4 ft 4 m

LIRN

Region: ITALY
Timezone: EUROPE/ROME
Runways: 1

Elevation: 292 ft / 89 m
Location: 40.886000 14.290800
Magnetic Var: 3.947 E

METAR

LIRN 190050Z 21005KT 9999 SCT020 14/12 Q1013 NOSIG

TAF

TAF LIRN 182300Z 1900/1924 20006KT 9999 BKN020 BECMG 1909/1911 05013KT BECMG 1921/1923 VRB05KT

Frequencies

APP - 124.35 MHz - NAPOLI APPROACH
TWR - 118.50 MHz - NAPOLI TOWER
REC - 135.97 MHz - ATIS

APP - 120.95 MHz - NAPOLI APPROACH
GND - 121.90 MHz - NAPOLI GROUND

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	148 ft 45 m	8,630 ft 2,630 m	58.04 54.09	ASPHALT	1,312 ft 400 m	217 ft 66 m
24	148 ft 45 m	8,630 ft 2,630 m	238.05 234.11	ASPHALT	607 ft 185 m	230 ft 70 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	DME	NPC	110.15 MHz	25 nm 46 km	- -	-	294 ft 294 m
24	DME	INPL	109.50 MHz	25 nm 46 km	- -	-	250 ft 250 m
06	LOC-ILS	NPC	110.15 MHz	18 nm 33 km	58.08 54.13	-	292 ft 292 m
24	LOC-ILS	INPL	109.50 MHz	18 nm 33 km	238.03 234.08	-	288 ft 288 m
24	LOC-ILS	INP	109.50 MHz	18 nm 33 km	238.08 234.13	-	292 ft 292 m
24	GS	INPL	109.50 MHz	10 nm 19 km	238.06 234.11	3.33	250 ft 250 m
24	GS	INP	109.50 MHz	10 nm 19 km	238.08 234.13	3.33	292 ft 292 m