


2024/05/18 0236Z

ESSA TORVA ESOE

91.50 nm / 169.46 km



Notes

Basic altitude profile:

- Ascent Rate: 3000ft/min
- Ascent Speed: 200kts
- Cruise Altitude: 35000ft
- Cruise Speed: 280kts
- Descent Rate: 1000ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
ESSA	-	59.65190	0 ft	-	Stockholm Arlanda
APT	-	17.91860	0 m		
TORVA	-	59.41240	8,000 ft	53	-
FIX	-	16.21200	2,438 m		
ESOE	-	59.22810	0 ft	37	Orebro
APT	-	15.04000	0 m		

ESSA

Region: SWEDEN
Timezone: EUROPE/STOCKHOLM
Runways: 3

Elevation: 138 ft / 42 m
Location: 59.651900 17.918600
Magnetic Var: 7.125 E

METAR

ESSA 180220Z 07002KT CAVOK 06/04 Q1020 NOSIG

TAF

TAF ESSA 180230Z 1803/1903 16002KT CAVOK BECMG 1810/1812 22010KT BECMG 1822/1824 VRB02KT

Frequencies

REC - 119.00 MHz - ATIS	REC - 121.62 MHz - ATIS
APP - 123.75 MHz - STOCKHOLM CONTROL APPROACH	APP - 120.15 MHz - STOCKHOLM CONTROL APPROACH
APP - 126.65 MHz - STOCKHOLM CONTROL APPROACH	DEP - 123.75 MHz - STOCKHOLM CONTROL DEPARTURE
DEP - 120.15 MHz - STOCKHOLM CONTROL DEPARTURE	DEP - 126.65 MHz - STOCKHOLM CONTROL DEPARTURE
TWR - 118.50 MHz - ARLANDA TOWER	TWR - 125.12 MHz - ARLANDA TOWER
TWR - 128.72 MHz - ARLANDA TOWER	TWR - 123.10 MHz - ARLANDA TOWER
GND - 121.70 MHz - ARLANDA GROUND	GND - 121.97 MHz - ARLANDA GROUND
GND - 121.92 MHz - ARLANDA GROUND	CLD - 121.82 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01L	148 ft	10,817 ft	10.38	ASPHALT	0 ft	154 ft
	45 m	3,297 m	3.25		0 m	47 m
19R	148 ft	10,817 ft	190.38	ASPHALT	0 ft	164 ft
	45 m	3,297 m	183.26		0 m	50 m
01R	148 ft	8,151 ft	10.38	ASPHALT	0 ft	223 ft
	45 m	2,484 m	3.25		0 m	68 m
19L	148 ft	8,151 ft	190.38	ASPHALT	0 ft	0 ft
	45 m	2,484 m	183.26		0 m	0 m
08	148 ft	8,180 ft	75.84	ASPHALT	0 ft	161 ft
	45 m	2,493 m	68.72		0 m	49 m
26	148 ft	8,180 ft	255.88	ASPHALT	0 ft	161 ft
	45 m	2,493 m	248.75		0 m	49 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01L	LOC-ILS	SSA	109.90 MHz	18 nm	10.38	-	138 ft
				33 km	3.25		138 m
01R	LOC-ILS	TSA	109.35 MHz	18 nm	10.38	-	138 ft
				33 km	3.25		138 m
19L	LOC-ILS	USA	111.35 MHz	18 nm	190.38	-	138 ft
				33 km	183.25		138 m
19R	LOC-ILS	NSA	110.70 MHz	18 nm	190.38	-	138 ft
				33 km	183.25		138 m
26	LOC-ILS	ESA	110.10 MHz	18 nm	255.86	-	138 ft
				33 km	248.73		138 m
08	LOC-LOC	WSA	109.55 MHz	18 nm	75.86	-	138 ft
				33 km	68.73		138 m
01L	GS	SSA	109.90 MHz	10 nm	10.38	3.00	138 ft
				19 km	3.25		138 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01R	GS	TSA	109.35 MHz	10 nm	10.38	3.00	138 ft
				19 km	3.25		138 m
19L	GS	USA	111.35 MHz	10 nm	190.38	3.00	138 ft
				19 km	183.25		138 m
19R	GS	NSA	110.70 MHz	10 nm	190.38	3.00	138 ft
				19 km	183.25		138 m
26	GS	ESA	110.10 MHz	10 nm	255.86	3.00	138 ft
				19 km	248.73		138 m

ESOE

Region: SWEDEN
Timezone: EUROPE/STOCKHOLM
Runways: 1

Elevation: 187 ft / 57 m
Location: 59.228100 15.040000
Magnetic Var: 5.945 E

METAR

ESOE 180220Z AUTO 34004KT 9999 R01///// R19///// NCD 05/04 Q1020

TAF

UNKNOWN

Frequencies

TWR - 133.60 MHz -

TWR - 120.27 MHz -

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01	148 ft	8,521 ft	11.65	ASPHALT	0 ft	0 ft
	45 m	2,597 m	5.71		0 m	0 m
19	148 ft	8,521 ft	191.66	ASPHALT	0 ft	0 ft
	45 m	2,597 m	185.72		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01	DME	SOE	109.10 MHz	18 nm	-	-	188 ft
				33 km	-		188 m
01	LOC-ILS	SOE	109.10 MHz	18 nm	11.68	-	188 ft
				33 km	5.73		188 m
19	LOC-ILS	NOE	108.50 MHz	18 nm	191.74	-	188 ft
				33 km	185.80		188 m
01	GS	SOE	109.10 MHz	10 nm	12.32	3.00	188 ft
				19 km	6.37		188 m
19	GS	NOE	108.50 MHz	10 nm	192.32	3.00	188 ft
				19 km	186.37		188 m