EGLL
London Heathrow


-

ENZV
Stavanger Lufthavn Sola

2024/03/28 1649Z

EGLL BANEM **UN866** LEDBO **UM604** INBOB **M604** BUSOM **P603** KARLI **UP603** RIRUT ENZV

526.65 nm / 975.36 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
EGLL	–	51.47122	0 ft	–	London Heathrow
APT	–	-0.46098	0 m		
BANEM	–	52.33556	31,900 ft	89	–
FIX	–	1.50528	9,723 m		
LEDBO	UN866	52.54306	35,000 ft	25	–
FIX	AWY-HI	2.10222	10,668 m		
ENITO	UM604	52.80139	35,000 ft	20	–
FIX	AWY-HI	2.46750	10,668 m		
BEKMO	UM604	52.98611	35,000 ft	12	–
FIX	AWY-HI	2.61944	10,668 m		
OKAMA	UM604	53.17083	35,000 ft	12	–
FIX	AWY-HI	2.77278	10,668 m		
GIVPO	UM604	53.28611	35,000 ft	7	–
FIX	AWY-HI	2.86917	10,668 m		
ROKAN	UM604	53.66333	35,000 ft	25	–
FIX	AWY-HI	3.18889	10,668 m		
VENAS	UM604	54.30556	35,000 ft	41	–
FIX	AWY-HI	3.65222	10,668 m		
LARGA	UM604	54.86389	35,000 ft	37	–
FIX	AWY-HI	4.15333	10,668 m		
INPUT	UM604	55.30500	35,000 ft	31	–
FIX	AWY-HI	4.65139	10,668 m		
INBOB	UM604	55.60694	35,000 ft	21	–
FIX	AWY-HI	5.00000	10,668 m		
BUSOM	M604	55.94194	35,000 ft	24	–
FIX	AWY-LO	5.39472	10,668 m		
NAMIK	P603	56.38139	32,100 ft	26	–
FIX	AWY-LO	5.44083	9,784 m		
KARLI	P603	57.00000	24,200 ft	37	–
FIX	AWY-LO	5.50750	7,376 m		
RIRUT	UP603	57.63944	15,900 ft	38	–
FIX	AWY-HI	5.55111	4,846 m		
ENZV	–	58.88046	0 ft	74	Stavanger Lufthavn Sola
APT	–	5.63143	0 m		

EGLL

Region: UNITED KINGDOM
Timezone: EUROPE/LONDON
Runways: 2

Elevation: 83 ft / 25 m
Location: 51.471200 -0.460881
Magnetic Var: 0.360 E

METAR

EGLL 281620Z AUTO 20020G31KT 9999 SCT029 BKN035 BKN043 11/06 Q0977

TAF

TAF AMD EGLL 281232Z 2812/2918 18022G33KT 9999 BKN020 TEMPO 2812/2821 7000 SHRA RA PROB30 TEMPO 2812/2816 3000 +SH

Frequencies

REC - 128.07 MHz - HEATHROW INFORMATION
CLD - 121.97 MHz - HEATHROW DELIVERY
GND - 121.85 MHz - HEATHROW GROUND
TWR - 118.50 MHz - HEATHROW TOWER
TWR - 124.47 MHz - HEATHROW TOWER
APP - 120.40 MHz - HEATHROW DIRECTOR
APP - 125.62 MHz - HEATHROW RADAR
DEP - 120.52 MHz - HEATHROW DEPARTURE

REC - 121.92 MHz - HEATHROW INFORMATION
GND - 121.70 MHz - HEATHROW GROUND
GND - 121.90 MHz - HEATHROW GROUND
TWR - 118.70 MHz - HEATHROW TOWER
APP - 119.72 MHz - HEATHROW DIRECTOR
APP - 134.97 MHz - HEATHROW DIRECTOR
APP - 127.52 MHz - HEATHROW RADAR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09L	164 ft 50 m	12,770 ft 3,892 m	89.66 89.30	ASPHALT	1,007 ft 307 m	0 ft 0 m
27R	164 ft 50 m	12,770 ft 3,892 m	269.70 269.34	ASPHALT	0 ft 0 m	177 ft 54 m
09R	164 ft 50 m	11,975 ft 3,650 m	89.68 89.32	ASPHALT	1,004 ft 306 m	0 ft 0 m
27L	164 ft 50 m	11,975 ft 3,650 m	269.72 269.36	ASPHALT	0 ft 0 m	95 ft 29 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	IAA	110.30 MHz	18 nm 33 km	- -	-	89 ft 89 m
09R	DME	IBB	109.50 MHz	18 nm 33 km	- -	-	84 ft 84 m
27L	DME	ILL	109.50 MHz	18 nm 33 km	- -	-	84 ft 84 m
27R	DME	IRR	110.30 MHz	18 nm 33 km	- -	-	89 ft 89 m
09L	LOC-ILS	IAA	110.30 MHz	18 nm 33 km	89.68 89.32	-	83 ft 83 m
09R	LOC-ILS	IBB	109.50 MHz	18 nm 33 km	89.70 89.34	-	83 ft 83 m
27L	LOC-ILS	ILL	109.50 MHz	18 nm 33 km	269.70 269.34	-	83 ft 83 m
27R	LOC-ILS	IRR	110.30 MHz	18 nm 33 km	269.68 269.32	-	83 ft 83 m
09L	GS	IAA	110.30 MHz	10 nm 19 km	89.68 89.32	3.00	83 ft 83 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09R	GS	IBB	109.50 MHz	10 nm	89.70	3.00	83 ft
				19 km	89.34		83 m
27L	GS	ILL	109.50 MHz	10 nm	269.70	3.00	83 ft
				19 km	269.34		83 m
27R	GS	IRR	110.30 MHz	10 nm	269.68	3.00	83 ft
				19 km	269.32		83 m

ENZV

Region: NORWAY
Timezone: EUROPE/OSLO
Runways: 2

Elevation: 27 ft / 8 m
Location: 58.880300 5.631380
Magnetic Var: 2.165 E

METAR

ENZV 281620Z 36005KT 9000 -RA FEW006 BKN039 OVC048 07/06 Q0981 NOSIG

TAF

TAF ENZV 281100Z 2812/2912 01010KT 9999 -RA BKN030 TEMPO 2812/2820 RA BECMG 2814/2816 VRB05KT BECMG 2818/2820 BKN

Frequencies

REC - 126.00 MHz - ATIS
TWR - 118.35 MHz -
APP - 119.60 MHz - RADAR

GND - 121.75 MHz -
TWR - 122.10 MHz -
APP - 118.50 MHz - ARR

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
18	197 ft 60 m	8,176 ft 2,492 m	179.13 176.97	ASPHALT	0 ft 0 m	0 ft 0 m
36	197 ft 60 m	8,176 ft 2,492 m	359.13 356.97	ASPHALT	0 ft 0 m	0 ft 0 m
11	148 ft 45 m	8,022 ft 2,445 m	106.31 104.15	ASPHALT	322 ft 98 m	0 ft 0 m
29	148 ft 45 m	8,022 ft 2,445 m	286.35 284.18	ASPHALT	509 ft 155 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
11	DME	ZL	109.50 MHz	18 nm 33 km	- -	-	37 ft 37 m
36	DME	SL	111.35 MHz	18 nm 33 km	- -	-	79 ft 79 m
11	LOC-ILS	ZL	109.50 MHz	18 nm 33 km	106.33 104.17	-	27 ft 27 m
18	LOC-ILS	ZV	110.30 MHz	18 nm 33 km	179.13 176.97	-	27 ft 27 m
36	LOC-ILS	SL	111.35 MHz	18 nm 33 km	359.13 356.97	-	27 ft 27 m
11	GS	ZL	109.50 MHz	10 nm 19 km	106.33 104.17	3.00	27 ft 27 m
18	GS	ZV	110.30 MHz	10 nm 19 km	179.13 176.97	3.00	27 ft 27 m
36	GS	SL	111.35 MHz	10 nm 19 km	359.13 356.97	3.00	27 ft 27 m