


2024/05/03 0324Z

KSAN TRAHF TEBBY BOUBY SUTIE R0953 KLAX

107.02 nm / 198.20 km



Notes

Requested: KSAN SADME TRAHF TEBBY BOUBY SUTIE R0953 KLAX

Unmatched points: SADME

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KSAN	-	32.73356	0 ft	-	San Diego Intl
APT	-	-117.18966	0 m		
TRAHP	-	32.91005	0 ft	16	-
FIX	-	-117.42781	0 m		
TEBBY	-	33.92329	0 ft	65	-
FIX	-	-117.90967	0 m		
BOUBY	-	33.97443	0 ft	12	-
FIX	-	-118.16245	0 m		
SUTIE	-	33.96308	0 ft	5	-
FIX	-	-118.27489	0 m		
R0953	-	33.95019	0 ft	6	-
FIX	-	-118.40166	0 m		
KLAX	-	33.94313	0 ft	0	Los Angeles Intl
APT	-	-118.40892	0 m		

KSAN

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 1

Elevation: 17 ft / 5 m
Location: 32.733600 -117.190000
Magnetic Var: 10.971 E

METAR

KSAN 030251Z 26006KT 10SM OVC020 17/12 A2989 RMK A02 SLP122 T01720117 53003 \$

TAF

TAF AMD KSAN 030257Z 0303/0406 26006KT P6SM OVC020 FM030400 VRB04KT P6SM OVC016 FM031600 19005KT P6SM BKN021 FM031800 19005KT P6SM BKN021

Frequencies

REC - 134.80 MHz - LINDBERGH ATIS	CLD - 125.90 MHz - LINDBERGH CLEARANCE
GND - 123.90 MHz - LINDBERGH GROUND	TWR - 118.30 MHz - LINDBERGH TOWER
DEP - 119.60 MHz - SOCAL WEST DEPARTURE	DEP - 124.35 MHz - SOCAL EAST DEPARTURE
APP - 119.60 MHz - SOCAL WEST APPROACH	APP - 124.35 MHz - SOCAL EAST APPROACH

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	200 ft	9,388 ft	106.13	ASPHALT	1,004 ft	390 ft
	61 m	2,861 m	95.16		306 m	119 m
27	200 ft	9,388 ft	286.15	ASPHALT	1,811 ft	0 ft
	61 m	2,861 m	275.18		552 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09	DME	ISAN	111.55 MHz	18 nm	-	-	29 ft
				33 km	-		29 m
27	DME	IUBR	110.90 MHz	18 nm	-	-	26 ft
				33 km	-		26 m
09	LOC-ILS	ISAN	111.55 MHz	18 nm	106.14	-	17 ft
				33 km	95.17		17 m
27	LOC-LOC	IUBR	110.90 MHz	18 nm	286.14	-	17 ft
				33 km	275.17		17 m
09	GS	ISAN	111.55 MHz	10 nm	106.14	3.10	17 ft
				19 km	95.17		17 m

KLAX

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 4

Elevation: 125 ft / 38 m
Location: 33.943100 -118.409000
Magnetic Var: 11.443 E

METAR

KLAX 030253Z 27009KT 10SM FEW012 15/12 A2987 RMK AO2 SLP113 T01500122 55001 \$

TAF

TAF AMD KLAX 030226Z 0302/0406 25010KT P6SM SCT022 FM030300 26005KT P6SM BKN013 FM030400 VRB03KT P6SM OVC010 FM030500 25010KT P6SM SCT022

Frequencies

COM - 122.95 MHz - UNICOM	GND - 121.65 MHz - LOS ANGELES GROUND
GND - 121.75 MHz - LOS ANGELES GROUND	GND - 121.40 MHz - LOS ANGELES GROUND
TWR - 119.80 MHz - LOS ANGELES TOWER	TWR - 120.95 MHz - LOS ANGELES TOWER
TWR - 133.90 MHz - LOS ANGELES TOWER	REC - 133.80 MHz - D-ATIS
REC - 135.65 MHz - D-ATIS	APP - 124.90 MHz - SOCAL APPROACH
APP - 124.30 MHz - SOCAL APPROACH	APP - 124.50 MHz - SOCAL APPROACH
APP - 128.50 MHz - SOCAL APPROACH	DEP - 125.20 MHz - SOCAL DEPARTURE
DEP - 124.30 MHz - SOCAL DEPARTURE	CLD - 120.35 MHz - CLEARANCE DELIVERY

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft	11,106 ft	82.96	CONCRETE	0 ft	381 ft
	61 m	3,385 m	71.51		0 m	116 m
25L	200 ft	11,106 ft	262.98	CONCRETE	0 ft	381 ft
	61 m	3,385 m	251.53		0 m	116 m
07L	151 ft	12,935 ft	82.95	CONCRETE	846 ft	374 ft
	46 m	3,943 m	71.51		258 m	114 m
25R	151 ft	12,935 ft	262.98	CONCRETE	968 ft	197 ft
	46 m	3,943 m	251.53		295 m	60 m
06R	151 ft	10,896 ft	82.95	CONCRETE	551 ft	384 ft
	46 m	3,321 m	71.50		168 m	117 m
24L	151 ft	10,896 ft	262.97	CONCRETE	814 ft	384 ft
	46 m	3,321 m	251.52		248 m	117 m
06L	151 ft	8,936 ft	82.95	CONCRETE	0 ft	0 ft
	46 m	2,724 m	71.51		0 m	0 m
24R	151 ft	8,936 ft	262.96	CONCRETE	0 ft	285 ft
	46 m	2,724 m	251.52		0 m	87 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06L	DME	IUWU	108.50 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
06R	DME	IGPE	111.70 MHz	18 nm	-	-	120 ft
				33 km	-		120 m
07L	DME	IIAS	111.10 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
07R	DME	IMKZ	109.90 MHz	18 nm	-	-	103 ft
				33 km	-		103 m
24L	DME	IHQB	111.70 MHz	18 nm	-	-	133 ft
				33 km	-		133 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
24R	DME	IOSS	108.50 MHz	18 nm 33 km	- -	-	133 ft 133 m
25L	DME	ILAX	109.90 MHz	18 nm 33 km	- -	-	126 ft 126 m
25R	DME	ICFN	111.10 MHz	18 nm 33 km	- -	-	126 ft 126 m
06L	LOC-ILS	IUWU	108.50 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
06R	LOC-ILS	IGPE	111.70 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
07L	LOC-ILS	IIAS	111.10 MHz	18 nm 33 km	82.98 71.54	-	125 ft 125 m
07R	LOC-ILS	IMKZ	109.90 MHz	18 nm 33 km	82.97 71.53	-	125 ft 125 m
24L	LOC-ILS	IHQB	111.70 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
24R	LOC-ILS	IOSS	108.50 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25L	LOC-ILS	ILAX	109.90 MHz	18 nm 33 km	262.97 251.53	-	125 ft 125 m
25R	LOC-ILS	ICFN	111.10 MHz	18 nm 33 km	262.98 251.54	-	125 ft 125 m
06L	GS	IUWU	108.50 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
06R	GS	IGPE	111.70 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
07L	GS	IIAS	111.10 MHz	10 nm 19 km	82.98 71.54	3.00	125 ft 125 m
07R	GS	IMKZ	109.90 MHz	10 nm 19 km	82.97 71.53	3.00	125 ft 125 m
24L	GS	IHQB	111.70 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
24R	GS	IOSS	108.50 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25L	GS	ILAX	109.90 MHz	10 nm 19 km	262.97 251.53	3.00	125 ft 125 m
25R	GS	ICFN	111.10 MHz	10 nm 19 km	262.98 251.54	3.00	125 ft 125 m